

形名	社名	最大定格							順方向特性			逆方向特性			t _{rr} max			その他の特性等	外形		
		V _{RSM}	V _{RRM}	V _R	I _O	T条件	I _{FSM}	T条件	V _{Fmax}	測定条件		I _{Rmax}	測定条件		測定条件						
		(V)	(V)	(V)	(A)	(°C)	(A)	(°C)	(V)	I _F (A)	T(°C)	(mA)	V _R (V)	T(°C)	(ns)	I _F (A)	I _R (A)			dI _F /dt (A/μs)	
S5S4	新電元	45	40		5	110C	100	125j	0.55	5	25C	5	40	25C	110	5		5			14
S5S4M	新電元	45	40		5	114C	100	125j	0.55	5		3.5	40	25C	110	5		5			272A
S15S4	新電元	45	40		15	98C	300	125j	0.55	15	25C	15	40		150	15		10			41
S15S6	新電元	65	60		15	96c	300	125j	0.67	15	25c	10	60	25c							41
S30S4A	新電元	45	40		30	97C	600	125j	0.55	30	25C	20	40	25C	200	30		20			42
S30S6	新電元	65	60		30	95c	600	125j	0.67	30	25c	20	60	25c							42
S60S4	新電元	45	40		60	83C	850	125j	0.58	60	25C	40	40		225	50		20			42
S60S6	新電元	65	60		60	82c	850	125j	0.67	60	25c	40	60	25c							42
SB05-03C	三洋		30		0.5		5		0.55	0.5		0.03	15		10	0.1					610A
SB05-03Q	三洋		30		0.5		3		0.55	0.5		0.03	15		10	0.1					205A
SB05-05CP	三洋	55	50		0.5		5		0.55	0.5	0.05	25			10	0.1	0.1				610A
SB05-05NP	三洋	55	50		0.5		5		0.55	0.5	0.05	25			10	0.1	0.1				730G
SB05-05P	三洋	55	50		0.5		5		0.55	0.5	0.05	25			10	0.1	0.1				730G
SB05-09	三洋	95	90		0.5	60a	10		0.7	0.5	0.08	45			10	0.1	0.1				237
SB05-18M	三洋	190	180		0.5	26a	10	25j	0.85	0.5	0.06	90			20	0.1	0.1				64
SB07-03C	三洋	35	30		0.7		5		0.55	0.7	0.08	15			10	0.1	0.1				610A
SB07-03N	三洋	35	30		0.7		5		0.55	0.7	0.08	15			10	0.1	0.1				730G
SB07-03P	三洋	35	30		0.7		5		0.55	0.7	0.08	15			10	0.1	0.1				237
SB10-03A2	三洋	35	30		1	50a	40	25j	0.55	1	1	30			30	1		50			666
SB10-03A3	三洋	35	30		1	46a	40	25j	0.55	1	1	30			30	1		50			88E
SB10-04A3	三洋	45	40		1		30		0.55	1	0.8	40									88F
SB10-05	三洋	55	50		1		10		0.55	1	0.08	25			10	0.1	0.1				64
SB10-05A2	三洋	55	50		1	33a	25	25j	0.58	1	1	50			30	1		50			666
SB10-05A3	三洋	55	50		1	29a	25	25j	0.58	1	1	50			30	1		50			88E
SB10-05PCP	三洋	55	50		1		10		0.55	1	0.08	25			10	0.1	0.1				237
SB10-09F	三洋	95	90		1	119c	10		0.7	1	0.4	45			20	0.1	0.1				243C
SB10-09P	三洋	95	90		1		5		0.7	1	0.2	45			20	0.1					237
SB11-04HP	三洋	45	40		0.85		30	25j	0.55	1.1	1	40									485B
SB20-03B	三洋	35	30		2	113c	20		0.55	2	0.1	15			20	0.1	0.1				241C
SB20-03E	三洋	35	30		2	113c	20		0.55	2	0.1	15			20	0.1	0.1				242C
SB20-03P	三洋	35	30		2		20		0.55	2	0.1	15			20	0.1	0.1				237
SB20-05P	三洋	55	50		2	117c	20		0.55	2	0.7	25			20	0.3	0.3				243C
SB20-05P	三洋	55	50		2		10		0.55	2	0.2	25			20	0.3	0.3				237
SB20-05Z	三洋		50		2		20		0.55	2	0.2	25			20	0.3					563
SB30-03F	三洋	35	30		3	114c	30		0.55	3	0.7	15			30	0.3	0.3				243C
SB30-03P	三洋	35	30		3		10		0.55	3	0.2	15			30	0.3	0.3				237
SB30-03Z	三洋	35	30		3		20		0.55	3	0.2	15			30	0.3	0.3				563
SB803-04	富士電機	48	40		2	105c	100	125j	0.55	2	5	40									486C
SB803-06	富士電機	60	60		2	105c	60	125j	0.58	2	5	60									486C
SB803-09	富士電機	90	90		2	105c	60	125j	0.9	2	5	90									486C
SC802-02	富士電機		20		1.5	112c	50	125j	0.47	1	1	20									60
SC802-4	富士電機	48	40		1	115L	40	125j	0.55	1	2	40									485G
SC802-6	富士電機	60	60		1	111L	30	125j	0.58	1	2	60									485G
SC802-9	富士電機	100	90		1	110L	30	125j	0.85	1	1	90									485G
SE014	富士電機	45	40		1		10	125j	0.55	1	2	40			50	0.1	0.1				237

