

<p>5102</p> <p>5102-0-00-XX-00-00-33-0 Press-fit in .057 mounting hole</p>	<p>1502</p> <p>1502-0-00-XX-00-00-03-0 Press-fit in .057 mounting hole</p>	<p>2956-0</p> <p>2956-0-00-XX-00-00-03-0 Surface mount</p>	<p>2956-1</p> <p>2956-1-00-XX-00-00-03-0 Surface mount</p>
--	--	--	--

<p>8940</p> <p>8940-0-00-XX-00-00-03-0 Press-fit in .057 mounting hole</p>	<p>8876</p> <p>8876-0-00-XX-00-00-03-0 Press-fit in .057 mounting hole</p>	<p>0259/0286/1941</p> <p>02XX-0-00-XX-00-00-03-0 Press-fit in .057/.059 mounting hole</p>	<table border="1"> <thead> <tr> <th>Basic Part Number</th> <th>Length L</th> <th>Barb Dia. E</th> <th>Mounting Hole</th> </tr> </thead> <tbody> <tr> <td>0259-0</td> <td>.173</td> <td>.062</td> <td>.059</td> </tr> <tr> <td>0286-0</td> <td>.115</td> <td>.060</td> <td>.057</td> </tr> <tr> <td>1941-0</td> <td>.169</td> <td>.058</td> <td>.057</td> </tr> </tbody> </table>	Basic Part Number	Length L	Barb Dia. E	Mounting Hole	0259-0	.173	.062	.059	0286-0	.115	.060	.057	1941-0	.169	.058	.057
Basic Part Number	Length L	Barb Dia. E	Mounting Hole																
0259-0	.173	.062	.059																
0286-0	.115	.060	.057																
1941-0	.169	.058	.057																

<p>1938</p> <p>1938-0-00-XX-00-00-03-0 Press-fit in .057 mounting hole</p>	<p>1940</p> <p>1940-0-00-XX-00-00-03-0 Press-fit in .057 mounting hole</p>	<p>1942</p> <p>1942-0-00-XX-00-00-03-0 Press-fit in .057 mounting hole</p>	<p>3024</p> <p>3024-0-01-XX-00-00-03-0 Press-fit in .057 mounting hole</p>
--	--	--	--

<p>SPECIFICATIONS</p> <p>PIN MATERIAL: Brass Alloy 360, 1/2 Hard (Except Swage pins which are annealed)</p> <p>DIMENSION IN INCHES TOLERANCES ON: LENGTHS: ±.005 DIAMETERS: ±.002 ANGLES: ± 2°</p>	<p>ORDER CODE: XXXX - X - XX - XX - 00 - 00 - 0X - 0</p> <p>BASIC PART # →</p>	<p>SPECIFY PIN FINISH:</p> <p>01 200 μ" TIN/LEAD OVER NICKEL</p> <p>80 200 μ" TIN OVER NICKEL ◇</p> <p>15 10 μ" GOLD OVER NICKEL ◇</p> <p>21 20 μ" GOLD OVER NICKEL ◇</p> <p>34 50 μ" GOLD OVER NICKEL ◇</p>
--	--	--

