


## Catalog

- ▶ [Home](#)
- ▶ [Part Number Search](#)
- ▶ [Document Search](#)
- ▶ [CAD Model Search](#)
- ▶ [Text Search](#)
- ▶ [Alternate/Lead Free Part Search](#)
- ▶ [Multiple Part Comparison](#)
- ▶ [Alphabetical Search](#)
- ▶ [Brand Search](#)
- ▶ [Industry Product Search](#)
- ▶ [Product Type Search](#)
- ▶ [Product Family Search](#)
- ▶ [Competitor Cross Reference](#)
- ▶ [Lead Free Solutions](#)
- ▶ [Tool Search](#)
- ▶ [Help/Glossary](#)

## Sockets

## ↳ DIP Sockets

**AMP 528-AG11D**  [Active](#)  
**(Tyco Electronics P/N: 5-1437536-5)**

[Not ELV or RoHS Compliant](#)

[Search for Compliant \(Leadfree\)](#)

[Alternative](#)

[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

## Related Part Information

General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> <li>▶ <a href="#">General Info</a></li> <li>▶ <a href="#">Sales Info</a></li> <li>▶ <a href="#">Assembly Subcontractors</a></li> </ul>	<ul style="list-style-type: none"> <li>▶ <a href="#">Pricing</a></li> <li>▶ <a href="#">Product Availability</a></li> </ul>	<ul style="list-style-type: none"> <li>▶ <a href="#">Tooling</a></li> </ul>

**Photos & Line Drawings** - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)

## Searchable Features:

<b>Brand:</b>	AMP
<b>RoHS/ELV Compliance:</b>	Non-compliant
<b>Lead Free Solder Process:</b>	Reflow solder capable to 245Å°C
<b>Product Type:</b>	DIP Socket
<b>No. of Positions:</b>	28
<b>Row-to-Row Spacing (mm [in]):</b>	15.24 [0.600]
<b>Contact Mount:</b>	Thru Hole
<b>Mount Style:</b>	Vertical
<b>Centerline (mm [in]):</b>	2.54 [0.100]
<b>Profile:</b>	Standard

## Other Properties:

<b>Insulation Resistance (M©):</b>	5,000
<b>Contact Resistance (m©):</b>	10
<b>Sleeve Material:</b>	Brass/Copper
<b>Contact Termination Area Plating:</b>	Tin-Lead
<b>Product Series:</b>	500 Series

<b>Frame Style:</b>	Closed
<b>Leg Style:</b>	Straight
<b>Contact Material:</b>	Beryllium Copper
<b>Contact Mating Area Plating:</b>	Gold (25)
<b>Contact Style:</b>	Screw Machine
<b>Mating Contact Type:</b>	Four-Fingered
<b>Height Above PC Board (mm [in]):</b>	4.57 [0.180]
<b>Temperature Range (°C):</b>	125
<b>Packaging Method:</b>	Tube
<b>Termination Post Length (mm [in]):</b>	3.18 [0.125]

---

[Copyright](#) and [Privacy Statement](#)

Visit [Tyco International, Ltd.](#)

[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)