



EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DLE-532-009 REV: 1.0

3.2X4.3 mm Elliptical Wide Angle LEDs

MODEL NO : 5284SURD/S530-A4/S929 ECN : _____ Page: 2/4

■ Absolute Maximum Ratings at Ta = 25°C

Parameter	Symbol	Rating	Unit
Forward Current	IF	25	mA
Operating Temperature	Topr	-40 to +85	°C
Storage Temperature	Tstg	-40 to +100	°C
Soldering Temperature	Tsol	260 ± 5	°C
Electrostatic Discharge	ESD	2000	V
Power Dissipation	Pd	60	mW
Peak Forward Current(Duty 1/10 @ 1KHZ)	IF(Peak)	160	mA
Reverse Voltage	VR	5	V

■ Electronic Optical Characteristics :

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	Iv	163	250		mcd	IF=20mA
Viewing Angle	2θ 1/2		X:80 Y: 35	----	deg	IF=20mA
Peak Wavelength	λ p	----	632	----	nm	IF=20mA
Dominant Wavelength	λ d	----	624	----	nm	IF=20mA
Spectrum Radiation Bandwidth	△ λ	----	20	----	nm	IF=20mA
Forward Voltage	Vf		2.0	2.4	V	IF=20mA
Reverse Current	IR	----	----	10	μ A	VR=5V



EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DLE-528-009 REV: 1.0

3.2X4.3 mm Elliptical Wide Angle LEDs

MODEL NO : 5284SURD/S530-A4/S929 ECN : _____ Page: 3/4

■ Typical Electro-Optical Characteristic Curves



