



TO-220F Encapsulate Three-terminal Voltage Regulator

CJ7812F Three-terminal positive voltage regulator

FEATURES

Maximum Output current I_{OM} : 1.5 A


Output voltage V_o : 12 V

Continuous total dissipation

P_D : 2 W ($T_J = 25^\circ\text{C}$)

15 W ($T_C = 25^\circ\text{C}$)

TO-220F



1. IN

2. GND

3. OUT

ABSOLUTE MAXIMUM RATINGS(Operating temperature range applies unless otherwise specified)

Parameter	Symbol	Value	Unit
Input Voltage	V_i	35	V
Operating Junction Temperature Range	T_{OPR}	0-150	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-65-150	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS($V_i=19\text{V}, I_o=500\text{mA}, 0^\circ\text{C}<T_J<125^\circ\text{C}, C_i=0.33\mu\text{F}, C_o=0.1\mu\text{F}$, unless otherwise specified)

Parameter	Symbol	Test conditions	MIN	TYP	MAX	UNIT
Output voltage	V_o	$T_J=25^\circ\text{C}$	11.5	12.0	12.5	V
		$I_o=5.0\text{mA}-1.0\text{A}, P\leq 15\text{W}$ $14.5\text{V}\leq V_i\leq 27\text{V}$	11.4	12	12.6	V
Load Regulation	ΔV_o	$T_J=25^\circ\text{C}, 14.5\text{V}\leq V_i\leq 30\text{V}$		10	240	mV
		$T_J=25^\circ\text{C}, 16\text{V}\leq V_i\leq 22\text{V}$		3	120	mV
Line regulation	ΔV_o	$T_J=25^\circ\text{C}, I_o=5.0\text{mA}-1.5\text{A}$		11	240	mV
		$T_J=25^\circ\text{C}, I_o=250\text{mA}-750\text{mA}$		5.0	120	mV
Quiescent Current	I_q	$T_J=25^\circ\text{C}$		5.1	8	mA
Quiescent Current Change	ΔI_q	$5.0\text{mA}\leq I_o\leq 1.0\text{A}$			0.5	mA
		$14.5\text{V}\leq V_i\leq 30\text{V}$			1.0	mA
Output Noise Voltage	V_N	$f=10\text{Hz to }100\text{kHz}, T_J=25^\circ\text{C}$		76		μV
Ripple Rejection	RR	$f=120\text{Hz}, 15\text{V}\leq V_i\leq 25\text{V}$	55	71		dB
Dropout Voltage	V_d	$I_o=1.0\text{A}, T_J=25^\circ\text{C}$		2		V
Output resistance	R_o	$f=1\text{kHz}$		18		$\text{m}\Omega$
Short Circuit Current	I_{sc}	$V_i=35\text{V}, T_J=25^\circ\text{C}$		230		mA
Peak Current	I_{pk}	$T_J=25^\circ\text{C}$		2.2		A

TYPICAL APPLICATION

