




## N-Channel 60-V (D-S), 175 °C MOSFET

## PRODUCT SUMMARY

$V_{(BR)DSS}$ (V)	$r_{DS(on)}$ ( $\Omega$ )	$I_D$ (A)
60	0.018	60

**175 °C Rated**  
Maximum Junction Temperature  
**TrenchFET<sup>®</sup>**  
Power MOSFETs

TO-220AB




Top View

SUP60N06-18


DRAIN connected to TAB

TO-263



Top View

SUB60N06-18



N-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS ( $T_C = 25^\circ\text{C}$  UNLESS OTHERWISE NOTED)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	$V_{DS}$	60	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	
Continuous Drain Current ( $T_J = 175^\circ\text{C}$ )	$I_D$	$T_C = 25^\circ\text{C}$	60
		$T_C = 100^\circ\text{C}$	39
Pulsed Drain Current	$I_{DM}$	120	A
Avalanche Current	$I_{AR}$	60	
Repetitive Avalanche Energy <sup>a</sup>	$E_{AR}$	L = 0.1 mH	180
Power Dissipation			$T_C = 25^\circ\text{C}$ (TO-220AB and TO-263)
		$T_A = 25^\circ\text{C}$ (TO-263) <sup>c</sup>	3.7
Operating Junction and Storage Temperature Range	$T_J, T_{stg}$	-55 to 175	$^\circ\text{C}$

## THERMAL RESISTANCE RATINGS

Parameter	Symbol	Limit	Unit
Junction-to-Ambient	$R_{thJA}$	PCB Mount (TO-263) <sup>c</sup>	40
		Free Air (TO-220AB)	62.5
Junction-to-Case	$R_{thJC}$	1.25	$^\circ\text{C}/\text{W}$

## Notes:

- Duty cycle  $\leq 1\%$ .
- See SOA curve for voltage derating.
- When mounted on 1" square PCB (FR-4 material).

For SPICE model information via the Worldwide Web: <http://www.vishay.com/www/product/spice.htm>

## SUP/SUB60N06-18









Vishay Siliconix

SPECIFICATIONS (T <sub>J</sub> = 25 °C UNLESS OTHERWISE NOTED)						
Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
<b>Static</b>						
Drain-Source Breakdown Voltage	V <sub>(BR)DSS</sub>	V <sub>GS</sub> = 0 V, I <sub>D</sub> = 250 μA	60			V
Gate Threshold Voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>DS</sub> = 1 mA	2.0		4.0	
Gate-Body Leakage	I <sub>GSS</sub>	V <sub>DS</sub> = 0 V, V <sub>GS</sub> = ±20 V			±100	nA
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>DS</sub> = 60 V, V <sub>GS</sub> = 0 V			1	μA
		V <sub>DS</sub> = 60 V, V <sub>GS</sub> = 0 V, T <sub>J</sub> = 125 °C			50	
		V <sub>DS</sub> = 60 V, V <sub>GS</sub> = 0 V, T <sub>J</sub> = 175 °C			150	
On-State Drain Current <sup>a</sup>	I <sub>D(on)</sub>	V <sub>DS</sub> = 5 V, V <sub>GS</sub> = 10 V	60			A
Drain-Source On-State Resistance <sup>a</sup>	r <sub>DS(on)</sub>	V <sub>GS</sub> = 10 V, I <sub>D</sub> = 30 A		0.014	0.018	Ω
		V <sub>GS</sub> = 10 V, I <sub>D</sub> = 30 A, T <sub>J</sub> = 125 °C		0.024	0.030	
		V <sub>GS</sub> = 10 V, I <sub>D</sub> = 30 A, T <sub>J</sub> = 175 °C		0.031	0.036	
Forward Transconductance <sup>a</sup>	g <sub>fs</sub>	V <sub>DS</sub> = 15 V, I <sub>D</sub> = 30 A		49		S
<b>Dynamic<sup>b</sup></b>						
Input Capacitance	C <sub>iss</sub>	V <sub>GS</sub> = 0 V, V <sub>DS</sub> = 25 V, f = 1 MHz		2000		pF
Output Capacitance	C <sub>oss</sub>			400		
Reverse Transfer Capacitance	C <sub>rss</sub>			115		
Total Gate Charge <sup>c</sup>	Q <sub>g</sub>	V <sub>DS</sub> = 30 V, V <sub>GS</sub> = 10 V, I <sub>D</sub> = 60 A		39	60	nC
Gate-Source Charge <sup>c</sup>	Q <sub>gs</sub>			12		
Gate-Drain Charge <sup>c</sup>	Q <sub>gd</sub>			10		
Turn-On Delay Time <sup>c</sup>	t <sub>d(on)</sub>	V <sub>DD</sub> = 30 V, R <sub>L</sub> = 0.5 Ω I <sub>D</sub> = 60 A, V <sub>GEN</sub> = 10 V, R <sub>G</sub> = 2.5 Ω		12	30	ns
Rise Time <sup>c</sup>	t <sub>r</sub>			11	30	
Turn-Off Delay Time <sup>c</sup>	t <sub>d(off)</sub>			25	50	
Fall Time <sup>c</sup>	t <sub>f</sub>			15	30	
<b>Source-Drain Diode Ratings and Characteristics (T<sub>C</sub> = 25 °C)<sup>b</sup></b>						
Continuous Current	I <sub>s</sub>				60	A
Pulsed Current	I <sub>SM</sub>				120	
Forward Voltage <sup>a</sup>	V <sub>SD</sub>	I <sub>F</sub> = 60 A, V <sub>GS</sub> = 0 V			1.6	V
Reverse Recovery Time	t <sub>rr</sub>	I <sub>F</sub> = 60 A, di/dt = 100 A/μs		60		ns
Peak Reverse Recovery Current	I <sub>RM(REC)</sub>			6.0		A
Reverse Recovery Charge	Q <sub>rr</sub>			0.4		μC

## Notes:

- Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
- Guaranteed by design, not subject to production testing.
- Independent of operating temperature.




**TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)**


# SUP/SUB60N06-18

Vishay Siliconix



## TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)



## THERMAL RATINGS

