



|   |      |
|---|------|
| 1 | VSS  |
| 2 | VDD  |
| 3 | CS   |
| 4 | SID  |
| 5 | SCLK |
| 6 | /RST |
| 7 | LED+ |

NOTE:

1. DISPLAY TYPE: STN-Y/G-POSITIVE-TRANSPARENT
2. DRIVE METHOD: 1/32 DUTY, 1/5 BIAS, 7.5V Vop(typ.), 5V VDD
3. VIEWING DIR.: 6:00
4. OP. TEMP.: -20°C~70°C
5. ST. TEMP.: -40°C~85°C
7. BACKLIGHT: LED(white), VLED=5.0V, If<30mA 50CD/m<sup>2</sup>
8. DRIVER IC:ST7920

|           |            |             |               |                |              |
|-----------|------------|-------------|---------------|----------------|--------------|
| TOLERANCE | >0~6 ±0.10 | >6~80 ±0.20 | >80~240 ±0.30 | >240~400 ±0.50 | // L ∅ ±0.10 |
| DESIGN    | LI JINTANG | 05.11.19    | STANDARD      | TECHNOLOGY     | Q.A          |
| CHECKED   |            |             |               |                |              |
| APPROVED  |            |             |               |                |              |

**HTDISPLAY CO., LTD.**

DRAWING No. : HG1223209C-YF62L-VA  
 DRAWING TITLE: LCD MODULE  
 FILE NO.: 8

REV. : A  
 SCALE : -  
 PROJECTION: UNIT : MM  
 SHEET : 1/2

| REV. | CHANGE CONTENT | BY | DATE |
|------|----------------|----|------|
|      |                |    |      |
|      |                |    |      |
|      |                |    |      |