



- NOTE:
1. DISPLAY TYPE: STN-POSITIVE-TRANSPARENT-reflective-Y/G
 2. VIEWING DIR.: 6:00
 3. DRIVE METHOD: 1/32DUTY, 1/6BIAS, Vop=8.0V, VDD=5.0V
 4. OP. TEMP.: -20°C~70°C
 5. ST. TEMP.: -30°C~80°C
 6. CONTROLLER: S6B0108, S6B0107
 7. BACKLIGHTED COLOR-Y/G, V_f=4.1±0.2V, I_f=350mA,

Pins Description

Pin No	Symbol	Description
1	A	LED+
2	K	LED-
3	V0	LCD Operation Voltage
4	VDD	Power Supply Pin :+5.0V
5	VSS	Ground
6	E	Enable signal
7	C/D	L:Data; H:Instruction
8	R/W	Write and read signal
9	CS	Chip select signal, H:left, L:right
10	/RST	Reset: L: Enable; H: Disable
11-18	DD-D7	Data Bus



HTDISPLAY CO., LTD.

DRAWING No. : HG1283203C-YF62L-VA
DRAWING TITLE: LCM DRAWING

TOLERANCE	>0~6 ±0.10	DESIGN	ZOUYS	06.01.18	STANDARD	REV. : A	SCALE : -
	>6~80 ±0.20	CHECKED		TECHNOLOGY		PROJECTION:	UNIT : mm
	>80~240 ±0.30	APPROVED		Q.A		Φ	SHEET : 1/1
	>240~400 ±0.50						
	/// L @ ±0.10						

REV.	CHANGE CONTENT	BY	DATE