

UC1605(i)

*Single-Chip, Ultra-Low Power
80COM x 128SEG Matrix
Passive LCD Controller-Driver*

INTRODUCTION

UC1605(i) is an advanced high-voltage mixed-signal CMOS IC, especially designed for the display needs of ultra-low power hand-held devices.

This chip employs UltraChip's unique DCC (Direct Capacitor Coupling) driver architecture to achieve near crosstalk free images.

In addition to low power COM and SEG drivers, UC1605(i) contains all necessary circuits for high-V LCD power supply, bias voltage generation, timing generation and graphics data memory.

Advanced circuit design techniques are employed to minimize external component counts and reduce connector size while achieving extremely low power consumption.

MAIN APPLICATIONS


- Cellular Phones, Smart Phones, PDA and other battery operated palm top devices and/or portable Instruments

FEATURE HIGHLIGHTS

- Single chip controller-driver supports 4-shade-per-pixel, 80 COM x 128 SEG LCD, with vertical scroll and soft ICON support.
- Available either with or without I²C license.
- Support industry standard 8-bit parallel interface (8080 or 6800), 4-wire SPI (S8), and 2-wire I²C serial interface.

- Special driver structure and gray shade modulation scheme. Sharp image and ultra-low power consumption under all display patterns.
- Support four multiplexing rates (40, 50, 64, 80), four frame rates and 48-32-48 partial display function.
- Self-configuring 6x charge pump with on-chip pumping capacitor requires only 3 external capacitors to operate.
- Flexible data addressing/mapping schemes to support wide ranges of software models and LCD layout placements.
- Software programmable 4 temperature compensation coefficients.
- On-chip bypass capacitor for V_{LCD} makes V_{LCD} bypass capacitor optional for small LCD panels.
- On-chip Power-ON-Reset and Software Reset commands, make RST pin optional.
- Very low pin count (9-pin, with I²C) allows exceptional image quality in COG format on conventional ITO glass.
- V_{DD} (digital) range: 2.4V ~ 3.3V
V_{DD} (analog) range: 2.4V ~ 3.3V
LCD V_{OP} range: 6.5V ~ 11.5V
- Available in gold bump dies
Bump pitch: 55μM min.
Bump gap: 20μM min.

BLOCK DIAGRAM



1605 v1.7D