



PIN RECEPTACLES
 for .015" - .020" diameter pins (#11 contact)
 and .015" - .022" diameter pins (#21 contact)
 (see specific contact range on page 217)



<p>8467</p> <p>8467-0-15-XX-21-XX-04-0 Hex press-fit in .036 plated thru hole</p>	<p>6192</p> <p>6192-0-15-XX-21-XX-04-0 Square press-fit in .032 plated thru hole</p>	<p>9553</p> <p>9553-0-15-XX-X1-XX-04-0 Hex press-fit in .041 plated thru hole</p>	<p>5531</p> <p>5531-0-15-XX-21-XX-10-0 Hex press-fit in .041 plated thru hole</p>
---	--	---	---

<p>7553</p> <p>7553-0-15-XX-11-XX-10-0 Hex press-fit in .041 plated thru hole</p>	<p>9407</p> <p>9407-0-15-XX-11-XX-10-0 Solder mount in .040 min. mounting hole</p>	<p>9462</p> <p>9462-0-15-XX-21-XX-04-0 Hex press-fit in .043 plated thru hole</p>	<p>1147</p> <p>1147-0-18-XX-21-XX-10-0 Press-fit in .043 min. mounting hole</p>
---	--	---	---

<p>3061</p> <p>3061-0-19-XX-21-XX-10-0 Wire Termination</p>	<p>0579</p> <p>0579-0-15-XX-X1-XX-10-0 Press-fit in .040 mounting hole</p>	<p>8874</p> <p>8874-0-15-XX-11-XX-10-0 Bottom entry Surface mount</p>	<p>0613</p> <p>0613-0-15-XX-21-XX-10-0 Press-fit in .047 mounting hole</p>
---	--	---	--

<p>SPECIFICATIONS</p> <p>SHELL MATERIAL: Brass Alloy 360, 1/2 Hard</p> <p>CONTACT MATERIAL: Beryllium Copper Alloy 172, HT</p> <p>DIMENSION IN INCHES TOLERANCES ON: LENGTHS: ±.005 DIAMETERS: ±.002 ANGLES: ± 2°</p>	<p>ORDER CODE: XXXX - X - XX - XX - XX - XX - 0</p> <p>BASIC PART # →</p> <p>SPECIFY SHELL FINISH:</p> <p>01 200μ" TIN/LEAD OVER NICKEL</p> <p>80 200μ" TIN OVER NICKEL ◊</p> <p>15 10μ" GOLD OVER NICKEL ◊</p>	<p>SPECIFY CONTACT FINISH:</p> <p>02 100μ" TIN/LEAD OVER NICKEL</p> <p>84 100μ" TIN OVER NICKEL ◊</p> <p>27 30μ" GOLD OVER NICKEL ◊</p>
<p>SELECT CONTACT #11 or #21 CONTACT (DATA ON PAGE 217)</p>		

