



A2804

LINEAR INTEGRATED CIRCUIT

ZERO VOLTAGE SWITCH

DESCRIPTION

The UTC A2804 is a TRIAC controller providing a complete solution for temperature controlled electric panel heaters, cookers, film processing baths etc.

Switching occurs at the zero voltage point in order to minimize radio frequency interference. The device is suitable for mains-on-line operation and requires minimal components.

FEATURES

- *Easy operation either through the AC line or a DC supply.
- *Supply voltage control.
- *Very few external components.
- *Symmetrical burst control-No DC current components in the load circuit
- *Negative output current pulse up to 250mA-short circuit protection.
- *Reference voltage output


ORDERING INFORMATION

Ordering Number		Package	Packing
Normal	Lead Free Plating		
A2804-D08-T	A2804L-D08-T	DIP-8	Tube
A2804-S08-R	A2804L-S08-R	SOP-8	Tape Reel
A2804-S08-T	A2804L-S08-T	SOP-8	Tube

A2804L-D08-T


- (1) Packing Type
- (2) Package Type
- (3) Lead Plating

- (1) T: Tube, R: Tape Reel
- (2) D08: DIP-8, S08: SOP-8
- (3) L: Lead Free Plating, Blank: Pb/Sn




*Pb-free plating product number: A2804L

■ PIN CONFIGURATION



■ BLOCK DIAGRAM



■ ABSOLUTE MAXIMUM RATINGS (Ta=25 °C)

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	-Vs	8.2	V
Input Voltage	V _{IN}	≤ V _S	V
Supply Current	-I _S	40(average)	mA
Synchronous Current	I _{SYN}	5.0(rms)	mA
Power Dissipation	P _D	350	mW
Junction Temperature	T _J	125	°C
Operating Ambient Temperature	T _{OPR}	-20 ~ +70	°C
Storage Temperature	T _{STG}	-65 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.


Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ ELECTRICAL CHARACTERISTICS (Vs=8.0V, V_{SYN}=100 ~ 115Vrms, Ta=25 °C, f=50/60Hz)


PARAMETER	SYMBOL	PIN NO.	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	V _{OUT}	6	I _{OUT} ≤ 200mA	4.2	5.2		V
Input Offset Voltage	V _{I(OFF)}	3, 4			2.0	5.0	mV
Supply Voltage 1	-Vs1	5	I _S =2.5mA, R _{SYN} =56K	7.2		8.4	V
Supply Voltage 2	-Vs2	5	I _S =20mA, R _{SYN} =56K	7.2		8.6	V
Common Mode Input Voltage Range	-V _{I(CM)}	3, 4		0		5.7	V
Reference Voltage	-V _R	1	I _R ≤ 1μA		3.6		V
Circuit Current	-I _S	5	R _{SYN} =56K		2.0	2.5	mA
Synchronous Current	I _{SYN}	8		0.3			mA
Output Current	I _{OUT}	6	R _{OUT} ≤ 25	200	250		mA
Output Leakage Current	I _{LO}	6				2.0	μA
Input Bias Current	I _{I(BIAS)}	3, 4			0.5	1.0	μA
Output Leakage Current	I _{LC}	2				0.2	μA
Output Pulse Width	T _{PULSE}	6	R _{SYN} =56K		200		μs

■ TYPICAL APPLICATIONS

ON-OFF TEMPERATURE CONTROL



TIME PROPORTIONAL TEMPERATURE CONTROL



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.