

16K CMOS Static RAM (2048x8) 24PIN 6116

型名	社名	温度範囲 (°C)	スイッチング特性										電 源		入 力 [*typ]				出 力 [*typ]		備 考	
			TAAC max (ns)	TCAC max (ns)	TOE max (ns)	TOH min (ns)	TOD max (ns)	TWP min (ns)	TDS min (ns)	TDR min (ns)	TWD min (ns)	TRR max (ns)	VDD or VCC (V)	IDD max (mA)	IDD STANDBY (1SB/1SB2) (mA)	VIL max (V)	VIH min (V)	CI max (pF)	VOL/1 VOL max (V/mA)	VOH/1 VOH min (V/mA)		Co max (pF)
HM6116FP-2	HITACHI	0~70	120	80	10	40	70	35	5	0	4.5~5.5	80	2/-	0.8	2.2	5	0.4/4	2.4/1	7			
HM6116FP-3	HITACHI	0~70	150	100	15	50	90	40	10	0	4.5~5.5	5	2/-	0.8	2.2	5	0.4/4	2.4/1	7			
HM6116FP-4	HITACHI	0~70	200	120	15	60	120	60	10	0	4.5~5.5	70	2/-	0.8	2.2	5	0.4/2.1	2.4/1	7			
HM6116L-2	MHS	-55~125	120	120	80	40	70	35	5	0	4.5~5.5	80	4.5/1.5	0.8	2.2	8	0.4/3.2	2.4/1	10			
HM6116L-5	MHS	0~70	120	120	80	40	70	35	5	0	4.5~5.5	60	2/0.1	0.8	2.2	8	0.4/3.2	2.4/1	10			
HM6116L-9	MHS	-40~85	120	120	80	40	70	35	5	0	4.5~5.5	70	4.0/0.5	0.8	2.2	8	0.4/3.2	2.4/1	10			
HM6116LP-2	HITACHI	0~70	120	80	10	40	70	35	5	0	4.5~5.5	70	2/-	0.8	2.2	5	0.4/4	2.4/1	7			
HM6116LP-3	HITACHI	0~70	150	100	15	50	90	40	10	0	4.5~5.5	60	2/-	0.8	2.2	5	0.4/2.1	2.4/1	7			
HM6116LP-4	HITACHI	0~70	200	120	15	60	120	60	10	0	4.5~5.5	60	2/-	0.8	2.2	5	0.4/2.1	2.4/1	7			
HM6116LP-2	HITACHI	0~70	120	80	10	40	70	35	5	0	4.5~5.5	70	12/0.05	0.8	2.2	5	0.4/2	2.4/1	7			
HM6116LP-3	HITACHI	0~70	150	100	15	50	90	40	10	0	4.5~5.5	60	12/0.05	0.8	2.2	5	0.4/2	2.4/1	7			
HM6116LP-4	HITACHI	0~70	200	120	15	60	120	60	10	0	4.5~5.5	60	12/0.05	0.8	2.2	5	0.4/2	2.4/1	7			
HM65716-25	HITACHI	0~70	25	25	20	5	10	20	15	5	0	4.5~5.5	130	30/10	0.8	2.2	6	0.4/4	2.4/1	8		
HM65716-30	HITACHI	0~70	30	30	20	5	10	25	15	5	0	4.5~5.5	130	30/10	0.8	2.2	6	0.4/4	2.4/1	8		
HM65716P-25	HITACHI	0~70	25	25	20	5	10	20	15	5	0	4.5~5.5	120	30/10	0.8	2.2	6	0.4/4	2.4/1	8		
HM65716P-30	HITACHI	0~70	30	30	20	5	12	25	15	5	0	4.5~5.5	120	30/10	0.8	2.2	6	0.4/4	2.4/1	8		
HM65161-2	MHS	-55~125	90	90	60	35	65	30	5	0	4.5~5.5	70	4/1	0.8	2.2	8	0.4/3.2	2.4/1	10			
HM65161-5	MHS	0~70	70	70	40	35	65	30	5	0	4.5~5.5	50	2/0.1	0.8	2.2	8	0.4/3.2	2.4/1	10			
HM65161-9	MHS	-40~85	80	80	40	35	65	30	5	0	4.5~5.5	35	3/0.35	0.8	2.2	8	0.4/3.2	2.4/1	10			
HM65162	MHS	-55~125	90	90	65	5	50	55	30	15	10	4.5~5.5	70	8/0.05	0.8	2.2	5	0.4/4	2.4/1	7		
HM65162-5	HARRIS	0~70	90	65	5	50	55	30	15	10	4.5~5.5	70	8/0.1	0.8	2.2	8	0.4/4	2.4/1	10			
HM65162-5	MHS	0~70	70	70	5	40	40	30	0	0	4.5~5.5	50.0	2.0/0.001	0.8	2.2	8	0.4/8.0	2.4/4.0	10			
HM65162-9	HARRIS	-40~85	90	65	5	50	55	30	15	10	4.5~5.5	70	8/0.1	0.8	2.2	8	0.4/4	2.4/1	10	EQUIVALENT TO uPD446		
HM65162B	MHS	-55~125	70	70	5	35	40	30	10	10	4.5~5.5	70	8/0.05	0.8	2.2	5	0.4/4	2.4/1	7			
HM65162B-5	HARRIS	0~70	70	50	5	35	40	30	10	10	4.5~5.5	70	8/0.05	0.8	2.2	8	0.4/4	2.4/1	10			
HM65162B-5	MHS	0~70	55	55	5	35	35	25	0	0	4.5~5.5	50.0	2.0/0.001	0.8	2.2	8	0.4/8.0	2.4/4.0	10			
HM65162B-9	HARRIS	-40~85	70	50	5	35	40	30	10	10	4.5~5.5	70	8/0.05	0.8	2.2	8	0.4/4	2.4/1	10	EQUIVALENT TO uPD446		
HM65162C	MHS	-55~125	90	90	65	5	50	55	30	15	10	4.5~5.5	70	8/0.5	0.8	2.2	5	0.4/4	2.4/1	7		
HM65162C-5	MHS	0~70	70	70	5	40	40	30	0	0	4.5~5.5	50.0	2.0/0.1	0.8	2.2	8	0.4/8.0	2.4/4.0	10			
HM65162C-9	HARRIS	-40~85	90	65	5	50	55	30	10	10	4.5~5.5	70	8/1	0.8	2.2	8	0.4/4	2.4/1	10			
HM65162S-5	HARRIS	0~70	55	35	5	30	35	25	10	5	4.5~5.5	70	8/0.1	0.8	2.4	8	0.4/4	2.4/1	10			
HM65162S-9	HARRIS	-40~85	55	35	5	30	35	25	10	5	4.5~5.5	70	8/0.1	0.8	2.4	8	0.4/4	2.4/1	10	EQUIVALENT TO uPD446		
HM65728K-5	MHS	0~70	35	35	15	15	20	15	0	0	4.5~5.5	120	30/-	0.8	2.0	7	0.4/8	2.4/4	7			
HM65728M-2	MHS	-55~125	45	45	20	20	20	20	0	0	4.5~5.5	130	30/-	0.8	2.0	7	0.4/8	2.4/4	7			
HM65728M-5	MHS	0~70	45	45	20	20	20	20	0	0	4.5~5.5	120	30/-	0.8	2.0	7	0.4/8	2.4/4	7			
HM65728N-2	MHS	-55~125	55	55	25	20	25	25	0	0	4.5~5.5	100	30/-	0.8	2.0	7	0.4/8	2.4/4	7			
HM65728N-5	MHS	0~70	55	55	25	20	25	25	0	0	4.5~5.5	90	30/-	0.8	2.0	7	0.4/8	2.4/4	7			
HY61C16-45	HYUNDAI	0~70	45	45	20	5	20	25	25	0	0	4.5~5.5	100	5/100	0.8	2.2	6	0.4/8	2.4/0.4	8		
HY61C16-55	HYUNDAI	0~70	55	55	25	5	25	30	30	5	10	5	4.5~5.5	80	5/100	0.8	2.2	6	0.4/8	2.4/0.4	8	
HY61C16-70	HYUNDAI	0~70	70	50	5	35	40	30	5	15	5	4.5~5.5	70	5/100	0.8	2.2	6	0.4/8	2.4/0.4	8		
HY61C16A-25	HYUNDAI	0~70	25	25	10	0	15	20	15	0	0	4.5~5.5	110	5/100	0.8	2.2	6	0.4/8	2.4/4.0	8		
HY61C16A-35	HYUNDAI	0~70	35	35	15	3	15	25	20	0	0	0	4.5~5.5	110	5/100	0.8	2.2	6	0.4/8	2.4/4.0	8	