




**Data Sheet**



Product Category: VCXO Surface Mount

Series Number	Package	Description	Last Modified
567	J-Lead Plastic	HCMOS / TTL Output	Jan. 01 2007



**FEATURES**

- Wide voltage control range
- Wave form symmetry of 40/60%
- HCMOS / TTL output
- Industry standard J-Lead Plastic Package
- RoHs / Lead Free compliant 




**OPERATING CONDITIONS / ELECTRICAL CHARACTERISTICS**

PARAMETERS	CONDITIONS	CHARACTERISTICS		UNITS
<b>Output Logic</b>	-	HCMOS / TTL Output		-
<b>Input Voltage (VDD)</b>	-	3.3 ±10%	5.0 ±10%	VDC
<b>Frequency Range (f<sub>0</sub>)</b>	-	1.544 ~ 32.000		MHz
<b>Operating Temperature (T<sub>OPR</sub>)</b>	-	0 ~ +70 (Std.) / -40 ~ 85 (Option)		°C
<b>Storage Temperature (T<sub>STG</sub>)</b>	-	-55 ~ +125		°C
<b>Overall Frequency Stability</b>	-	±50, ±100 max.		PPM
	(a) Frequency Tolerance	Inclusive of Overall Stability		-
	(b) Temperature Stability	Inclusive of Overall Stability (Operating Temperature)		-
	(c) Input Voltage Stability	Inclusive of Overall Stability (VDD ±10%)		-
	(d) Load Stability	Inclusive of Overall Stability (RL ±5%)		-
<b>Input Current (I<sub>DD</sub>)</b>	-	10 ~ 35 max.	15 ~ 50 max.	mA
<b>Aging</b>	@ 25°C	±5 max.		PPM/Y
<b>Rise Time (T<sub>R</sub>) &amp; Fall Time (T<sub>F</sub>)</b>	-	8 max. (0.4V to 2.4V w/TTL , 20% to 80% /HCMOS)		nS
<b>Pin 1 Control Voltage Range</b>	-	1.65 ±1.35	2.5 ±2.0	V
<b>Output Voltage High "1" VOH</b>	TTL Load	2.4 min.		VDC
	HCMOS Load	2.7 min.	VDD - 0.5 min.	
<b>Output Voltage Low "0" VOL</b>	TTL Load	0.4 max.		VDC
	HCMOS Load	0.5 max.		
<b>Duty Cycle</b>	-	50 ±10 (Std.) / 50 ±5 (Option)		%
<b>Start-Up Time (T<sub>S</sub>)</b>	-	6 max.		mS
<b>Jitter</b>	-	±25 max.		ps
<b>Linearity</b>	-	±20 (Std.)		%
<b>Absolute Pull Range (APR)</b>	-	±50, ±100, ±150 min.		PPM

**PACKAGE DIMENSIONS (mm)**

PIN CONNECTIONS	
#1	Voltage Control
#2	Ground
#3	Output
#4	VDD



Suggested Solder Pad Layout

**PART NUMBER GUIDE**

Series Number	Frequency	Voltage Supply Option	Frequency Tolerance & Stability (max.)	Operating Temp. (°C)	Duty Cycle	Absolute Pulling Range	Linearity
<b>567</b>	<b>- 25.0 M</b>	<b>- 3</b>	<b>E</b>	<b>N</b>	<b>- T</b>	<b>P1</b>	<b>20</b>
Oscilent VCXO	Enter your desired frequency e.g. <b>25.0M</b> for 25.000 MHz	5 = 5VDC 3 = 3.3VDC	D = ±100 PPM E = ±50 PPM	Blank* = 0~+70 N = -40~+85	Blank* = 50±10% T = 50±5%	P1 = 50PPM P2 = 100PPM P3 = 150PPM	20 = 20%
<p><b>NOTE:</b> - Deviations on all parameters available. Please consult Oscilent for details.  <b>DEFINITIONS:</b> - Click on the characteristic names above for definitions of that particular characteristic.  <b>*STANDARDS:</b> - "Blank" part number selections indicate standard variables for that particular characteristic.  <b>PACKAGING:</b> - Standard tube packaging, add <b>-TR</b> for Tape/Reel. Click <a href="#">here</a> for tape/reel specifications</p>							

Oscilent Corporation - CALL **949.252.0522****Series No.: 567**

18195 East McDermott Street, Building D, Irvine, CA 92614, USA  
 Fax: 949.252.0599, E-Mail: [Sales@Oscilent.com](mailto:Sales@Oscilent.com)