

# FMMT413


## SOT23 NPN silicon planar avalanche transistor

### Summary

$V_{(BR)CES} = 150V$ ,  $V_{(BR)CEO} = 50V$ ,  $I_{USB} = 25A$

### Description

The FMMT413 is a NPN silicon planar bipolar transistor optimized for avalanche mode operation. Tight process control and low inductance packaging combine to produce high current pulses with fast edges, ideal for laser diode driving.




### Features

- Avalanche mode operation
- 50A peak avalanche current
- Low inductance packaging


### Applications

- Laser LED drivers
- Fast edge generation
- High speed pulse generators



### Ordering information

Device	Reel size (inches)	Tape width (mm)	Quantity per reel
FMMT413TD	7	8	500
FMMT413TA	7	8	3,000



Pinout - top view

### Device marking

413

# FMMT413

## Absolute maximum ratings

Parameter	Symbol	Limit	Unit
Collector-base voltage	$BV_{CBO}$	150	V
Collector-emitter voltage	$BV_{CEO}$	50	V
Emitter-base voltage	$BV_{EBO}$	6	V
Peak pulse current (25ns Pulse Width)	$I_{CM}$	50	A
Continuous collector current	$I_C$	100	mA
Power dissipation at $T_{amb} = 25^{\circ}C$ Linear derating factor	$P_D$	330	mW
Operating and storage temperature range	$T_j, T_{stg}$	-55 to +150	$^{\circ}C$

## Thermal resistance

Parameter	Symbol	Limit	Unit
Junction to ambient	$R_{\theta JA}$	378	$^{\circ}C/W$

# FMMT413


## Electrical characteristics (at $T_{amb} = 25^{\circ}\text{C}$ unless otherwise stated)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Collector-base breakdown voltage	$BV_{CBO}$	150			V	
Collector-emitter breakdown voltage	$BV_{CES}$	150			V	$I_C = 100\mu\text{A}$
Collector-emitter breakdown voltage	$BV_{CEO}$	50			V	$I_C = 10\text{mA}$
Emitter-base breakdown voltage	$BV_{EBO}$	6			V	$I_E = 100\mu\text{A}$
Collector cut-off current	$I_{CBO}$			100	nA	$V_{CB} = 120\text{V}$
Emitter cut-off current	$I_{EBO}$			100	nA	$V_{EB} = 4\text{V}$
Collector-emitter saturation voltage	$V_{CE(sat)}$			150	mV	$I_C = 10\text{mA}$ , $I_B = 1\text{mA}$
Base-emitter saturation voltage	$V_{BE(sat)}$			800	mV	$I_C = 10\text{mA}$ , $I_B = 1\text{mA}$
Current in second breakdown (pulsed)	$I_{USB}$	22			A	$V_C=110\text{V}$ , $C_{CE}=4.7\text{nF}^{(*)}$
		25			A	$V_C=130\text{V}$ , $C_{CE}=4.7\text{nF}^{(*)}$
Static forward current transfer ratio	$h_{FE}$	50				$I_C = 10\text{mA}$ , $V_{CE} = 10\text{V}$
Collector-emitter inductance	$L_{ce}$		2.5		nH	Standard SOT23 leads
Transition frequency	$f_T$		150		MHz	$I_C = 10\text{mA}$ , $V_{CE} = 5\text{V}$ , $f = 20\text{MHz}$
Output capacitance	$C_{OBO}$		2		pF	$V_{CB} = 10\text{V}$ , $I_E = 0$ , $f = 1\text{MHz}$

### NOTES:


(\*) Measured with a circuit possessing an approximate loop inductance of 12nH.

Typical characteristics



Intentionally left blank

## Package outline - SOT23



Dim.	Millimeters		Inches		Dim.	Millimeters		Inches	
	Min.	Max.	Min.	Max.		Min.	Max.	Max.	Max.
A	2.67	3.05	0.105	0.120	H	0.33	0.51	0.013	0.020
B	1.20	1.40	0.047	0.055	K	0.01	0.10	0.0004	0.004
C	-	1.10	-	0.043	L	2.10	2.50	0.083	0.0985
D	0.37	0.53	0.015	0.021	M	0.45	0.64	0.018	0.025
F	0.085	0.15	0.0034	0.0059	N	0.95 NOM		0.0375 NOM	
G	1.90 NOM		0.075 NOM		-	-	-	-	-

**Note:** Controlling dimensions are in millimeters. Approximate dimensions are provided in inches

### Europe

Zetex GmbH  
Streitfeldstraße 19  
D-81673 München  
Germany

Telefon: (49) 89 45 49 49 0  
Fax: (49) 89 45 49 49 49  
europe.sales@zetex.com

### Americas

Zetex Inc  
700 Veterans Memorial Highway  
Hauppauge, NY 11788  
USA

Telephone: (1) 631 360 2222  
Fax: (1) 631 360 8222  
usa.sales@zetex.com

### Asia Pacific

Zetex (Asia Ltd)  
3701-04 Metroplaza Tower 1  
Hing Fong Road, Kwai Fong  
Hong Kong

Telephone: (852) 26100 611  
Fax: (852) 24250 494  
asia.sales@zetex.com

### Corporate Headquarters

Zetex Semiconductors plc  
Zetex Technology Park, Chadderton  
Oldham, OL9 9LL  
United Kingdom

Telephone: (44) 161 622 4444  
Fax: (44) 161 622 4446  
hq@zetex.com

For international sales offices visit [www.zetex.com/offices](http://www.zetex.com/offices)

Zetex products are distributed worldwide. For details, see [www.zetex.com/salesnetwork](http://www.zetex.com/salesnetwork)

This publication is issued to provide outline information only which (unless agreed by the company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contact or be regarded as a representation relating to the products or services concerned. The company reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service.