

**INDUCTORS**

Inductors Designed for  
Nationals' 150 KHz SIMPLE SWITCHER™

8540-8548







- Designed for use with National Semiconductor LM 259X series
- Compact size and low cost
- Meets flammability rating of UL 94V-0



**MECHANICAL AND SCHEMATIC (All dimensions in inches)**

SUGGESTED PAD LAYOUT

SCHEMATIC



**ELECTRICAL SPECIFICATION @ 25°C**

Part Number	Nominal Inductance (µH)	Rated Current (Amps DC)	Nominal DCR (Ω)
8540	17	3.00	0.05
8541	24	2.74	0.07
8542	37	2.24	0.10
8543	53	1.87	0.13
8544	77	1.54	0.20
8545	112	1.26	0.30
8546	168	1.02	0.40
8547	248	0.83	0.60
8548	377	0.68	1.00

NOTES:  
1. SIMPLE SWITCHER™ is a trademark of National Semiconductor Corporation.  
2. Inductance values are ±20%.

ISSUE A 05/01 8540-8548



**FILTRAN LTD**  
An ISO 9001 Registered Company

229 Colonnade Road, Ottawa, Ontario, Canada K2E 7K3  
Tel: (613) 226-1626 Fax: (613) 226-7124 www.filtran.com