

SERIES 632 14 PIN TRIPLE H-CMOS DIGITAL DELAY MODULES

- 14 Pin DIP Auto-Insertable
- Three Independent Equal Delay Units Per Package
- H-Cmos Logic

Specifications:


- Supply Voltage : 4.75 to 5.25VDC
- Logic 1 Input Voltage : 3.2v
- Logic 0 Input Voltage : 0.9v
- Logic 1 Output Voltage : 4.5v
- Logic 0 Output Voltage : 0.1v
- Input Current : 1µA Max
- Supply Current : ICCH = 5mA, ICCL = 20µA
- Fan-Out : 10 LSTTL Loads Min
- Rise-Time : 8NS TYP. (measured from 0.8v to 2.0v)
- Operating Temp Range : 0°C to 70°C
- Temp Coefficient : 300 PPM/°C



Electrical Specifications at 25°C (Measured with no Loads on Taps)

Part Number	Total Delay Nanosecond (1)
632-5	5±1
632-6	6±1
632-8	8±2
632-10	10±2
632-12	12±2
632-16	16±2
632-25	25±2
632-30	30±2
632-35	35±2
632-40	40±2
632-45	45±2.2
632-50	50±2.5
632-60	60±3
632-75	75±3.5
632-100	100±5.0
632-125	125±5.5
632-150	150±6.0
632-175	175±8.7
632-200	200±10
632-250	250±12.5

Note: (1) Measured at 1.5v level leading edge.



SCHMATIC

