

# 6LU8



16LU8, 21LU8

Color Television Type

## VERTICAL DEFLECTION OSCILLATOR and AMPLIFIER

### High Mu Triode and Beam Power Pentode

Construction ..... Compactron T-12  
 Base ..... Button 12 Pin, E12-74  
 Basing ..... 12DZ  
 Outline ..... 12-57  
 Maximum Diameter ..... 1.562 In.  
 Maximum Seated Height ..... 2.750 In.  
 Maximum Overall Height ..... 3.125 In.



### ELECTRICAL DATA

#### HEATER OPERATION

	21LU8	16LU8	6LU8
Heater Voltage.....	21	15.8	6.3 Volts
Heater Current .....	450	600	1500 Ma
Heater Warm-up Time .....	11	11	— Seconds
Maximum Heater-Cathode Voltage			
Heater Negative with Respect to Cathode			
Total DC and Peak.....			200 Volts
Heater Positive with Respect to Cathode			
DC .....			100 Volts
Total DC and Peak.....			200 Volts

#### DIRECT INTERELECTRODE CAPACITANCES (Unshielded)

##### Triode Section

Grid to Plate: tg to tp .....	6.0 Pf
Input: tg to (h + Tk) .....	7.0 Pf
Output: tp to (h + Tk) .....	2.0 Pf

##### Pentode Section

Grid No. 1 to Plate: pg1 to pp .....	0.5 Pf
Input: pg1 to (h + Pk + Pg2) .....	16 Pf
Output: pp to (h + Pk + Pg2) .....	9.0 Pf

##### Coupling

Pentode Grid No. 1 to Triode Plate (Max.) .....	0.13 Pf
Pentode Plate to Triode Plate (Max.) .....	0.40 Pf

#### RATINGS (Design Maximum Rating System)

##### Vertical Deflection Oscillator and Amplifier<sup>(1)</sup>

	Triode Osc.	Pentode Amp.
Plate Voltage (Max.) .....	400	400 Volts
Grid No. 2 Voltage (Max.) .....	—	300 Volts
Peak Positive Pulse Plate Voltage (Max.) .....	—	2500 Volts
Peak Negative Grid No. 1 Voltage (Max.) .....	400	250 Volts
Plate Dissipation (Max.) <sup>(2)</sup> .....	2.5	14 Watts
Grid No. 2 Dissipation (Max.) .....	—	2.75 Watts
Average Cathode Current (Max.).....	30	75 Ma
Peak Cathode Current (Max.) .....	105	260 Ma
Grid Circuit Resistance		
Self Bias (Max.) .....	2.2	2.2 Megohms
Fixed Bias (Max.) .....	—	1.0 Megohm
Bulb Temperature (Max.) .....	—	210 °C

#### CHARACTERISTICS AND TYPICAL OPERATION

	Triode Section	Pentode Section
Plate Voltage .....	250	135 Volts
Grid No. 2 Voltage .....	—	120 Volts
Grid No. 1 Voltage .....	-4	-10 Volts
Plate Current .....	2.3	56 Ma
Grid No. 2 Current .....	—	3 Ma
Transconductance .....	3600	9300 μmhos
Amplification Factor .....	58	6.5 <sup>(3)</sup>
Plate Resistance (Approx.) .....	16,000	12,000 Ohms
Ec for Ib = 10 μa .....	-6.6	— Volts
Ec for Ib = 1 Ma (Approx.) .....	—	-26 Volts
Ec for Ib = 100 μa .....	—	-30 Volts

#### INSTANTANEOUS PLATE KNEE VALUES

Eb = 45 V; Ec2 = 125 V; and Ec = 0 V  
 Ib = 200 Ma, and Ic2 = 20 Ma