

ECM Surface Mount Oscillator




ECXO62-63

- Tri-state HCMOS / TTL
- 3.3V Version Available
- SMD Ceramic Package
- Low Profile




Parameter	ECXO62 - 63	
Frequency Range	1.80MHz to 50.0MHz	Specify
Frequency Stability	+/-50ppm (B) +/-100ppm (C)	Specify
Supply Voltage	5V +/-5% 3.3V +/-5%	ECXO62 ECXO63
Supply Current	40mA max Frequency dependent	
Load	50pF / 10TTL 15pF / 10LSTTL	ECXO62 ECXO63
Duty Cycle	40 / 60	
Rise & Fall Times	5ns max 6nS max	ECXO62 ECXO63
Start-up Time	10mS max	
Operating Temp	-10°C to +70°C (S) -40°C to +85°C (H) 100ppm only	
Storage Temp	-40°C to +85°C	

Environmental & Mechanical	
Mechanical Shock	JIS-C-6701
Thermal Shock	JIS-C-9701
Vibration	JIS-C-6701
Soldering Condition	230°C for 10s max
Hermetic Seal	JIS-C-6701



Part Numbering **ECXO62 H 25.00M B**



Pin	1	2	3	4
Function	E/D	GND	O/P	VDD

A	B	C	D	E	F	G	H
6.00	3.50	1.40	1.00	2.54	1.00	2.40	1.40

Dimensions in mm

ECM Electronics Limited, Penmaen House, Ashington, West Sussex, RH20 3JR, UK
Tel: +44(0)1903 892810: Fax: +44(0)1903 892738. Email: ecm@ecmelectronics.co.uk

Although we have attempted to accurately reflect the products we market. ECM reserve the right without prior notice to discontinue any product or make design changes we believe necessary.