


Low Resistance Power Wirewounds

PLO Series

- 3 watts to 15 watts
- $\pm 1, 2, 3, 5$ and 10% tolerance
- 0.005 ohm to 0.18 ohm
- TC's from 30 ppm/°C to +500 ppm/°C



Electrical Data

Type		PLO-3	PLO-5	PLO-7	PLO-10	PLO-15
Power @ 25°C	watts	3	5	7	10	15
Resistance range	ohms	R005 to R18	R005 to R18	R01 to R18	R01 to R18	R01 to R18

Inductance less than 10 nanohenries


Note: When ordering the alternate configuration please add an 'A' after the part number. (ie. PLO-3A)

Standard test points for PLO-3 and PLO-5 are 44.45mm; test points for PLO-7, PLO-10 and PLO-15 are 63.50mm.


Physical Data

Dimensions (mm)						Standard Configuration
Type	L	W	H	d	E	
	± 1.6	± 0.8	± 0.8	± 0.05	± 0.8	
PLO-3	22.4	7.87	7.87	0.040	9.65	
PLO-5	22.4	9.65	8.89	0.040	10.4	
PLO-7	35.3	9.65	8.89	0.040	11.9	
PLO-10	47.8	9.65	8.89	0.040	11.9	
PLO-15	47.8	12.7	12.7	0.040	16.0	

Power Derating



Temperature Rise



Packaging

Resistors are supplied bulk packed.

General Note

Welwyn Components reserves the right to make changes in product specification without notice or liability. All information is subject to Welwyn's own data and is considered accurate at time of going to print.

© Welwyn Components Limited · Bedlington, Northumberland NE22 7AA, UK
 Telephone: +44 (0) 1670 822181 · Facsimile: +44 (0) 1670 829465 · Email: info@welwyn-tt.com · Website: www.welwyn-tt.com