

FEATURES

- Red enhanced
- Photovoltaic
- High quantum efficiency

DESCRIPTION

The **PDB-V615-2** is a silicon, planar diffused, red enhanced solderable photodiode that comes with PVC wire leads .

APPLICATIONS


- Optical encoder
- Position sensor
- Industrial controls
- Instrumentation

ABSOLUTE MAXIMUM RATING (TA)= 23°C UNLESS OTHERWISE NOTED

SYMBOL	PARAMETER	MIN	MAX	UNITS
V _{BR}	Reverse Voltage		25	V
T _{STG}	Storage Temperature	-40	+125	°C
T _O	Operating Temperature	-40	+100	°C
T _S	Soldering Temperature*		+224	°C

* 1/16 inch from case for 3 seconds max.

SPECTRAL RESPONSE



ELECTRO-OPTICAL CHARACTERISTICS RATING (TA)= 23°C UNLESS OTHERWISE NOTED

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	MIN	TYP	MAX	UNITS
I _{SC}	Short Circuit Current	H = 100 fc, 2850 K	2.5	2.8		mA
I _D	Dark Current	V _R = 5 V		350	700	nA
R _{SH}	Shunt Resistance	V _R = 10 mV	0.2	0.5		MΩ
C _J	Junction Capacitance	V _R = 0 V, f = 1 MHz		25800		pF
λ _{range}	Spectral Application Range	Spot Scan	350		1100	nm
V _{BR}	Breakdown Voltage	I = 10 μA	5	15		V
NEP	Noise Equivalent Power	V _R = 0V @ λ = Peak		5.0x10 ⁻¹³		W/√Hz
t _r	Response Time	RL = 1KΩ, V _R = 0V		7000		nS

**Response time of 10% to 90% is specified at 660nm wavelength light.

Information in this technical datasheet is believed to be correct and reliable. However, no responsibility is assumed for possible inaccuracies or omission. Specifications are subject to change without notice.