

P-tec Corp. Tel:(800)688-0613
 2405 Commerce Circle Tel:(719) 589 3122
 Alamosa Co. 81101 Fax:(719) 589 3592
 www.p-tec.net sales@p-tec.net



PL1010 Series Oval Lens High Power Warm White SMD LED

Features

- *TO-220 Package
- *High Light Output
- *Wide Viewing Angle
- *Thermal Resistance Junction to Board is 15°C/W
- *RoHS Complaint

Absolute Maximum Ratings at T_A = 25°C

| | |
|--|----------------------|
| Reverse Voltage (50μA) | 5.0V |
| Power Dissipation | 1W |
| D.C. Forward Current | 350mA |
| Pulsed Forward Current : tp ≤100μs, Duty Cycle=0.005 | 1000mA |
| Operating Temperature Range | -30°C to +85°C |
| Storage Temperature Range | -40°C to +105°C |
| Reflow Soldering Temperature | 260°C for 10 seconds |
| ESD Threshold (HBM) | 6000V |
| LED Junction Temperature | 120°C |

Electrical & Optical Characteristics at T_A = 25°C

| Part Number | Emitting Color | Chip Material | Color Temperature (°K) | | View Angle 2θ ½ Deg | Forward Voltage @350mA (V) | | Luminous Flux (lm) | |
|---------------|----------------|---------------|------------------------|------|------------------------|----------------------------|------|--------------------|------|
| | | | Min | Max | | Typ | Max | Min | Max |
| PL1010SO-WCWW | White | InGaN | 2700 | 3700 | H60° V30° | 2.7 | 4.25 | 23.5 | 51.6 |

Package Dimensions are in **Millimeters**. Tolerance is ± 0.25mm unless otherwise specified.

