


**IR-enhanced Si PIN photodiodes**



S11499 series

**Large area, enhanced near IR sensitivity, using a MEMS technology**

HAMAMATSU has developed various types of Si detectors that offer enhanced near-infrared sensitivity due to a MEMS structure formed on the back side of the photodiode. The S11499 series is a family of Si PIN photodiodes with drastically improved sensitivity in the near infrared region at wavelengths longer than 900 nm. Compared to our conventional product, the S11499 series has much higher sensitivity to YAG laser light (1.06 μm). It also offers improved temperature characteristics of sensitivity at wavelengths longer than 950 nm.

**Features**

- High sensitivity: 0.6 A/W ( $\lambda=1060$  nm)
- Large active area:  $\phi 5.0$  mm (S11499-01)
- High reliability package: TO-5/TO-8 metal package

**Applications**

- YAG laser monitor

**General ratings**

Parameter	S11499	S11499-01	Unit
Package	TO-5	TO-8	-
Active area	$\phi 3.0$	$\phi 5.0$	mm


**Absolute maximum ratings**

Parameter	Symbol	Condition	S11499	S11499-01	Unit
Reverse voltage	$V_R$ max.	$T_a=25$ °C	30		V
Operating temperature	$T_{opr}$		-40 to +100		°C
Storage temperature	$T_{stg}$		-55 to +125		°C


**Electrical and optical characteristics ( $T_a=25$  °C)**

Parameter	Symbol	Condition	S11499			S11499-01			Unit
			Min.	Typ.	Max.	Min.	Typ.	Max.	
Spectral response range	$\lambda$		-	360 to 1140	-	-	360 to 1140	-	nm
Peak sensitivity wavelength	$\lambda_p$		-	1000	-	-	1000	-	nm
Photo sensitivity	S	$\lambda=1060$ nm	0.54	0.6	-	0.54	0.6	-	A/W
Short circuit current	$I_{sc}$	100 lx	6.0	7.8	-	15	21	-	μA
Dark current	$I_D$	$V_R=20$ V	-	0.05	5	-	0.1	10	nA
Cut-off frequency	$f_c$	$V_R=20$ V, -3 dB	-	30	-	-	15	-	MHz
Terminal capacitance	$C_t$	$V_R=20$ V, $f=1$ MHz	-	13	-	-	33	-	pF


**Spectral response**




**Photo sensitivity temperature characteristic**



**Dark current vs. reverse voltage**






**Terminal capacitance vs. reverse voltage**



### Dimensional outlines (unit: mm)




S11499



The glass window may extend a maximum of 0.2 mm above the upper surface of the cap.

KPINA0024EB

S11499-01



The glass window may extend a maximum of 0.3 mm above the upper surface of the cap.

KPINA0027EC

Information furnished by HAMAMATSU is believed to be reliable. However, no responsibility is assumed for possible inaccuracies or omissions.

Specifications are subject to change without notice. No patent rights are granted to any of the circuits described herein.

Type numbers of products listed in the specification sheets or supplied as samples may have a suffix "(X)" which means tentative specifications or a suffix "(Z)" which means developmental specifications. ©2010 Hamamatsu Photonics K.K.

# HAMAMATSU

[www.hamamatsu.com](http://www.hamamatsu.com)

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Higashi-ku, Hamamatsu City, 435-8558 Japan, Telephone: (81) 53-434-3311, Fax: (81) 53-434-5184

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, P.O.Box 6910, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1) 908-231-0960, Fax: (1) 908-231-1218

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49) 8152-375-0, Fax: (49) 8152-265-8

France: Hamamatsu Photonics France S.A.R.L.: 19, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: 33-(1) 69 53 71 00, Fax: 33-(1) 69 53 71 10

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, United Kingdom, Telephone: (44) 1707-294888, Fax: (44) 1707-325777

North Europe: Hamamatsu Photonics Norden AB: Smidesvägen 12, SE-171 41 Solna, Sweden, Telephone: (46) 8-509-031-00, Fax: (46) 8-509-031-01

Italy: Hamamatsu Photonics Italia S.R.L.: Strada della Moia, 1 int. 6, 20020 Arese, (Milano), Italy, Telephone: (39) 02-935-81-733, Fax: (39) 02-935-81-741