


High Performance BGA Cooling Solutions w/ maxiGRIP™ Attachment

ATS PART # ATS-53300R-C2-R0

Features & Benefits

- » High aspect ratio, straight fin heat sinks that are ideal for compact PCB environments
- » maxiGRIP™ attachment applies steady, even pressure to the component and does not require holes in the PCB
- » Designed specifically for BGAs and other surface mount packages
- » Meets Telcordia GR-63-Core Office Vibration; ETSI 300 019 Transportation Vibration; and MIL-STD-810 Shock Testing and Unpackaged Drop Testing standards
- » Comes preassembled with high performance, phase changing, thermal interface material

Thermal Performance





*Image above is for illustration purposes only.

AIR VELOCITY		THERMAL RESISTANCE		
FT/MIN	M/S	°C/W (UNDUCTED FLOW)	°C/W (DUCTED FLOW)	
200	1.0	4.8	3.1	
300	1.5	3.9		
400	2.0	3.3		
500	2.5	3		
600	3.0	2.7		
700	3.5	2.6		
800	4.0	2.4		

Product Details

DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D	INTERFACE MATERIAL	FINISH
30 mm	30 mm	19.5 mm	30 mm	SAINT-GOBAIN C1100F	BLACK-ANODIZED

NOTES:

 ATS-53300R-C1-R0 is a subsitute item available utilizing an equivalent phase change material (Chomerics T766).

3) Thermal performance data are provided for reference only. Actual performance may vary

by application.
ATS reserves the right to update or change its products without notice to improve the design or performance.

5) Optional maxiGRIP[™] Installation/Removal Tool Set P/N: MGT300

6) Contact ATS to learn about custom options available.



For more information, to find a distributor or to place an order, visit www.qats.com or call: 781.769.2800 (North America); +31 (0) 3569 84715 (Europe).

¹⁾ Dimension C = heat sink height from bottom of the base to the top of the fin field.