



Phase leg
Intelligent Power Module

V_{CES} = 600V
I_C = 350A @ T_c = 80°C



Application

- Motor control
- Uninterruptible Power Supplies
- Switched Mode Power Supplies
- Amplifier

Features

- **Non Punch Through (NPT) FAST IGBT**
 - Low voltage drop
 - Low tail current
 - Soft recovery parallel diodes
 - Low diode VF
 - Low leakage current
 - RBSOA & SCSOA rated
- **Integrated Fail Safe IGBT Protection (Driver)**
 - Top Bottom input signals Interlock
 - Isolated DC/DC Converter
- Low stray inductance
- M5 power connectors
- High level of integration

Benefits

- Outstanding performance at high frequency operation
- Stable temperature behavior
- Very rugged
- Direct mounting to heatsink (isolated package)
- Low junction to case thermal resistance
- Very high noise immunity
(common mode rejection > 25kV/μs)
- Galvanic Isolation: 3750V for the optocoupler
2500V for the transformer
- 5V logic level with Schmitt-trigger Input
- Single V_{DD}=5V supply required
- Secondary auxiliary power supplies internally generated
(15V, -6V)
- Optocoupler qualified to AEC-Q100 test guidelines
- RoHS compliant



CAUTION: These Devices are sensitive to Electrostatic Discharge. Proper Handling Procedures Should Be Followed.
 See application note APT0502 on www.microsemi.com

All ratings @ $T_j = 25^\circ\text{C}$ unless otherwise specified

1. Inverter Power Module

Absolute maximum ratings

Symbol	Parameter		Max ratings	Unit
V_{CES}	Collector - Emitter Breakdown Voltage		600	V
I_C	Continuous Collector Current	$T_C = 25^\circ\text{C}$	430	A
		$T_C = 80^\circ\text{C}$	350	
I_{CM}	Pulsed Collector Current	$T_C = 25^\circ\text{C}$	700	
P_D	Maximum Power Dissipation	$T_C = 25^\circ\text{C}$	1562	W
RBSOA	Reverse Bias Safe Operating Area	$T_j = 125^\circ\text{C}$	800A@550V	

Electrical Characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
I_{CES}	Zero Gate Voltage Collector Current	$V_{GE} = 0\text{V}$	$T_j = 25^\circ\text{C}$		0.5	mA
		$V_{CE} = 600\text{V}$	$T_j = 125^\circ\text{C}$		1.5	
$V_{CE(\text{sat})}$	Collector Emitter Saturation Voltage	$V_{DD} = V_{IN} = 5\text{V}$	$T_j = 25^\circ\text{C}$	2	2.5	V
		$I_C = 400\text{A}$	$T_j = 125^\circ\text{C}$	2.2		

Dynamic Characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
C_{ies}	Input Capacitance	$V_{GE} = 0\text{V}$ $V_{CE} = 25\text{V}$ $f = 1\text{MHz}$		17.2		nF
C_{oes}	Output Capacitance			1.88		
C_{res}	Reverse Transfer Capacitance			1.6		
T_r	Rise Time	Inductive Switching (25°C) $V_{DD} = V_{IN} = 5\text{V}$ $V_{Bus} = 400\text{V} ; I_C = 400\text{A}$		25		ns
T_f	Fall Time			30		
T_r	Rise Time			25		
T_f	Fall Time	$V_{DD} = V_{IN} = 5\text{V}$ $V_{Bus} = 400\text{V}$ $I_C = 400\text{A}$		45		ns
E_{on}	Turn-on Switching Energy			17.2		
E_{off}	Turn-off Switching Energy			14		
I_{sc}	Short Circuit data	$V_{DD} = V_{IN} = 5\text{V}; V_{Bus} = 360\text{V}$ $t_p \leq 10\mu\text{s} ; T_j = 125^\circ\text{C}$		1800		A
R_{thJC}	Junction to Case thermal resistance				0.08	°C/W

Reverse diode ratings and characteristics

Symbol	Characteristic	Test Conditions		Min	Typ	Max	Unit
V _{RRM}	Maximum Peak Repetitive Reverse Voltage			600			V
I _{RM}	Maximum Reverse Leakage Current	V _R =600V	T _j = 25°C			100	μA
			T _j = 125°C			2000	
I _F	DC Forward Current		T _c = 80°C		240		A
V _F	Diode Forward Voltage	I _F = 240A			1.7	2.3	V
		I _F = 480A			2		
		I _F = 240A	T _j = 125°C		1.4		
t _{rr}	Reverse Recovery Time	I _F = 240A V _R = 400V di/dt = 800A/μs	T _j = 25°C		70		ns
			T _j = 125°C		140		
Q _{rr}	Reverse Recovery Charge	T _j = 25°C T _j = 125°C	T _j = 25°C		400		nC
			T _j = 125°C		2760		
R _{thJC}	Junction to Case Thermal Resistance					0.22	°C/W

2. Driver

Absolute maximum ratings

Symbol	Parameter	Max ratings	Unit
V _{DD}	Supply Voltage	5.5	V
V _{INI}	Input signal voltage i=L, H	5.5	
I _{VDDmax}	Maximum Supply current	V _{INI} = 0V, i =L & H	0.35
		V _{DD} =5V, V _{INH} = /V _{INL} ; F _{out} = 60kHz	
f _{max}	Maximum Switching Frequency	60	kHz

Driver Electrical Characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
V _{DD}	Operating Supply Voltage		4.5	5	5.5	V
V _{INI(max)}	Maximum Input Voltage		-0.5	5	5.5	V
V _{INI(th+)}	Positive Going Threshold Voltage	i = L, H		3.2		
V _{INI(th-)}	Negative Going Threshold Voltage			1		
R _{INI}	Input Resistance *			1		kΩ
T _{d(on)}	Turn On delay time	Driver + IGBT		1100 ^①		ns
D _T	Built in dead time			600		
T _{d(off)}	Turn Off delay time	Driver + IGBT		750		
PWD	Pulse Width Distortion				300	ns
PDD	Propagation Delay Difference between any two driver	T _{d(on)} - T _{d(off)}	-350		350	
V _{ISOL}	Primary to Secondary Isolation		2500			V _{RMS}


* Low impedance guarantees good noise immunity.









① Including built in dead time.




3. Package characteristics

Symbol	Characteristic		Min	Typ	Max	Unit
V _{ISOL}	RMS Isolation Voltage, any terminal to case t =1 min, I isol<1mA, 50/60Hz		2500			V
T _J	Operating junction temperature range		-40		150	°C
T _{OP}	Operating Ambient Temperature		-40		85	°C
T _{STG}	Storage Temperature Range		-40		100	°C
T _C	Operating Case Temperature		-40		100	°C
Torque	Mounting torque	To heatsink For terminals	M5 M5	2 2	4.7 4	N.m
Wt	Package Weight			550		g


4. LP8 Package outline (dimensions in mm)



Typical IGBT Performance Curve




Typical diode Performance Curve



Microsemi reserves the right to change, without notice, the specifications and information contained herein