

PH16030L

N-channel TrenchMOS™ logic level FET

Rev. 01 — 24 February 2005

Product data sheet

1. Product profile

1.1 General description

Logic level N-channel enhancement mode Field-Effect Transistor (FET) in a plastic package using TrenchMOS™ technology.

1.2 Features

- Logic level threshold
- SO8 equivalent area footprint
- Low thermal resistance
- Low gate charge.

1.3 Applications

- DC-to-DC converters
- Portable appliances.

1.4 Quick reference data

- $V_{DS} \leq 30$ V
- $R_{DS(on)} \leq 16.9$ m Ω
- $I_D \leq 38$ A
- $Q_{gd} = 2.9$ nC (typ).

2. Pinning information

Table 1: Pinning

| Pin | Description | Simplified outline | Symbol |
|---------|-----------------------------------|--------------------|--------|
| 1, 2, 3 | source | | |
| 4 | gate | | |
| mb | mounting base; connected to drain | | |

SOT669 (LFPAK)

PHILIPS

3. Ordering information

Table 2: Ordering information


| Type number | Package | | Version |
|-------------|---------|---|---------|
| | Name | Description | |
| PH16030L | LFAK | plastic single-ended surface mounted package; 4 leads | SOT669 |

4. Limiting values

Table 3: Limiting values


In accordance with the Absolute Maximum Rating System (IEC 60134).

| Symbol | Parameter | Conditions | Min | Max | Unit |
|-----------------------------|--|---|-----|----------|------|
| V_{DS} | drain-source voltage (DC) | $25\text{ °C} \leq T_j \leq 150\text{ °C}$ | - | 30 | V |
| V_{DGR} | drain-gate voltage (DC) | $25\text{ °C} \leq T_j \leq 150\text{ °C}$; $R_{GS} = 20\text{ k}\Omega$ | - | 30 | V |
| V_{GS} | gate-source voltage (DC) | | - | ± 15 | V |
| I_D | drain current (DC) | $T_{mb} = 25\text{ °C}$; $V_{GS} = 10\text{ V}$; Figure 2 and 3 | - | 38 | A |
| | | $T_{mb} = 100\text{ °C}$; $V_{GS} = 10\text{ V}$; Figure 2 | - | 24 | A |
| I_{DM} | peak drain current | $T_{mb} = 25\text{ °C}$; pulsed; $t_p \leq 10\text{ }\mu\text{s}$; Figure 3 | - | 100 | A |
| P_{tot} | total power dissipation | $T_{mb} = 25\text{ °C}$; Figure 1 | - | 41.6 | W |
| T_{stg} | storage temperature | | -55 | +150 | °C |
| T_j | junction temperature | | -55 | +150 | °C |
| Source-drain diode | | | | | |
| I_S | source (diode forward) current (DC) | $T_{mb} = 25\text{ °C}$ | - | 38 | A |
| I_{SM} | peak source (diode forward) current | $T_{mb} = 25\text{ °C}$; pulsed; $t_p \leq 10\text{ }\mu\text{s}$ | - | 100 | A |
| Avalanche ruggedness | | | | | |
| $E_{DS(AL)S}$ | non-repetitive drain-source avalanche energy | unclamped inductive load; $I_D = 21\text{ A}$; $t_p = 0.1\text{ ms}$; $V_{DD} \leq 25\text{ V}$; $R_{GS} = 50\text{ }\Omega$; $V_{GS} = 10\text{ V}$; starting at $T_j = 25\text{ °C}$ | - | 44 | mJ |




$$P_{der} = \frac{P_{tot}}{P_{tot(25^{\circ}\text{C})}} \times 100\%$$

Fig 1. Normalized total power dissipation as a function of mounting base temperature



$$I_{der} = \frac{I_D}{I_{D(25^{\circ}\text{C})}} \times 100\%$$

Fig 2. Normalized continuous drain current as a function of mounting base temperature



$T_{mb} = 25^{\circ}\text{C}$; I_{DM} is single pulse; $V_{GS} = 10\text{ V}$

Fig 3. Safe operating area; continuous and peak drain currents as a function of drain-source voltage

5. Thermal characteristics

Table 4: Thermal characteristics

| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|----------------|---|------------|-----|-----|-----|------|
| $R_{th(j-mb)}$ | thermal resistance from junction to mounting base | Figure 4 | - | - | 3 | K/W |




Fig 4. Transient thermal impedance from junction to mounting base as a function of pulse duration

6. Characteristics

Table 5: Characteristics
T_j = 25 °C unless otherwise specified.

| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|--------------------------------|---|--|---------------|--------------------|----------------------|----------------|
| Static characteristics | | | | | | |
| V _{(BR)DSS} | drain-source breakdown voltage | I _D = 250 μA; V _{GS} = 0 V T _j = 25 °C T _j = -55 °C | 30 27 | - - | - - | V V |
| V _{GS(th)} | gate-source threshold voltage | I _D = 1 mA; V _{DS} = V _{GS} ; Figure 9 and 10 T _j = 25 °C T _j = 150 °C T _j = -55 °C | 1 0.6 - | 1.5 - - | 2 - 2.2 | V V V |
| I _{DSS} | drain-source leakage current | V _{DS} = 30 V; V _{GS} = 0 V T _j = 25 °C T _j = 150 °C | - - - | - - - | 1 100 | μA μA |
| I _{GSS} | gate-source leakage current | V _{GS} = ±15 V; V _{DS} = 0 V | - | - | 100 | nA |
| R _{DSon} | drain-source on-state resistance | V _{GS} = 10 V; I _D = 15 A; Figure 6 and 8 T _j = 25 °C T _j = 150 °C V _{GS} = 4.5 V; I _D = 15 A; Figure 6 and 8 | - - - | 14.1 24 18.8 | 16.9 28.7 23.5 | mΩ mΩ mΩ |
| Dynamic characteristics | | | | | | |
| Q _{g(tot)} | total gate charge | I _D = 15 A; V _{DS} = 12 V; V _{GS} = 4.5 V; Figure 11 and 12 | - | 8.2 | - | nC |
| Q _{gs} | gate-source charge | | - | 2.3 | - | nC |
| Q _{gs1} | pre-V _{GS(th)} gate-source charge | | - | 0.9 | - | nC |
| Q _{gs2} | post-V _{GS(th)} gate-source charge | | - | 1.4 | - | nC |
| Q _{gd} | gate-drain (Miller) charge | | - | 2.9 | - | nC |
| V _{plat} | plateau voltage | | - | 2.6 | - | V |
| Q _{g(tot)} | total gate charge | I _D = 0 A; V _{DS} = 0 V; V _{GS} = 4.5 V | - | 6.7 | - | nC |
| C _{iss} | input capacitance | V _{GS} = 0 V; V _{DS} = 12 V; f = 1 MHz; Figure 14 | - | 680 | - | pF |
| C _{oss} | output capacitance | | - | 280 | - | pF |
| C _{rss} | reverse transfer capacitance | | - | 135 | - | pF |
| C _{iss} | input capacitance | V _{GS} = 0 V; V _{DS} = 0 V; f = 1 MHz | - | 1090 | - | pF |
| t _{d(on)} | turn-on delay time | V _{DS} = 15 V; R _L = 1 Ω; V _{GS} = 4.5 V; | - | 9 | - | ns |
| t _r | rise time | R _G = 5.6 Ω | - | 18 | - | ns |
| t _{d(off)} | turn-off delay time | | - | 16 | - | ns |
| t _f | fall time | | - | 33 | - | ns |
| Source-drain diode | | | | | | |
| V _{SD} | source-drain (diode forward) voltage | I _S = 15 A; V _{GS} = 0 V; Figure 13 | - | 0.86 | 1.2 | V |
| t _{rr} | reverse recovery time | I _S = 15 A; dI _S /dt = -100 A/μs; V _{GS} = 0 V; | - | 34 | - | ns |
| Q _r | recovered charge | V _R = 30 V | - | 12 | - | nC |




Fig 5. Output characteristics: drain current as a function of drain-source voltage; typical values




Fig 6. Drain-source on-state resistance as a function of drain current; typical values




Fig 7. Transfer characteristics: drain current as a function of gate-source voltage; typical values






Fig 8. Normalized drain-source on-state resistance factor as a function of junction temperature




$I_D = 1 \text{ mA}; V_{DS} = V_{GS}$

Fig 9. Gate-source threshold voltage as a function of junction temperature




$T_j = 25 \text{ °C}; V_{DS} = 5 \text{ V}$

Fig 10. Sub-threshold drain current as a function of gate-source voltage




$I_D = 15 \text{ A}; V_{DS} = 12 \text{ V and } 19 \text{ V}$

Fig 11. Gate-source voltage as a function of gate charge; typical values




003aaa508

Fig 12. Gate charge waveform definitions



$T_J = 25^\circ\text{C}$ and 150°C ; $V_{GS} = 0\text{ V}$

Fig 13. Source (diode forward) current as a function of source-drain (diode forward) voltage; typical values




$V_{GS} = 0\text{ V}$; $f = 1\text{ MHz}$

Fig 14. Input, output and reverse transfer capacitances as a function of drain-source voltage; typical values

7. Package outline

Plastic single-ended surface mounted package (LPAK); 4 leads

SOT669



DIMENSIONS (mm are the original dimensions)

| UNIT | A | A ₁ | A ₂ | A ₃ | b | b ₂ | b ₃ | b ₄ | c | c ₂ | D ⁽¹⁾ | D ₁ ⁽¹⁾ max | E ⁽¹⁾ | E ₁ ⁽¹⁾ | e | H | L | L ₁ | L ₂ | w | y | θ |
|------|--------------|----------------|----------------|----------------|--------------|----------------|----------------|----------------|--------------|----------------|------------------|-----------------------------------|------------------|-------------------------------|------|------------|--------------|----------------|----------------|------|-----|----------|
| mm | 1.20 1.01 | 0.15 0.00 | 1.10 0.95 | 0.25 | 0.50 0.35 | 4.41 3.62 | 2.2 2.0 | 0.9 0.7 | 0.25 0.19 | 0.30 0.24 | 4.10 3.80 | 4.20 | 5.0 4.8 | 3.3 3.1 | 1.27 | 6.2 5.8 | 0.85 0.40 | 1.3 0.8 | 1.3 0.8 | 0.25 | 0.1 | 8° 0° |

Note

1. Plastic or metal protrusions of 0.15 mm maximum per side are not included.

| OUTLINE VERSION | REFERENCES | | | | EUROPEAN PROJECTION | ISSUE DATE |
|-----------------|------------|--------|-------|--|---------------------|----------------------|
| | IEC | JEDEC | JEITA | | | |
| SOT669 | | MO-235 | | | | 03-09-15 04-10-13 |

Fig 15. Package outline SOT669 (LPAK)

8. Revision history

Table 6: Revision history

| Document ID | Release date | Data sheet status | Change notice | Doc. number | Supersedes |
|-------------|--------------|--------------------|---------------|----------------|------------|
| PH16030L_1 | 20050224 | Product data sheet | - | 9397 750 14431 | - |

9. Data sheet status

| Level | Data sheet status ^[1] | Product status ^{[2] [3]} | Definition |
|-------|----------------------------------|-----------------------------------|--|
| I | Objective data | Development | This data sheet contains data from the objective specification for product development. Philips Semiconductors reserves the right to change the specification in any manner without notice. |
| II | Preliminary data | Qualification | This data sheet contains data from the preliminary specification. Supplementary data will be published at a later date. Philips Semiconductors reserves the right to change the specification without notice, in order to improve the design and supply the best possible product. |
| III | Product data | Production | This data sheet contains data from the product specification. Philips Semiconductors reserves the right to make changes at any time in order to improve the design, manufacturing and supply. Relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN). |

[1] Please consult the most recently issued data sheet before initiating or completing a design.

[2] The product status of the device(s) described in this data sheet may have changed since this data sheet was published. The latest information is available on the Internet at URL <http://www.semiconductors.philips.com>.

[3] For data sheets describing multiple type numbers, the highest-level product status determines the data sheet status.

10. Definitions

Short-form specification — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

Limiting values definition — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 60134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

Application information — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors make no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

11. Disclaimers

Life support — These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors

13. Contact information

For additional information, please visit: <http://www.semiconductors.philips.com>

For sales office addresses, send an email to: sales.addresses@www.semiconductors.philips.com

customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

Right to make changes — Philips Semiconductors reserves the right to make changes in the products - including circuits, standard cells, and/or software - described or contained herein in order to improve design and/or performance. When the product is in full production (status 'Production'), relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN). Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no license or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

12. Trademarks

TrenchMOS — is a trademark of Koninklijke Philips Electronics N.V.

14. Contents

| | | |
|-----------|--------------------------------------|-----------|
| 1 | Product profile | 1 |
| 1.1 | General description | 1 |
| 1.2 | Features | 1 |
| 1.3 | Applications | 1 |
| 1.4 | Quick reference data | 1 |
| 2 | Pinning information | 1 |
| 3 | Ordering information | 2 |
| 4 | Limiting values | 2 |
| 5 | Thermal characteristics | 4 |
| 6 | Characteristics | 5 |
| 7 | Package outline | 9 |
| 8 | Revision history | 10 |
| 9 | Data sheet status | 11 |
| 10 | Definitions | 11 |
| 11 | Disclaimers | 11 |
| 12 | Trademarks | 11 |
| 13 | Contact information | 11 |



© Koninklijke Philips Electronics N.V. 2005

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Date of release: 24 February 2005
Document number: 9397 750 14431

Published in The Netherlands