

P-tec Corp. Tel: (800) 688-0613
 2405 Commerce Circle Tel: (719) 589 3122
 Alamosa Co. 81101 Fax: (719) 589 3592
 www.p-tec.net sales@p-tec.net



PL03 Series 3mm (T1) LED

Features

- *Popular 3mm Lens Style with Flange
- *1 InGaN Ultra Bright White Chip used
- *High Light Output
- *Long Life & Reliability
- *Integrated Zener Diode for ESD Protection
- *RoHS Compliant

Absolute Maximum Ratings at $T_A = 25^\circ\text{C}$

Power Dissipation	120mW
Reverse Voltage (<5.0 μ A).....	5.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range.....	-25°C to +85°C
Storage Temperature Range.....	-40°C to +100°C
Soldering Temperature (1.6mm below body).....	260°C for 5 seconds
Electric Static Discharge Threshold (HBM).....	6000V

Electrical & Optical Characteristics at $T_A = 25^\circ\text{C}$

Part Number	Emitting Color	Chip Material	Chromaticity Coordinates		Viewing Angle 2 θ ½	Reverse Current V _r =5V (μ A)	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
			X Axis	Y Axis			Typ	Max	Min	Typ
PL03F-WCW24Z	White	InGaN	0.31	0.30	30°	50	3.2	4.0	1950	5500

All dimensions are in **Millimeters**. Tolerance is $\pm 0.25\text{mm}$ unless otherwise specified. An epoxy meniscus may extend about 1mm down the leads.

