

Europa Components

Battery charges 146 418.

change of design 29/11/83, r/p Dr Sheindan.

Battery positions 1 & 2 : now 250 mA for AA cells
" " 3 & 4 : 150 mA for C & D cells.

This now permits the float charging of AA cells
(previously limited to max 5 hrs).

Note that in practical terms, C, D & AA cells
may only be charged in pairs.

ie 2C (+2AA)
2D (+2AA)
or 2AA.

not 4C or 4D.



**Ni-Cad
Battery Charger**
Order Code 146-418
Farnell Electronic Components Ltd
Canal Road, Leeds LS12 2TU
Tel: (0532) 636311 Telex 56147



CHARGE FOR 14 HRS

use only

Sockets 1+2

Charge for 14 hrs

146 418



MADE IN HONG KONG

Automatic Battery Charger

Cat. No. NC-383M

Charges Nickel cadmium batteries in AA, C, D or 9 volt sizes

For best results charge batteries at first sign of battery weakness (e.g. dim flashlight, weak calculator display, reduced radio volume, slow movement of toys, etc.)

If battery is completely dead, it cannot be recharged

Recharge AA, C and D cells. Insert AA, C and/or D cells in charger in pairs starting in chamber no 1 pointed end of battery should face + symbol in charger

Close lid, plug in unit (Charging indicator will light)
Charge for times indicated below

Battery Size	Charging Time
AA cells	5 Hours
C cells	15 Hours
D cells	24 Hours
9 volt	15 Hours

Input AC 220V - 240V 50Hz 3W
Output 2.6V DC 150mA 9V DC 10mA



WARNING

When this unit is not in use also before attempting internal examination, remove the mains plug from the wall socket.

3111 158 01921