


# Panasonic

## Multilayer Ceramic Capacitors<sup>(For General)</sup>

### Multilayer Ceramic Chip Capacitors (For General Electronic Equipment)



Series: **ECU**  
Series: **ECJ**

■ Features

- Small in size and wide capacitance range
- Superior humidity characteristics and long life thanks to monolithic construction
- Excellent solderability and resistance to soldering heat thanks to terminals with three layers of silver, nickel, and solder
- Low self-inductance and excellent frequency characteristics

■ Recommended Applications

- Class 1 (T.C. Type)  
Temperature compensation, tuned circuits, and filter circuits, where low loss, high stability of capacitance, and high insulation resistance are required
- Class 2 (Hi-K Type)  
Coupling and By-pass, where low loss and high stability of capacitance are not so important

■ Explanation of Part Numbers

- ECU Series

1 2 3 4 5 6 7 8 9 10 11 12 (Example)

**E C U X 1 H 1 0 1 J C G**

Product Code	Packaging Styles		Rated Voltage		Nominal Capacitance		Capacitance Tolerance			Temperature Characteristics		Suffix		
	Code	Styles	Code	Voltage	Ex.	Cap.	Code	Tol.	Note	Code	Temp.Char.	Code	Size Code	
ECU Multilayer Ceramic Chip Capacitors	X	Bulk	1H	50 VDC	0R5	0.5 pF	C	±0.25 pF	≤10 pF	C	NP0	Q	10 type 0402	
	E	Paper Taping (Pitch: 2 mm)	1E	25 VDC	010	1 pF	D	±0.5 pF		P	N150	V	11 type 0603	
	V	Paper Taping (Pitch: 4 mm)	1C	16 VDC	100	10 pF	F	±1 pF		R	N220	N/G	12 type 0805	
	Y	Embossed Taping (Pitch: 4 mm)			101	100 pF	J	±5 %		S	N330	X	12 type 1206	
	W	Large Size Reel Taping (Pitch: 2 mm)			104	100000 pF (0.1 μF)	K	±10 %		T	N470	M/H	13 type 1206	
	Z	Large Size Reel Taping (Pitch: 4 mm)					M	±20 %		U	N750	W	13 type 1206	
	C	Bulk Case					Z	+80 % -20 %		Nil*	SL/GP			
										B	B/X7R			
										F	F/Y5V			

\* When omitted, all the rest P/N factors shall be moved up respectively

- ECJ Series

1 2 3 4 5 6 7 8 9 10 11 12 (Example)

**E C J 3 Y F 1 C 4 7 5 Z**

Product Code	Suffix		Packaging Styles		Temperature Characteristics		Rated Voltage		Nominal Capacitance		Capacitance Tolerance		
	Code	Size Code (EIA)	Code	Styles	Code	Temp.Char.	Code	Voltage	Ex.	Cap.	Code	Tol.	Note
ECJ Multilayer Ceramic Chip Capacitors	0	10 type (0402)	X	Bulk	B	B/X7R	1H	50 VDC	103	10000 pF	K	±10 %	>10 pF
	1	11 type (0603)	E	Paper Taping (Pitch: 2 mm)	F	F/Y5V	1E	25 VDC	104	100000 pF (0.1 μF)	M	±20 %	
	2	12 type (0805)	V	Paper Taping (Pitch: 4 mm)			1C	16 VDC	105	1 μF	Z	+80 % -20 %	
	3	13 type (1206)	Y	Embossed Taping (Pitch: 4 mm)			1A	10 VDC					
			W	Large Size Reel Taping (Pitch: 2 mm)									
			Z	Large Size Reel Taping (Pitch: 4 mm)									
			C	Bulk Case									

■ Precautions for Handling




See Page 26 to 30

Design and Specifications are subject to change without notice. Ask factory for technical specifications before purchase and/or use. Whenever a doubt about safety issues arises from this product, please inform us immediately for technical consultation.

# Panasonic

## Multilayer Ceramic Capacitors<sup>(For General)</sup>

### ■ Construction



### ■ Dimensions in mm (not to scale)

Size Code (EIA)	L	W	T	L <sub>1</sub> , L <sub>2</sub>
"10" Type (0402)	1.00±0.05	0.50±0.05	0.50±0.05	0.20±0.10
"11" Type (0603)	1.60±0.10	0.80±0.10	0.80±0.10	0.30±0.20
"12" Type (0805)	2.00±0.10	1.25±0.10	1.35 max.*	0.50±0.25
"13" Type (1206)	3.20±0.15	1.60±0.15	1.8 max.*	0.60±0.30

\* Specified by the nominal capacitance

### ■ Capacitance Range in pF

#### ● T.C. Type

Class	Size Code (EIA)	Dim. "T" (mm)	Capacitance Range (pF) [50 VDC]						
			NP0 CΔ	SL 50VDC	N150	N220	N330	N470	N750
					PA*	RA*	SΔ*	TΔ*	UΔ*
1	"10" (0402)	0.50±0.05	0.5-220	0.5-220	0.5-39	0.5-39	0.5-39	0.5-39	0.5-120
	"11" (0603)	0.80±0.1	0.5-1000	0.5-1200	0.5-150	0.5-180	0.5-180	0.5-220	0.5-1200
	"12" (0805)	0.6±0.1	0.5-2200	0.5-2700	0.5-220	0.5-220	0.5-220	0.5-270	0.5-2700
		0.85±0.10	2400, 2700	—	240-330	240-390	240-470	300-470	—
	"13" (1206)	0.6±0.1	2400-4700	3000-5600	240-560	240-680	240-680	300-820	3000-5600
		0.85±0.10	5100-6800	—	620-1200	750-1200	750-1500	910-1500	—
		1.15±0.10	7500-10000	—	—	—	—	—	

\* PA to UA : Special order

● (Capacitance values) E12 series : Standard order, E24 series : Special order

#### ● Hi-K Type

Class	Size Code (EIA)	Dim. "T" (mm)	Capacitance Range (pF)							
			B [X7R]				F [Y5V]			
			50 VDC	25 VDC	16 VDC	10 VDC	50 VDC	25 VDC	16 VDC	10 VDC
2	"10" (0402)	0.50±0.05	100-3900	100-6800	5600-15000	—	1000-10000	1000-22000	15000-100000	—
	"11" (0603)	0.8±0.1	220-15000	10000-47000	10000-100000	120000-220000	1000-47000	68000, 100000	100000-470000	1000000
		0.6±0.1	1000-22000	—	—	—	10000-68000	68000-150000	100000-220000	—
	"12" (0805)	0.85±0.10	27000-39000	39000-100000	47000-220000	—	100000-220000	220000	330000-1000000	—
		1.25±0.10	47000-100000	120000-220000	270000-470000	560000-1000000	—	330000, 470000	1500000, 2200000	3300000, 4700000
	"13" (1206)	0.85±0.10	—	100000-330000	100000-680000	—	—	470000	680000-2200000	—
1.15±0.10		—	390000-470000	820000, 1000000	—	—	680000-2200000	3300000, 4700000	—	
		1.6±0.2	—	560000-1000000	—	200000-3300000	—	—	10000000	

● (Capacitance values) B[X7R] E6 series : Standard order, E12 series : Special order

F[Y5V] E3 series : Standard order, E6 series : Special order

Design and Specifications are subject to change without notice. Ask factory for technical specifications before purchase and/or use. Whenever a doubt about safety issues arises from this product, please inform us immediately for technical consultation.

**Panasonic****Multilayer Ceramic Capacitors<sup>(For General)</sup>**

### ■ Nominal Capacitance vs. Capacitance Tolerance

Tol. Code	Capacitance Tolerance	Nominal Capacitance Available (pF)		Temp. Char.	Class	
C	≤ 10 pF	±0.25 pF	0.5, 1, 1.5, 2, 3, 4, 5		CΔ to UΔ (NPO) (N750) and SL	1 (T.C. Type)
D		±0.5 pF	1, 1.5, 2, 3, 4, 5, 6, 7, 8, 9, 10			
F		±1.0 pF	10			
J	> 10 pF	±5 %	E24	Within Capacitance Range, E-Series Numbers ×10 <sup>n</sup>	B (X7R) F (Y5V)	2 (Hi-K Type)
K		±10 %	E12			
K		±10 %	E12			
M		±20 %	E6			
Z	+80, -20 %	E6				

### ■ E-Series Numbers

E3	1				2.2				4.7															
E6	1		1.5		2.2		3.3		4.7		6.8													
E12	1	1.2	1.5	1.8	2.2	2.7	3.3	3.9	4.7	5.6	6.8	8.2												
E24	1	1.1	1.2	1.3	1.5	1.6	1.8	2	2.2	2.4	2.7	3	3.3	3.6	3.9	4.3	4.7	5.1	5.6	6.2	6.8	7.5	8.2	9.1

### ■ Temperature Coefficient of Class 1 Capacitors/T.C. Tolerance

(ppm/°C)

Temp. Coeff. Code.	Cap.	CΔ (NPO)	PΔ (N150)	RΔ (N220)	SΔ (N330)	TΔ (N470)	UΔ (N750)	SL
		T.C.	T.C.	T.C.	T.C.	T.C.	T.C.	T.C.
T.C. Tol.	≤ 2 pF	CK(±250)	PK(±250)	RK(±250)	SK(±250)	TK(±250)	UK(±250)	+350 to -1000
	3 pF	CJ(±120)	PJ(±120)	RJ(±120)	SJ(±120)	TJ(±120)	UJ(±120)	+350 to -1000
	≥ 4 pF	CH(±60)	PH(±60)	RH(±60)	SH(±60)	TH(±60)	UJ(±120)	+350 to -1000

### ■ Temperature Characteristics of Class 2 Capacitors

Temp. Char.	Capacitance Change		Measurement Temperature Range	Reference Temperature
	No DC Voltage Applied	1/2 Rated Voltage Applied		
B (X7R)	±10 % max.	+10, -30 % max.	-25 to 85 °C	20 °C
F (Y5V)	+30, -80 % max.	+30, -95 % max.	-25 to 85 °C	20 °C

Design and Specifications are subject to change without notice. Ask factory for technical specifications before purchase and/or use.  
Whenever a doubt about safety issues arises from this product, please inform us immediately for technical consultation.

# Panasonic


## Multilayer Ceramic Capacitors<sup>(For General)</sup>

### Specifications


Characteristics	Specifications			Test Methods								
	Class 1 (T.C. Type)	Class 2 (Hi-K Type)										
	CΔ to UΔ, SL	B(X7R)	F(Y5V)									
Operating Temperature Range	-55 to 125 °C*		-25 to 85 °C	—								
Rated Voltage	50 VDC	50 VDC, 25 VDC 16 VDC, 10 VDC		—								
Dielectric Withstanding Voltage	No break down			Test Voltage Class 1: Rated Voltage x3 Class 2: Rated Voltage x2.5 Electrification time : 1 to 5 s Limit surge current: 50 mA max.								
Insulation Resistance(IR)	IR ≥ 10000MΩ	IR ≥ 10000MΩ or 500/C (MΩ) whichever is less [C: Rated capacitance in μF]		Measurement Voltage: Rated Voltage Electrification time : 60 ± 5 s (Electrification time of 10VDC is 2 minutes) Limit surge current: 50 mA max.								
Capacitance	Within the specified tolerance			Standard Temperature : 20 °C Measurement								
Q Factor or Dissipation Factor (tan δ)	Capacitance < 30 pF Q ≥ 400+20 C*** 30 pF ≤ Cap. ≤ 1000 pF Q ≥ 1000 Capacitance > 1000 pF (tan δ) ≤ 0.002	Temperature Characteristics		<table border="1"> <thead> <tr> <th>Nominal Cap</th> <th>Frequency</th> <th>Voltage</th> </tr> </thead> <tbody> <tr> <td>C ≤ 1000 pF</td> <td>1 MHz ± 10 %</td> <td rowspan="2">0.5-5 Vrms</td> </tr> <tr> <td>C &gt; 1000 pF</td> <td>1 kHz ± 10 %</td> </tr> </tbody> </table>	Nominal Cap	Frequency	Voltage	C ≤ 1000 pF	1 MHz ± 10 %	0.5-5 Vrms	C > 1000 pF	1 kHz ± 10 %
		Nominal Cap	Frequency		Voltage							
C ≤ 1000 pF	1 MHz ± 10 %	0.5-5 Vrms										
C > 1000 pF	1 kHz ± 10 %											
		Rated Voltage	Characteristics	(1) Class 1 (T.C. Type)								
		50 VDC	B									
		25 VDC	F									
		16 VDC		(2) Class 2 (Hi-K Type)								
		10 VDC		Pretreatment : 150+0/-10 °C for 1 hour and then shall be stored in a room temperature for 48 ± 4 hours, before initial measurement.								
				<table border="1"> <thead> <tr> <th>Frequency</th> <th>Voltage</th> </tr> </thead> <tbody> <tr> <td>1 kHz ± 10 %</td> <td>1.0 ± 0.2 Vrms</td> </tr> </tbody> </table>	Frequency	Voltage	1 kHz ± 10 %	1.0 ± 0.2 Vrms				
Frequency	Voltage											
1 kHz ± 10 %	1.0 ± 0.2 Vrms											

\* Operating Temperature Range: -25 to 85 °C for capacitance range of 5100 to 10000 pF, NPO, Type 13.  
 \*\* Specified by individual Specification  
 \*\*\* Nominal capacitance value in pF

Minimum Q at 1 MHz



Minimum Insulation Resistance



Design and Specifications are subject to change without notice. Ask factory for technical specifications before purchase and/or use.  
 Whenever a doubt about safety issues arises from this product, please inform us immediately for technical consultation.

# Panasonic


## Multilayer Ceramic Capacitors<sup>(For General)</sup>

- Capacitance Range (in pF)
- [Size Code "10" Type/"0402"]

Temp. Char. Rated Voltage Cap. (pF)	CΔ (NPO)	SL (50 V)	PΔ (N150)	RΔ (N220)	SΔ (N330)	TΔ (N470)	UΔ (N750)
	0.5						
1							
1.5							
2							
3							
4							
5							
6							
7							
8							
9							
10							
11							
12							
13							
15							
16							
18							
20							
22							
24							
27							
30							
33							
36							
39							
43							
47							
51							
56							
62							
68							
75							
82							
91							
100							
110							
120							
130							
150							
160							
180							
200							
220							

Temp. Char. Rated Voltage Cap. (pF)	B/X7R			F/Y5V		
	50 V	25 V	16 V	50 V	25 V	16 V
100						
120						
150						
180						
220						
270						
330						
390						
470						
560						
680						
820						
1000						
1200						
1500						
1800						
2200						
2700						
3300						
3900						
4700						
5600						
6800						
8200						
10000						
12000						
15000						
18000						
22000						
27000						
33000						
39000						
47000						
56000						
68000						
82000						
100000						

■ Dimensions in mm (not to scale)  
[10 Type] [0402(EIA)]



Design and Specifications are subject to change without notice. Ask factory for technical specifications before purchase and/or use. Whenever a doubt about safety issues arises from this product, please inform us immediately for technical consultation.

# Panasonic

## Multilayer Ceramic Capacitors<sup>(For General)</sup>


- Capacitance Range (in pF)
- [Size Code "11" Type/ "0603" (EIA)]

Temp. Char. Rated Voltage Cap. (pF)	CΔ (NPO)		SL	PΔ (N150)	RΔ (N220)	SΔ (N330)	TΔ (N470)	UΔ (N750)
	50 V	50 V	50 V	50 V	50 V	50 V	50 V	50 V
0.5								
1								
1.5								
2								
3								
4								
5								
6								
7								
8								
9								
10								
11								
12								
13								
15								
16								
18								
20								
22								
24								
27								
30								
33								
36								
39								
43								
47								
51								
56								
62								
68								
75								
82								
91								
100								
110								
120								
130								
150								
160								
180								
200								
220								
240								
270								
300								
330								
360								
390								
430								
470								
510								
560								
620								
680								
750								
820								
910								
1000								
1100								
1200								

Temp. Char. Rated Voltage Cap. (pF)	B/X7R				F/Y5V			
	50 V	25 V	16 V	6-10V	50 V	25 V	16 V	6-10V
220								
270								
330								
390								
470								
560								
680								
820								
1000								
1200								
1500								
1800								
2200								
2700								
3300								
3900								
4700								
5600								
6800								
8200								
10000								
12000								
15000								
18000								
22000								
27000								
33000								
39000								
47000								
56000								
68000								
82000								
100000								
120000								
150000								
180000								
220000								
270000								
330000								
390000								
470000								
560000								
680000								
820000								
1000000								

\* Under development

- Dimensions in mm (not to scale)
- [11 Type] [0603 (EIA)]



Design and Specifications are subject to change without notice. Ask factory for technical specifications before purchase and/or use. Whenever a doubt about safety issues arises from this product, please inform us immediately for technical consultation.


# Panasonic

## Multilayer Ceramic Capacitors (For General)

- Capacitance Range (in pF)
- [Size Code "12" Type/ "0805" (EIA)]

Temp. Char. Rate of Change	CΔ (NP0)		SL	PΔ (N150)		RΔ (N220)	SΔ (N330)	TΔ (N470)	UΔ (N750)
	50 V	50 V	50 V	50 V	50 V	50 V	50 V	50 V	50 V
0.5									
1									
1.5									
2									
3									
4									
5									
6									
7									
8									
9									
10									
11									
12									
13									
15									
16									
18									
20									
22									
24									
27									
30									
33									
36									
39									
43									
47									
51									
56									
62									
68									
75									
82									
91									
100									
110									
120									
130									
150									
160									
180									
200									
220									
240									
270									
300									
330									
360									
390									
430									
470									
510									
560									
620									
680									
750									
820									
910									
1000									
1100									
1200									
1300									
1500									
1600									
1800									
2000									
2200									
2400									
2700									

Temp. Char. Rate of Change	B/X7R				F/Y5V			
	50 V	25 V	16 V	6-10 V	50 V	25 V	16 V	6-10 V
220								
270								
330								
390								
470								
560								
680								
820								
1000								
1200								
1500								
1800								
2200								
2700								
3300								
3900								
4700								
5600								
6800								
8200								
10000								
12000								
15000								
18000								
22000								
27000								
33000								
39000								
47000								
56000								
68000								
82000								
100000								
120000								
150000								
180000								
220000								
270000								
330000								
390000								
470000								
560000								
680000								
820000								
1000000								
1200000								
1500000								
1800000								
2200000								
2700000								
3300000								
3900000								
4700000								



■ Thickness "T"

T (mm)
0.6±0.1
0.85±0.10
1.25±0.10

Design and Specifications are subject to change without notice. Ask factory for technical specifications before purchase and/or use. Whenever a doubt about safety issues arises from this product, please inform us immediately for technical consultation.

# Panasonic

## Multilayer Ceramic Capacitors (For General)


- Capacitance Range (in pF)
- [Size Code "13" Type/ "1206" (EIA)]

Cap. (pF)	Temp. Char. Rated Voltage	CA	SL	PA	RA	SA	TΔ	UA
		(NP0) 50 V	50 V	(N150) 50 V	(N220) 50 V	(N330) 50 V	(N470) 50 V	(N750) 50 V
240								
270								
300								
330								
360								
390								
430								
470								
510								
560								
620								
680								
750								
820								
910								
1000								
1100								
1200								
1300								
1500								
1600								
1800								
2000								
2200								
2400								
2700								
3000								
3300								
3600								
3900								
4300								
4700								
5100								
5600								
6200								
6800								
7500								
8200								
9100								
10000								

Cap. (pF)	Temp. Char. Rated Voltage	B/X7R				F/Y5V			
		50 V	25 V	16 V	6-10 V	50 V	25 V	16 V	6-10 V
68000									
82000									
100000									
120000									
150000									
180000									
220000									
270000									
330000									
390000									
470000									
560000									
680000									
820000									
1000000									
1200000									
1500000									
1800000									
2200000									
2700000									
3300000									
3900000									
4700000									
5600000									
6800000									
8200000									
10000000									

\* Under development

- Dimensions in mm (not to scale)
- [13 Type] [1206 (EIA)]



- Thickness "T"

	T (mm)
	0.6±0.1
	0.85±0.10
	1.15±0.10
	1.6±0.2

• T 1.6mm : L=3.20±0.20, W=1.60±0.20

Design and Specifications are subject to change without notice. Ask factory for technical specifications before purchase and/or use. Whenever a doubt about safety issues arises from this product, please inform us immediately for technical consultation.





Multilayer Ceramic Capacitors<sup>(For General)</sup>

■ Standard Products for "10" Type (EIA "0402" Type), Taped Version [Rated Voltage 50 VDC]

Capacitance (pF)	Capacitance Tolerance	CA (NP0)		SL		PA (N150)		RA (N220)		SA (N330)		TA (N470)		UA (N750)	
		Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)
0.5	±0.25 pF (C)	ECUE1H0R5C0Q	0.5	ECUE1H0R5C0Q	0.5	ECUE1H0R5C0P	0.5	ECUE1H0R5C0Q	0.5	ECUE1H0R6C0Q	0.5	ECUE1H0R6C0Q	0.5	ECUE1H0R5C0Q	0.5
1	±0.25 pF (C)	ECUE1H010C0Q	0.5	ECUE1H010C0Q	0.5	ECUE1H010C0P	0.5	ECUE1H010C0Q	0.5	ECUE1H010C0Q	0.5	ECUE1H010C0Q	0.5	ECUE1H010C0Q	0.5
1.5		ECUE1H1R5C0Q	0.5	ECUE1H1R5C0Q	0.5	ECUE1H1R5C0P	0.5	ECUE1H1R5C0Q	0.5	ECUE1H1R5C0Q	0.5	ECUE1H1R5C0Q	0.5	ECUE1H1R5C0Q	0.5
2	±0.5 pF (D)	ECUE1H020C0Q	0.5	ECUE1H020C0Q	0.5	ECUE1H020C0P	0.5	ECUE1H020C0Q	0.5	ECUE1H020C0Q	0.5	ECUE1H020C0Q	0.5	ECUE1H020C0Q	0.5
3		ECUE1H030C0Q	0.5	ECUE1H030C0Q	0.5	ECUE1H030C0P	0.5	ECUE1H030C0Q	0.5	ECUE1H030C0Q	0.5	ECUE1H030C0Q	0.5	ECUE1H030C0Q	0.5
4	±0.5 pF (D)	ECUE1H040C0Q	0.5	ECUE1H040C0Q	0.5	ECUE1H040C0P	0.5	ECUE1H040C0Q	0.5	ECUE1H040C0Q	0.5	ECUE1H040C0Q	0.5	ECUE1H040C0Q	0.5
5		ECUE1H050C0Q	0.5	ECUE1H050C0Q	0.5	ECUE1H050C0P	0.5	ECUE1H050C0Q	0.5	ECUE1H050C0Q	0.5	ECUE1H050C0Q	0.5	ECUE1H050C0Q	0.5
6	±0.5 pF (D)	ECUE1H060C0Q	0.5	ECUE1H060C0Q	0.5	ECUE1H060C0P	0.5	ECUE1H060C0Q	0.5	ECUE1H060C0Q	0.5	ECUE1H060C0Q	0.5	ECUE1H060C0Q	0.5
7		ECUE1H070C0Q	0.5	ECUE1H070C0Q	0.5	ECUE1H070C0P	0.5	ECUE1H070C0Q	0.5	ECUE1H070C0Q	0.5	ECUE1H070C0Q	0.5	ECUE1H070C0Q	0.5
8	±0.5 pF (D)	ECUE1H080C0Q	0.5	ECUE1H080C0Q	0.5	ECUE1H080C0P	0.5	ECUE1H080C0Q	0.5	ECUE1H080C0Q	0.5	ECUE1H080C0Q	0.5	ECUE1H080C0Q	0.5
9		ECUE1H090C0Q	0.5	ECUE1H090C0Q	0.5	ECUE1H090C0P	0.5	ECUE1H090C0Q	0.5	ECUE1H090C0Q	0.5	ECUE1H090C0Q	0.5	ECUE1H090C0Q	0.5
10	±0.5 pF (D) or ±1 pF (F)	ECUE1H100C0Q	0.5	ECUE1H100C0Q	0.5	ECUE1H100C0P	0.5	ECUE1H100C0Q	0.5	ECUE1H100C0Q	0.5	ECUE1H100C0Q	0.5	ECUE1H100C0Q	0.5
11	±5%*** (J) or ±10% (K)	ECUE1H110C0Q	0.5	ECUE1H110C0Q	0.5	ECUE1H110C0P	0.5	ECUE1H110C0Q	0.5	ECUE1H110C0Q	0.5	ECUE1H110C0Q	0.5	ECUE1H110C0Q	0.5
12		ECUE1H120C0Q	0.5	ECUE1H120C0Q	0.5	ECUE1H120C0P	0.5	ECUE1H120C0Q	0.5	ECUE1H120C0Q	0.5	ECUE1H120C0Q	0.5	ECUE1H120C0Q	0.5
13	±5%*** (J) or ±10% (K)	ECUE1H130C0Q	0.5	ECUE1H130C0Q	0.5	ECUE1H130C0P	0.5	ECUE1H130C0Q	0.5	ECUE1H130C0Q	0.5	ECUE1H130C0Q	0.5	ECUE1H130C0Q	0.5
15		ECUE1H150C0Q	0.5	ECUE1H150C0Q	0.5	ECUE1H150C0P	0.5	ECUE1H150C0Q	0.5	ECUE1H150C0Q	0.5	ECUE1H150C0Q	0.5	ECUE1H150C0Q	0.5
16	±5%*** (J) or ±10% (K)	ECUE1H160C0Q	0.5	ECUE1H160C0Q	0.5	ECUE1H160C0P	0.5	ECUE1H160C0Q	0.5	ECUE1H160C0Q	0.5	ECUE1H160C0Q	0.5	ECUE1H160C0Q	0.5
18		ECUE1H180C0Q	0.5	ECUE1H180C0Q	0.5	ECUE1H180C0P	0.5	ECUE1H180C0Q	0.5	ECUE1H180C0Q	0.5	ECUE1H180C0Q	0.5	ECUE1H180C0Q	0.5
20	±5%*** (J) or ±10% (K)	ECUE1H200C0Q	0.5	ECUE1H200C0Q	0.5	ECUE1H200C0P	0.5	ECUE1H200C0Q	0.5	ECUE1H200C0Q	0.5	ECUE1H200C0Q	0.5	ECUE1H200C0Q	0.5
22		ECUE1H220C0Q	0.5	ECUE1H220C0Q	0.5	ECUE1H220C0P	0.5	ECUE1H220C0Q	0.5	ECUE1H220C0Q	0.5	ECUE1H220C0Q	0.5	ECUE1H220C0Q	0.5
24	±5%*** (J) or ±10% (K)	ECUE1H240C0Q	0.5	ECUE1H240C0Q	0.5	ECUE1H240C0P	0.5	ECUE1H240C0Q	0.5	ECUE1H240C0Q	0.5	ECUE1H240C0Q	0.5	ECUE1H240C0Q	0.5
27		ECUE1H270C0Q	0.5	ECUE1H270C0Q	0.5	ECUE1H270C0P	0.5	ECUE1H270C0Q	0.5	ECUE1H270C0Q	0.5	ECUE1H270C0Q	0.5	ECUE1H270C0Q	0.5
30	±5%*** (J) or ±10% (K)	ECUE1H300C0Q	0.5	ECUE1H300C0Q	0.5	ECUE1H300C0P	0.5	ECUE1H300C0Q	0.5	ECUE1H300C0Q	0.5	ECUE1H300C0Q	0.5	ECUE1H300C0Q	0.5
33		ECUE1H330C0Q	0.5	ECUE1H330C0Q	0.5	ECUE1H330C0P	0.5	ECUE1H330C0Q	0.5	ECUE1H330C0Q	0.5	ECUE1H330C0Q	0.5	ECUE1H330C0Q	0.5
36	±5%*** (J) or ±10% (K)	ECUE1H360C0Q	0.5	ECUE1H360C0Q	0.5	ECUE1H360C0P	0.5	ECUE1H360C0Q	0.5	ECUE1H360C0Q	0.5	ECUE1H360C0Q	0.5	ECUE1H360C0Q	0.5
39		ECUE1H390C0Q	0.5	ECUE1H390C0Q	0.5	ECUE1H390C0P	0.5	ECUE1H390C0Q	0.5	ECUE1H390C0Q	0.5	ECUE1H390C0Q	0.5	ECUE1H390C0Q	0.5
43	±5%*** (J) or ±10% (K)	ECUE1H430C0Q	0.5	ECUE1H430C0Q	0.5								ECUE1H430C0Q	0.5	
47		ECUE1H470C0Q	0.5	ECUE1H470C0Q	0.5								ECUE1H470C0Q	0.5	
51	±5%*** (J) or ±10% (K)	ECUE1H510C0Q	0.5	ECUE1H510C0Q	0.5								ECUE1H510C0Q	0.5	
56		ECUE1H560C0Q	0.5	ECUE1H560C0Q	0.5								ECUE1H560C0Q	0.5	
62	±5%*** (J) or ±10% (K)	ECUE1H620C0Q	0.5	ECUE1H620C0Q	0.5								ECUE1H620C0Q	0.5	
68		ECUE1H680C0Q	0.5	ECUE1H680C0Q	0.5								ECUE1H680C0Q	0.5	
75	±5%*** (J) or ±10% (K)	ECUE1H750C0Q	0.5	ECUE1H750C0Q	0.5								ECUE1H750C0Q	0.5	
82		ECUE1H820C0Q	0.5	ECUE1H820C0Q	0.5								ECUE1H820C0Q	0.5	
91	±5%*** (J) or ±10% (K)	ECUE1H910C0Q	0.5	ECUE1H910C0Q	0.5								ECUE1H910C0Q	0.5	
100		ECUE1H101C0Q	0.5	ECUE1H101C0Q	0.5								ECUE1H101C0Q	0.5	
110	±5%*** (J) or ±10% (K)	ECUE1H111C0Q	0.5	ECUE1H111C0Q	0.5								ECUE1H111C0Q	0.5	
120		ECUE1H121C0Q	0.5	ECUE1H121C0Q	0.5								ECUE1H121C0Q	0.5	
130	±5%*** (J) or ±10% (K)	ECUE1H131C0Q	0.5	ECUE1H131C0Q	0.5										
150		ECUE1H151C0Q	0.5	ECUE1H151C0Q	0.5										
160	±5%*** (J) or ±10% (K)	ECUE1H161C0Q	0.5	ECUE1H161C0Q	0.5										
180		ECUE1H181C0Q	0.5	ECUE1H181C0Q	0.5										
200	±5%*** (J) or ±10% (K)	ECUE1H201C0Q	0.5	ECUE1H201C0Q	0.5										
220		ECUE1H221C0Q	0.5	ECUE1H221C0Q	0.5										

(Packing Style Code)\*

\*Packaging Style Code: "E" for Taped Version (Taping pitch: 2 mm) and "X" for Bulk Type.  
 \*\*□: Capacitance Tolerance Codes.  
 \*\*\*: Capacitance values of "E24" series and capacitance tolerance of ±5% are available on special order.

Design and Specifications are subject to change without notice. Ask factory for technical specifications before purchase and/or use. Whenever a doubt about safety issues arises from this product, please inform us immediately for technical consultation.

# Panasonic

## Multilayer Ceramic Capacitors<sup>(For General)</sup>

### Standard Products for "10" Type (EIA "0402" Type) , Taped Version

Capacitance (pF)	Capacitance Tolerance	B/X7R						Capacitance Tolerance	F/Y5V						
		50 VDC		25 VDC		16 VDC			50 VDC		25 VDC		16 VDC		
		Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)		Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	
100		ECUE1H101□BC	0.5	ECUE1E101□BC	0.5										
120		ECUE1H121KBQ	0.5	ECUE1E121KBQ	0.5										
150		ECUE1H151□BC	0.5	ECUE1E151□BC	0.5										
180		ECUE1H181KBQ	0.5	ECUE1E181KBQ	0.5										
220		ECUE1H221□BC	0.5	ECUE1E221□BC	0.5										
270		ECUE1H271KBQ	0.5	ECUE1E271KBQ	0.5										
330		ECUE1H331□BC	0.5	ECUE1E331□BC	0.5										
390		ECUE1H391KBQ	0.5	ECUE1E391KBQ	0.5										
470		ECUE1H471□BC	0.5	ECUE1E471□BC	0.5										
560		ECUE1H561KBQ	0.5	ECUE1E561KBQ	0.5										
680		ECUE1H681□BC	0.5	ECUE1E681□BC	0.5										
820		ECUE1H821KBQ	0.5	ECUE1E821KBQ	0.5										
1000		ECUE1H102□BC	0.5	ECUE1E102□BC	0.5					ECUE1H102ZFQ	0.5	ECUE1E102ZFQ	0.5		
1200	±10 %	ECUE1H122KBQ	0.5	ECUE1E122KBQ	0.5										
1500	(K)	ECUE1H152□BC	0.5	ECUE1E152□BC	0.5					ECUE1H152ZFQ	0.5	ECUE1E152ZFQ	0.5		
1800	or	ECUE1H182KBQ	0.5	ECUE1E182KBQ	0.5										
2200	±20 %	ECUE1H222□BC	0.5	ECUE1E222□BC	0.5					ECUE1H222ZFQ	0.5	ECUE1E222ZFQ	0.5		
2700	(M)	ECUE1H272KBQ	0.5	ECUE1E272KBQ	0.5										
3300		ECUE1H332□BC	0.5	ECUE1E332□BC	0.5					ECUE1H332ZFQ	0.5	ECUE1E332ZFQ	0.5		
3900		ECUE1H392KBQ	0.5	ECUE1E392KBQ	0.5										
4700	(Packaging Style Code)**	ECUE1H472□BC	0.5							ECUE1H472ZFQ	0.5	ECUE1E472ZFQ	0.5		
5600				ECUE1E562KBQ	0.5	ECUE1C562KBQ	0.5								
6800				ECUE1E682□BC	0.5	ECUE1C682□BC	0.5			ECUE1H682ZFQ	0.5	ECUE1E682ZFQ	0.5		
8200						ECUE1C822KBQ	0.5								
10000						ECUE1C103□BC	0.5			ECUE1H103ZFQ	0.5	ECUE1E103ZFQ	0.5		
12000						ECUE1C123KBQ	0.5								
15000						ECUE1C153□BC	0.5					ECUE1E153ZFQ	0.5	ECUE1C153ZFQ	0.5
18000						(Cap. Tol. Code)*									
22000												ECUE1E223ZFQ	0.5	ECUE1C223ZFQ	0.5
27000															
33000														ECUE1C333ZFQ	0.5
39000															
47000														ECUE1C473ZFQ	0.5
56000															
68000														ECUE1C683ZFQ	0.5
82000															
100000														ECUE1C104ZFQ	0.5

\* □: Capacitance Tolerance Code.  
 \*\* Packaging Styles Code: "E" for Taped Version (Taping pitch: 2 mm) and "X" for Bulk Type

Design and Specifications are subject to change without notice. Ask factory for technical specifications before purchase and/or use. Whenever a doubt about safety issues arises from this product, please inform us immediately for technical consultation.

# Panasonic

## Multilayer Ceramic Capacitors<sup>(For General)</sup>

### ■ Standard Products for "11" Type (EIA "0603" Type), Taped Version [Rated Voltage 50 VDC]

Capacitance (pF)	Capacitance Tolerance	CA (NPO)		SL		PA (N150)		RA (N220)		SA (N330)		TA (N470)		UA (N750)	
		Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)
0.5	±0.25 pF(C)	ECUV1H0R5CCV	0.8	ECUV1H0R5CV	0.8	ECUV1H0R5CPV	0.8	ECUV1H0R5CRV	0.8	ECUV1H0R5CSV	0.8	ECUV1H0R5CTV	0.8	ECUV1H0R5CUV	0.8
1	±0.25 pF (C)	ECUV1H010CV	0.8	ECUV1H010V	0.8	ECUV1H010PV	0.8	ECUV1H010RV	0.8	ECUV1H010SV	0.8	ECUV1H010TV	0.8	ECUV1H010UV	0.8
1.5		ECUV1H1R5CV	0.8	ECUV1H1R5V	0.8	ECUV1H1R5PV	0.8	ECUV1H1R5RV	0.8	ECUV1H1R5SV	0.8	ECUV1H1R5TV	0.8	ECUV1H1R5UV	0.8
2	±0.5 pF (D)	ECUV1H020CV	0.8	ECUV1H020V	0.8	ECUV1H020PV	0.8	ECUV1H020RV	0.8	ECUV1H020SV	0.8	ECUV1H020TV	0.8	ECUV1H020UV	0.8
3		ECUV1H030CV	0.8	ECUV1H030V	0.8	ECUV1H030PV	0.8	ECUV1H030RV	0.8	ECUV1H030SV	0.8	ECUV1H030TV	0.8	ECUV1H030UV	0.8
4	±0.5 pF (D)	ECUV1H040CV	0.8	ECUV1H040V	0.8	ECUV1H040PV	0.8	ECUV1H040RV	0.8	ECUV1H040SV	0.8	ECUV1H040TV	0.8	ECUV1H040UV	0.8
5		ECUV1H050CV	0.8	ECUV1H050V	0.8	ECUV1H050PV	0.8	ECUV1H050RV	0.8	ECUV1H050SV	0.8	ECUV1H050TV	0.8	ECUV1H050UV	0.8
6	±0.5 pF (D)	ECUV1H060CV	0.8	ECUV1H060V	0.8	ECUV1H060PV	0.8	ECUV1H060RV	0.8	ECUV1H060SV	0.8	ECUV1H060TV	0.8	ECUV1H060UV	0.8
7		ECUV1H070CV	0.8	ECUV1H070V	0.8	ECUV1H070PV	0.8	ECUV1H070RV	0.8	ECUV1H070SV	0.8	ECUV1H070TV	0.8	ECUV1H070UV	0.8
8		ECUV1H080CV	0.8	ECUV1H080V	0.8	ECUV1H080PV	0.8	ECUV1H080RV	0.8	ECUV1H080SV	0.8	ECUV1H080TV	0.8	ECUV1H080UV	0.8
9		ECUV1H090CV	0.8	ECUV1H090V	0.8	ECUV1H090PV	0.8	ECUV1H090RV	0.8	ECUV1H090SV	0.8	ECUV1H090TV	0.8	ECUV1H090UV	0.8
10	±0.5 pF (D) or ±1 pF (F)	ECUV1H100CV	0.8	ECUV1H100V	0.8	ECUV1H100PV	0.8	ECUV1H100RV	0.8	ECUV1H100SV	0.8	ECUV1H100TV	0.8	ECUV1H100UV	0.8
12	±5% (J) or ±10% (K)	ECUV1H120CV	0.8	ECUV1H120V	0.8	ECUV1H120PV	0.8	ECUV1H120RV	0.8	ECUV1H120SV	0.8	ECUV1H120TV	0.8	ECUV1H120UV	0.8
15		ECUV1H150CV	0.8	ECUV1H150V	0.8	ECUV1H150PV	0.8	ECUV1H150RV	0.8	ECUV1H150SV	0.8	ECUV1H150TV	0.8	ECUV1H150UV	0.8
18		ECUV1H180CV	0.8	ECUV1H180V	0.8	ECUV1H180PV	0.8	ECUV1H180RV	0.8	ECUV1H180SV	0.8	ECUV1H180TV	0.8	ECUV1H180UV	0.8
22		ECUV1H220CV	0.8	ECUV1H220V	0.8	ECUV1H220PV	0.8	ECUV1H220RV	0.8	ECUV1H220SV	0.8	ECUV1H220TV	0.8	ECUV1H220UV	0.8
27		ECUV1H270CV	0.8	ECUV1H270V	0.8	ECUV1H270PV	0.8	ECUV1H270RV	0.8	ECUV1H270SV	0.8	ECUV1H270TV	0.8	ECUV1H270UV	0.8
33		ECUV1H330CV	0.8	ECUV1H330V	0.8	ECUV1H330PV	0.8	ECUV1H330RV	0.8	ECUV1H330SV	0.8	ECUV1H330TV	0.8	ECUV1H330UV	0.8
39		ECUV1H390CV	0.8	ECUV1H390V	0.8	ECUV1H390PV	0.8	ECUV1H390RV	0.8	ECUV1H390SV	0.8	ECUV1H390TV	0.8	ECUV1H390UV	0.8
47		ECUV1H470CV	0.8	ECUV1H470V	0.8	ECUV1H470PV	0.8	ECUV1H470RV	0.8	ECUV1H470SV	0.8	ECUV1H470TV	0.8	ECUV1H470UV	0.8
56		ECUV1H560CV	0.8	ECUV1H560V	0.8	ECUV1H560PV	0.8	ECUV1H560RV	0.8	ECUV1H560SV	0.8	ECUV1H560TV	0.8	ECUV1H560UV	0.8
68		ECUV1H680CV	0.8	ECUV1H680V	0.8	ECUV1H680PV	0.8	ECUV1H680RV	0.8	ECUV1H680SV	0.8	ECUV1H680TV	0.8	ECUV1H680UV	0.8
82		ECUV1H820CV	0.8	ECUV1H820V	0.8	ECUV1H820PV	0.8	ECUV1H820RV	0.8	ECUV1H820SV	0.8	ECUV1H820TV	0.8	ECUV1H820UV	0.8
100		ECUV1H101CV	0.8	ECUV1H101V	0.8	ECUV1H101PV	0.8	ECUV1H101RV	0.8	ECUV1H101SV	0.8	ECUV1H101TV	0.8	ECUV1H101UV	0.8
120		ECUV1H121CV	0.8	ECUV1H121V	0.8	ECUV1H121PV	0.8	ECUV1H121RV	0.8	ECUV1H121SV	0.8	ECUV1H121TV	0.8	ECUV1H121UV	0.8
150		ECUV1H151CV	0.8	ECUV1H151V	0.8	ECUV1H151PV	0.8	ECUV1H151RV	0.8	ECUV1H151SV	0.8	ECUV1H151TV	0.8	ECUV1H151UV	0.8
180		ECUV1H181CV	0.8	ECUV1H181V	0.8		0.8	ECUV1H181RV	0.8	ECUV1H181SV	0.8	ECUV1H181TV	0.8	ECUV1H181UV	0.8
220		ECUV1H221CV	0.8	ECUV1H221V	0.8		0.8	(Packaging Style Code)*				ECUV1H221TV	0.8	ECUV1H221UV	0.8
270	ECUV1H271CV	0.8	ECUV1H271V	0.8		0.8							ECUV1H271UV	0.8	
330	ECUV1H331CV	0.8	ECUV1H331V	0.8		0.8							ECUV1H331UV	0.8	
390	ECUV1H391CV	0.8	ECUV1H391V	0.8		0.8							ECUV1H391UV	0.8	
470	ECUV1H471CV	0.8	ECUV1H471V	0.8		0.8							ECUV1H471UV	0.8	
560	ECUV1H561CV	0.8	ECUV1H561V	0.8		0.8							ECUV1H561UV	0.8	
680	ECUV1H681CV	0.8	ECUV1H681V	0.8		0.8							ECUV1H681UV	0.8	
820	ECUV1H821CV	0.8	ECUV1H821V	0.8		0.8							ECUV1H821UV	0.8	
1000	ECUV1H102CV	0.8	ECUV1H102V	0.8		0.8							ECUV1H102UV	0.8	
1200			(Cap. Tol. Code)**	ECUV1H122V	0.8								ECUV1H122UV	0.8	

\* Packaging Style Code "V" for Taped Version (Taping pitch: 4mm) and "X" for Bulk Type.  
 \*\*: □ Capacitance Tolerance Codes.  
 \*\*\*: Capacitance values of "E24" series and capacitance tolerance of ±5% are available on special order.

Design and Specifications are subject to change without notice. Ask factory for technical specifications before purchase and/or use. Whenever a doubt about safety issues arises from this product, please inform us immediately for technical consultation.

# Panasonic

## Multilayer Ceramic Capacitors<sup>(For General)</sup>

### Standard Products for "11" Type (EIA "0603" Type), Taped Version

Capacitance (pF)	B/X7R								F/Y5V							
	50 VDC		25 VDC		16 VDC		10 VDC		50 VDC		25 VDC		16 VDC		10 VDC	
	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)
220	ECUV1H21□□BV	0.8														
270	ECUV1H271KRV	0.8														
330	ECUV1H331□□BV	0.8														
390	ECUV1H391KRV	0.8														
470	ECUV1H471□□BV	0.8														
560	ECUV1H561KRV	0.8														
680	ECUV1H681□□BV	0.8														
820	ECUV1H821KRV	0.8														
1000	ECJ1V81H10□□	0.8							ECUV1H102ZFV	0.8						
1200	ECJ1V81H12□□	0.8														
1500	ECJ1V81H15□□	0.8							ECUV1H152ZFV	0.8						
1800	ECJ1V81H18□□	0.8														
2200	ECJ1V81H22□□	0.8							ECUV1H222ZFV	0.8						
2700	ECJ1V81H27□□	0.8														
3300	ECJ1V81H33□□	0.8							ECUV1H332ZFV	0.8						
3900	ECJ1V81H39□□	0.8														
4700	ECJ1V81H47□□	0.8							ECUV1H472ZFV	0.8						
5600	ECJ1V81H56□□	0.8														
6800	ECJ1V81H68□□	0.8							ECUV1H682ZFV	0.8						
8200	ECJ1V81H82□□	0.8														
10000	ECJ1V81H10□□	0.8	ECJ1V81E10□□	0.8	ECJ1V81C10□□	0.8			ECJ1VF1H103Z	0.8						
12000	ECJ1V81H12□□	0.8	ECJ1V81E12□□	0.8	ECJ1V81C12□□	0.8										
15000	ECJ1V81H15□□	0.8	ECJ1V81E15□□	0.8	ECJ1V81C15□□	0.8			ECJ1VF1H153Z	0.8						
18000	(Cap. Tol. Code)**		ECJ1V81E18□□	0.8	ECJ1V81C18□□	0.8										
22000			ECJ1V81E22□□	0.8	ECJ1V81C22□□	0.8			ECJ1VF1H223Z	0.8						
27000			ECJ1V81E27□□	0.8	ECJ1V81C27□□	0.8										
33000			ECJ1V81E33□□	0.8	ECJ1V81C33□□	0.8			ECJ1VF1H333Z	0.8						
39000			ECJ1V81E39□□	0.8	ECJ1V81C39□□	0.8										
47000			ECJ1V81E47□□	0.8	ECJ1V81C47□□	0.8			ECJ1VF1H473Z	0.8						
56000	(Packaging Style Code)*				ECJ1V81C56□□	0.8										
68000					ECJ1V81C68□□	0.8					ECJ1VF1E683Z	0.8				
82000					ECJ1V81C82□□	0.8										
100000					ECJ1V81C10□□	0.8					ECJ1VF1E104Z	0.8	ECJ1VF1C104Z	0.8		
150000							ECJ1V81A15□□	0.8					ECJ1VF1C154Z	0.8		
220000							ECJ1V81A22□□	0.8					ECJ1VF1C224Z	0.8		
330000													ECJ1VF1C334Z	0.8		
470000													ECJ1VF1C474Z	0.8		
680000																
1000000															ECJ1VF1A106Z	0.8
1500000																
2200000																

\*Packaging Styles Code: "V" for Taped Version (Taping pitch: 4 mm) and "X" for Bulk Type.  
 \*\*: □: Capacitance Tolerance Codes.

Design and Specifications are subject to change without notice. Ask factory for technical specifications before purchase and/or use. Whenever a doubt about safety issues arises from this product, please inform us immediately for technical consultation.

# Panasonic

## Multilayer Ceramic Capacitors<sup>(For General)</sup>

### Standard Products for "12" Type (EIA "0805" Type), Taped Version [Rated Voltage 50 VDC]

Capacitance (pF)	Capacitance Tolerance	CΔ (NPO)		SL		PΔ (N150)		RΔ (N220)		SΔ (N330)		TΔ (N470)		UΔ (N750)		
		Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	
0.5	±0.25 pF(C)	ECUV1H0R6CCN	0.6	ECUV1H0R6CCN	0.6	ECUV1H0R6CCN	0.6	ECUV1H0R6CCN	0.6	ECUV1H0R6CCN	0.6	ECUV1H0R6CCN	0.6	ECUV1H0R6CCN	0.6	
1	±0.25 pF (C) or ±0.5 pF (D)	ECUV1H010CCN	0.6	ECUV1H010CCN	0.6	ECUV1H010CCN	0.6	ECUV1H010CCN	0.6	ECUV1H010CCN	0.6	ECUV1H010CCN	0.6	ECUV1H010CCN	0.6	
1.5		ECUV1H1R5CCN	0.6	ECUV1H1R5CCN	0.6	ECUV1H1R5CCN	0.6	ECUV1H1R5CCN	0.6	ECUV1H1R5CCN	0.6	ECUV1H1R5CCN	0.6	ECUV1H1R5CCN	0.6	
2	±0.5 pF (D)	ECUV1H020CCN	0.6	ECUV1H020CCN	0.6	ECUV1H020CCN	0.6	ECUV1H020CCN	0.6	ECUV1H020CCN	0.6	ECUV1H020CCN	0.6	ECUV1H020CCN	0.6	
3		ECUV1H030CCN	0.6	ECUV1H030CCN	0.6	ECUV1H030CCN	0.6	ECUV1H030CCN	0.6	ECUV1H030CCN	0.6	ECUV1H030CCN	0.6	ECUV1H030CCN	0.6	
4	±0.5 pF (D)	ECUV1H040CCN	0.6	ECUV1H040CCN	0.6	ECUV1H040CCN	0.6	ECUV1H040CCN	0.6	ECUV1H040CCN	0.6	ECUV1H040CCN	0.6	ECUV1H040CCN	0.6	
5		ECUV1H050CCN	0.6	ECUV1H050CCN	0.6	ECUV1H050CCN	0.6	ECUV1H050CCN	0.6	ECUV1H050CCN	0.6	ECUV1H050CCN	0.6	ECUV1H050CCN	0.6	
6	±0.5 pF (D)	ECUV1H060CCN	0.6	ECUV1H060CCN	0.6	ECUV1H060CCN	0.6	ECUV1H060CCN	0.6	ECUV1H060CCN	0.6	ECUV1H060CCN	0.6	ECUV1H060CCN	0.6	
7		ECUV1H070CCN	0.6	ECUV1H070CCN	0.6	ECUV1H070CCN	0.6	ECUV1H070CCN	0.6	ECUV1H070CCN	0.6	ECUV1H070CCN	0.6	ECUV1H070CCN	0.6	
8	±0.5 pF (D)	ECUV1H080CCN	0.6	ECUV1H080CCN	0.6	ECUV1H080CCN	0.6	ECUV1H080CCN	0.6	ECUV1H080CCN	0.6	ECUV1H080CCN	0.6	ECUV1H080CCN	0.6	
9		ECUV1H090CCN	0.6	ECUV1H090CCN	0.6	ECUV1H090CCN	0.6	ECUV1H090CCN	0.6	ECUV1H090CCN	0.6	ECUV1H090CCN	0.6	ECUV1H090CCN	0.6	
10	±0.5 pF (D) or ±1 pF (F)	ECUV1H100CCN	0.6	ECUV1H100CCN	0.6	ECUV1H100CCN	0.6	ECUV1H100CCN	0.6	ECUV1H100CCN	0.6	ECUV1H100CCN	0.6	ECUV1H100CCN	0.6	
12		ECUV1H120CCN	0.6	ECUV1H120CCN	0.6	ECUV1H120CCN	0.6	ECUV1H120CCN	0.6	ECUV1H120CCN	0.6	ECUV1H120CCN	0.6	ECUV1H120CCN	0.6	
15	±5%*** (J) or ±10% (K)	ECUV1H150CCG	0.6	ECUV1H150CCG	0.6	ECUV1H150CCG	0.6	ECUV1H150CCG	0.6	ECUV1H150CCG	0.6	ECUV1H150CCG	0.6	ECUV1H150CCG	0.6	
18		ECUV1H180CCG	0.6	ECUV1H180CCG	0.6	ECUV1H180CCG	0.6	ECUV1H180CCG	0.6	ECUV1H180CCG	0.6	ECUV1H180CCG	0.6	ECUV1H180CCG	0.6	
22	±10% (K)	ECUV1H220CCG	0.6	ECUV1H220CCG	0.6	ECUV1H220CCG	0.6	ECUV1H220CCG	0.6	ECUV1H220CCG	0.6	ECUV1H220CCG	0.6	ECUV1H220CCG	0.6	
27		ECUV1H270CCG	0.6	ECUV1H270CCG	0.6	ECUV1H270CCG	0.6	ECUV1H270CCG	0.6	ECUV1H270CCG	0.6	ECUV1H270CCG	0.6	ECUV1H270CCG	0.6	
33	±10% (K)	ECUV1H330CCG	0.6	ECUV1H330CCG	0.6	ECUV1H330CCG	0.6	ECUV1H330CCG	0.6	ECUV1H330CCG	0.6	ECUV1H330CCG	0.6	ECUV1H330CCG	0.6	
39		ECUV1H390CCG	0.6	ECUV1H390CCG	0.6	ECUV1H390CCG	0.6	ECUV1H390CCG	0.6	ECUV1H390CCG	0.6	ECUV1H390CCG	0.6	ECUV1H390CCG	0.6	
47	±10% (K)	ECUV1H470CCG	0.6	ECUV1H470CCG	0.6	ECUV1H470CCG	0.6	ECUV1H470CCG	0.6	ECUV1H470CCG	0.6	ECUV1H470CCG	0.6	ECUV1H470CCG	0.6	
56		ECUV1H560CCG	0.6	ECUV1H560CCG	0.6	ECUV1H560CCG	0.6	ECUV1H560CCG	0.6	ECUV1H560CCG	0.6	ECUV1H560CCG	0.6	ECUV1H560CCG	0.6	
68	±10% (K)	ECUV1H680CCG	0.6	ECUV1H680CCG	0.6	ECUV1H680CCG	0.6	ECUV1H680CCG	0.6	ECUV1H680CCG	0.6	ECUV1H680CCG	0.6	ECUV1H680CCG	0.6	
82		ECUV1H820CCG	0.6	ECUV1H820CCG	0.6	ECUV1H820CCG	0.6	ECUV1H820CCG	0.6	ECUV1H820CCG	0.6	ECUV1H820CCG	0.6	ECUV1H820CCG	0.6	
100	±10% (K)	ECUV1H101CCG	0.6	ECUV1H101CCG	0.6	ECUV1H101CCG	0.6	ECUV1H101CCG	0.6	ECUV1H101CCG	0.6	ECUV1H101CCG	0.6	ECUV1H101CCG	0.6	
120		ECUV1H121CCG	0.6	ECUV1H121CCG	0.6	ECUV1H121CCG	0.6	ECUV1H121CCG	0.6	ECUV1H121CCG	0.6	ECUV1H121CCG	0.6	ECUV1H121CCG	0.6	
150	±10% (K)	ECUV1H151CCG	0.6	ECUV1H151CCG	0.6	ECUV1H151CCG	0.6	ECUV1H151CCG	0.6	ECUV1H151CCG	0.6	ECUV1H151CCG	0.6	ECUV1H151CCG	0.6	
180		ECUV1H181CCG	0.6	ECUV1H181CCG	0.6	ECUV1H181CCG	0.6	ECUV1H181CCG	0.6	ECUV1H181CCG	0.6	ECUV1H181CCG	0.6	ECUV1H181CCG	0.6	
220	±10% (K)	ECUV1H221CCG	0.6	ECUV1H221CCG	0.6	ECUV1H221CCG	0.6	ECUV1H221CCG	0.6	ECUV1H221CCG	0.6	ECUV1H221CCG	0.6	ECUV1H221CCG	0.6	
270		ECUV1H271CCG	0.6	ECUV1H271CCG	0.6	ECUV1H271CCG	0.85	ECUV1H271CCG	0.85	ECUV1H271CCG	0.85	ECUV1H271CCG	0.6	ECUV1H271CCG	0.6	
330	±10% (K)	ECUV1H331CCG	0.6	ECUV1H331CCG	0.6	ECUV1H331CCG	0.85	ECUV1H331CCG	0.85	ECUV1H331CCG	0.85	ECUV1H331CCG	0.85	ECUV1H331CCG	0.6	
390		ECUV1H391CCG	0.6	ECUV1H391CCG	0.6	ECUV1H391CCG	0.85	ECUV1H391CCG	0.85	ECUV1H391CCG	0.85	ECUV1H391CCG	0.85	ECUV1H391CCG	0.6	
470	±10% (K)	ECUV1H471CCX	0.6	ECUV1H471CCX	0.6			ECUV1H471CCX	0.85	ECUV1H471CCX	0.85	ECUV1H471CCX	0.85	ECUV1H471CCX	0.6	
560		ECUV1H561CCX	0.6	ECUV1H561CCX	0.6					(Packaging Style Code)*				ECUV1H561CCX	0.6	
680	±10% (K)	ECUV1H681CCX	0.6	ECUV1H681CCX	0.6									ECUV1H681CCX	0.6	
820		ECUV1H821CCX	0.6	ECUV1H821CCX	0.6										ECUV1H821CCX	0.6
1000	±10% (K)	ECUV1H102CCX	0.6	ECUV1H102CCX	0.6										ECUV1H102CCX	0.6
1200		ECUV1H122CCX	0.6	ECUV1H122CCX	0.6										ECUV1H122CCX	0.6
1500	±10% (K)	ECUV1H152CCX	0.6	ECUV1H152CCX	0.6										ECUV1H152CCX	0.6
1800		ECUV1H182CCX	0.6	ECUV1H182CCX	0.6										ECUV1H182CCX	0.6
2200	±10% (K)	ECUV1H222CCX	0.6	ECUV1H222CCX	0.6										ECUV1H222CCX	0.6
2700		ECUV1H272CCX	0.85	ECUV1H272CCX	0.6										ECUV1H272CCX	0.6

(Cap. Tol. Code)\*\*

\* Packaging Style Code: "V" for Taped Version (Taping pitch: 4mm) and "X" for Bulk Type.

\*\* □: Capacitance Tolerance Codes.  
 \*\*\*: Capacitance values of "E24" series and capacitance tolerance of ±5% are available on special order.

Design and Specifications are subject to change without notice. Ask factory for technical specifications before purchase and/or use. Whenever a doubt about safety issues arises from this product, please inform us immediately for technical consultation.

# Panasonic

## Multilayer Ceramic Capacitors<sup>(For General)</sup>

### Standard Products for "12" Type (EIA "0805" Type), Taped Version

Capacitance (pF)	B/X7R						F/Y5V									
	50 VDC		25 VDC		16 VDC		10 VDC		50 VDC		25 VDC		16 VDC		10 VDC	
	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)
220																
270																
330																
390																
470																
560																
680																
820																
1000	ECUV1H102□BN	0.6														
1200	ECUV1H122KBN	0.6														
1500	ECUV1H152□BN	0.6														
1800	ECUV1H182KBN	0.6														
2200	ECUV1H222□BN	0.6														
2700	ECUV1H272KBN	0.6														
3300	ECUV1H332□BN	0.6														
3900	ECUV1H392KBN	0.6														
4700	ECUV1H472□BG	0.6														
5600	ECUV1H562KBG	0.6														
6800	ECUV1H682□BG	0.6														
8200	ECUV1H822KBG	0.6														
10000	ECUV1H103□BG	0.6														
12000	ECUV1H123KBX	0.6														
15000	ECUV1H153□BX	0.6														
18000	ECUV1H183KBX	0.6														
22000	ECUV1H223□BX	0.6														
27000	ECJ2VB1H273K	0.85														
33000	ECJ2VB1H333□	0.85														
39000	ECJ2VB1H393K	0.85	ECJ2VB1E393K	0.85												
47000	ECJ2VB1H473□	1.25	ECJ2VB1E473□	0.85	ECJ2VB1C473□	0.85										
56000	ECJ2VB1H563K	1.25	ECJ2VB1E563K	0.85	ECJ2VB1C563K	0.85										
68000	ECJ2VB1H683□	1.25	ECJ2VB1E683□	0.85	ECJ2VB1C683□	0.85										
82000	ECJ2VB1H823K	1.25	ECJ2VB1E823K	0.85	ECJ2VB1C823K	0.85										
100000	ECJ2VB1H104□	1.25	ECJ2VB1E104□	0.85	ECJ2VB1C104□	0.85										
120000	(Cap. Tol. Code) <sup>*)</sup>		ECJ2VB1E124K	1.25	ECJ2VB1C124K	0.85										
150000			ECJ2VB1E154□	1.25	ECJ2VB1C154□	0.85										
180000			ECJ2VB1E184K	1.25	ECJ2VB1C184K	0.85										
220000			ECJ2VB1E224□	1.25	ECJ2VB1C224□	0.85										
330000	(Packaging Style Code) <sup>*</sup>				ECJ2VB1C334□	1.25										
470000					ECJ2VB1C474□	1.25										
680000							ECJ2VB1A684□	1.25					ECJ2VF1C684Z	0.85		
1000000							ECJ2VB1A105□	1.25					ECJ2VF1C105Z	0.85		
1500000													ECJ2VF1C155Z	1.25		
2200000													ECJ2VF1C225Z	1.25		
3300000															ECJ2VF1A335Z	1.25
4700000															ECJ2VF1A475Z	1.25
6800000																
10000000																

\*Packaging Style Code: "V" for Taped Version (Taping pitch: 4 mm) and "X" for Bulk Type.  
 \*\*□: Capacitance Tolerance Codes.

Design and Specifications are subject to change without notice. Ask factory for technical specifications before purchase and/or use. Whenever a doubt about safety issues arises from this product, please inform us immediately for technical consultation.

# Panasonic

## Multilayer Ceramic Capacitors<sup>(For General)</sup>

### ■ Standard Products for "13" Type (EIA "1206" Type) , Taped Version

[Rated Voltage 50 VDC]

Capacitance (pF)	Capacitance Tolerance	CΔ (NP0)		SL		PΔ (N150)		RΔ (N220)		SΔ (N330)		TΔ (N470)		UΔ (N750)			
		Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)		
270	±5 % <sup>***</sup> (J) or ±10 % (K)					ECUV1H271□ <sub>PM</sub>	0.6	ECUV1H271□ <sub>RM</sub>	0.6	ECUV1H271□ <sub>SM</sub>	0.6	ECUV1H271□ <sub>TM</sub>	0.6				
330						ECUV1H331□ <sub>PM</sub>	0.6	ECUV1H331□ <sub>RM</sub>	0.6	ECUV1H331□ <sub>SM</sub>	0.6	ECUV1H331□ <sub>TM</sub>	0.6				
390						ECUV1H391□ <sub>PM</sub>	0.6	ECUV1H391□ <sub>RM</sub>	0.6	ECUV1H391□ <sub>SM</sub>	0.6	ECUV1H391□ <sub>TM</sub>	0.6				
470						ECUV1H471□ <sub>PM</sub>	0.6	ECUV1H471□ <sub>RM</sub>	0.6	ECUV1H471□ <sub>SM</sub>	0.6	ECUV1H471□ <sub>TM</sub>	0.6				
560						ECUV1H561□ <sub>PM</sub>	0.6	ECUV1H561□ <sub>RM</sub>	0.6	ECUV1H561□ <sub>SM</sub>	0.6	ECUV1H561□ <sub>TM</sub>	0.6				
680						ECUV1H681□ <sub>PM</sub>	0.85	ECUV1H681□ <sub>RM</sub>	0.6	ECUV1H681□ <sub>SM</sub>	0.6	ECUV1H681□ <sub>TM</sub>	0.6				
820						ECUV1H821□ <sub>PM</sub>	0.85	ECUV1H821□ <sub>RM</sub>	0.85	ECUV1H821□ <sub>SM</sub>	0.85	ECUV1H821□ <sub>TM</sub>	0.6				
1000						ECUV1H102□ <sub>PM</sub>	0.85	ECUV1H102□ <sub>RM</sub>	0.85	ECUV1H102□ <sub>SM</sub>	0.85	ECUV1H102□ <sub>TM</sub>	0.85				
1200						ECUV1H122□ <sub>PM</sub>	0.85	ECUV1H122□ <sub>RM</sub>	0.85	ECUV1H122□ <sub>SM</sub>	0.85	ECUV1H122□ <sub>TM</sub>	0.85				
1500								(Packaging Style Code)*			ECUV1H152□ <sub>SM</sub>	0.85	ECUV1H152□ <sub>TM</sub>	0.85			
1800																	
2200																	
2700																	
3300							ECUV1H332□ <sub>DW</sub>	0.6								ECUV1H332□ <sub>JW</sub>	0.6
3900							ECUV1H392□ <sub>DW</sub>	0.6	ECUV1H392□ <sub>JW</sub>	0.6						ECUV1H392□ <sub>JW</sub>	0.6
4700						ECUV1H472□ <sub>DW</sub>	0.6	ECUV1H472□ <sub>JW</sub>	0.6						ECUV1H472□ <sub>JW</sub>	0.6	
5600						ECUV1H562□ <sub>DW</sub>	0.85	ECUV1H562□ <sub>JW</sub>	0.6						ECUV1H562□ <sub>JW</sub>	0.6	
6800						ECUV1H682□ <sub>DW</sub>	0.85										
8200						ECUV1H822□ <sub>DW</sub>	1.15										
10000						ECUV1H103□ <sub>DW</sub>	1.15										

(Cap. Tol. Code)\*\*

\* Packaging Style Code: "V", "Y" for Taped Version (Taping pitch: 4 mm) and "X" for Bulk Type.

\*\* □ : Capacitance Tolerance Codes.

\*\*\* Capacitance values of "E24" series and capacitance tolerance of ±5 % are available on special order.

Design and Specifications are subject to change without notice. Ask factory for technical specifications before purchase and/or use. Whenever a doubt about safety issues arises from this product, please inform us immediately for technical consultation.

# Panasonic

## Multilayer Ceramic Capacitors<sup>(For General)</sup>

### Standard Products for "13" Type (EIA "1206" Type), Taped Version

Capacitance (pF)	Capacitance Tolerance	B/X7R						Capacitance Tolerance	F/Y5V								
		25 VDC		16 VDC		10VDC			25 VDC		16 VDC		10 VDC				
		Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)		Part No.	Dim. T (mm)	Part No.	Dim. T (mm)	Part No.	Dim. T (mm)			
68000																	
82000																	
100000		ECJ3VB1E104	0.85	ECJ3VB1C104	0.85												
120000		ECJ3VB1E124K	0.85	ECJ3VB1C124K	0.85												
150000		ECJ3VB1E154	0.85	ECJ3VB1C154	0.85												
180000		ECJ3VB1E184K	0.85	ECJ3VB1C184K	0.85												
220000	±10 % (K) or ±20 % (M)	ECJ3VB1E224	0.85	ECJ3VB1C224	0.85			+80 -20 % (Z)									
270000		ECJ3VB1E274K	0.85	ECJ3VB1C274K	0.85												
330000		ECJ3VB1E334	0.85	ECJ3VB1C334	0.85												
390000		ECJ3YB1E394K	1.15	ECJ3VB1C394K	0.85												
470000		ECJ3YB1E474	1.15	ECJ3VB1C474	0.85				ECJ3VF1E474Z	0.85							
560000				ECJ3VB1C564K	0.85												
680000		ECJ3YB1E684	1.6	ECJ3VB1C684	0.85				ECJ3YF1E684Z	1.15	ECJ3VF1C684Z	0.85					
820000				ECJ3YB1C824K	1.15												
1000000		ECJ3YB1E105	1.6	ECJ3YB1C105	1.15				ECJ3YF1E105Z	1.15	ECJ3VF1C105Z	0.85					
1500000		(Cap. Tol. Code)**				ECJ3YB1A155	1.6		ECJ3YF1E155Z	1.15	ECJ3VF1C155Z	0.85					
2200000						ECJ3YB1A225	1.6		ECJ3YF1E225Z	1.15	ECJ3VF1C225Z	0.85					
3300000						ECJ3YB1A335	1.6				ECJ3YF1C335Z	1.15					
4700000											ECJ3YF1C475Z	1.15					
6800000																	
10000000																	ECJ3YF1A106Z 1.6

\*Packaging Style Code: "V", "Y" for Taped Version (Taping pitch: 4mm) and "X" for Bulk Type.  
 \*\*:□: Capacitance Tolerance Codes.



# Panasonic

## Multilayer Ceramic Capacitors<sup>(For General)</sup>

### ■ Packaging Specifications


#### ● Standard Packing Quantity

Size Code (EIA)	Thickness	Paper taping	Embossed taping	Bulk	Bulk case
10 (0402)	0.5 mm	Pitch 2 mm: 10000 (50000) pcs./reel	—	1000 pcs./bag	50000 pcs./case
11 (0603)	0.8 mm	Pitch 2 mm: 8000 (20000) pcs./reel Pitch 4 mm: 4000 (10000) pcs./reel	—	1000 pcs./bag	15000 pcs./case
	0.6 mm	Pitch 2 mm: 10000 (40000) pcs./reel Pitch 4 mm: 5000 (20000) pcs./reel	—	1000 pcs./bag	10000 pcs./case
12 (0805)	0.85 mm	Pitch 4 mm: 4000 (10000) pcs./reel	—	1000 pcs./bag	—
	1.25 mm	—	Pitch 4 mm: 2000 (10000) pcs./reel	1000 pcs./bag	—
13 (1206)	0.6 mm	Pitch 4 mm: 5000 (20000) pcs./reel	—	1000 pcs./bag	—
	0.85 mm	Pitch 4 mm: 4000 (10000) pcs./reel	—	1000 pcs./bag	—
	1.15 mm	—	Pitch 4 mm: 2000 (10000) pcs./reel	1000 pcs./bag	—
	1.6 mm	—	Pitch 4 mm: 2000 pcs./reel	1000 pcs./bag	—

( ) for large size reel applied


#### ● Paper Taping

P<sub>1</sub>: 2mm




Symbol	A	B	W	F	E	P <sub>1</sub>	P <sub>2</sub>	P <sub>0</sub>	φD <sub>0</sub>	t <sub>1</sub>	t <sub>2</sub>
10 (0402)	0.65 ±0.05	1.15 ±0.05								0.7 max.	1.0 max.
11 (0603)	1.10 ±0.10	1.90 ±0.10	8.0 ±0.2	3.50 ±0.05	1.75 ±0.10	2.00 ±0.05	2.00 ±0.05	4.0 ±0.1	1.5 +0.1 0	1.1 max.	1.4 max.
12 (0805)	1.65 ±0.20	2.4 ±0.2									

P<sub>1</sub>: 4mm




Symbol	A	B	W	F	E	P <sub>1</sub>	P <sub>2</sub>	P <sub>0</sub>	φD <sub>0</sub>	t <sub>1</sub>	t <sub>2</sub>
11 (0603)	1.10 ±0.10	1.90 ±0.10									
12 (0805)	1.65 ±0.20	2.4 ±0.2	8.0 ±0.2	3.50 ±0.05	1.75 ±0.10	4.0 ±0.1	2.00 ±0.05	4.0 ±0.1	1.5 +0.1 0	1.1 max.	1.4 max.
13 (1206)	2.0 ±0.2	3.6 ±0.2									

#### ● Embossed Taping



Symbol	A	B	W	F	E	P <sub>1</sub>	P <sub>2</sub>	P <sub>0</sub>	φD <sub>0</sub>	t <sub>1</sub>	t <sub>2</sub>
12 (0805)	1.55 ±0.20	2.35 ±0.2	8.0 ±0.2	3.50 ±0.05	1.75 ±0.10	4.0 ±0.1	2.00 ±0.05	4.0 ±0.1	1.5 +0.1 0	0.6 max.	2.1 max.
13 (1206)	1.95 ±0.20	3.6 ±0.2									

#### ● Reel for Taping




Symbol	A	B	C	D	E	W	W <sub>1</sub>
Dim. (mm)	φ180 ± <sub>(30±5)</sub>	φ60.0 ±0.5 (50 min.)	13.0 ±0.5	21.0 ±0.8 (20 min.)	2.0 ±0.5	9.0 ±0.3 (8.5 ±1.0)	1.3 ±0.2 (2.0 ±0.5)


( ) : Large size reel

#### ● Leader Part and Taped End

##### Tape end




##### Leader part



Unit : mm

#### (1) Bulk Case



Unit: mm








Design and Specifications are subject to change without notice. Ask factory for technical specifications before purchase and/or use. Whenever a doubt about safety issues arises from this product, please inform us immediately for technical consultation.

# Panasonic



## Multilayer Ceramic Capacitors<sup>(For General)</sup>

### ■ Typical Temperature Characteristics

[Class 1 (T.C. Type)]



[Class 2 (Hi-K Type)]



Design and Specifications are subject to change without notice. Ask factory for technical specifications before purchase and/or use.  
Whenever a doubt about safety issues arises from this product, please inform us immediately for technical consultation.

**Multilayer Ceramic Chip Capacitors**Series: **ECU, ECJ** (For General Electronic Equipment)**Handling Precautions****⚠ Safety Precautions**

The Multilayer Ceramic Chip Capacitors (hereafter referred to as "The Capacitors") may fail in a short circuit mode or in an open-circuit mode, when subjected to severe conditions of electrical, environmental and/or mechanical stresses beyond the specified "Ratings" and specified "Conditions" in the Catalog and the Specifications, resulting in burnout, flaming or glowing in the worst case.

Following "⚠ Precautions for Safety" and "Application Notes" shall be taken in your major consideration. If you have a question about the Precautions for Handling, please contact our engineering section or factory.

**1. ⚠ Operating Conditions and Circuit Design****1.1 Operating Temperature Range**

The specified "Operating Temperature Range" in the catalog is absolute maximum and minimum temperature rating. So in any case, the Capacitors shall be operated within the specified "Operating Temperature Range".

**1.2 Designs of Voltage Applications**

The Capacitors shall not be operated exceeding the specified "Rated Voltage" in the catalog. If voltage ratings are exceeded, the result could be failure or damage. In case of application of DC and AC voltages to the capacitors, the designed peak voltage shall be within the specified "Rated Voltage".

In case of AC of pulse voltage, the peak voltage (peak to peak) shall be within the specified "Rated Voltage". If high frequency voltage or fast rising pulse voltage is applied continuously even within the "Rated Voltage", contact our engineering section before use.

**1.3 Charging and Discharging Current**

The Capacitors shall not be operated beyond the specified "Maximum Charging/Discharging Current Ratings" in the specifications. Applications to a low impedance circuit such as a "secondary power circuit" are not recommended for safety.

**1.4 Temperature Rise by Dielectric Loss of the Capacitor**

The "Operating Temperature Range" mentioned above shall include a maximum surface temperature rise of 20 °C, which is caused by the Dielectric Loss of the Capacitor and applied electrical stresses (such as voltage, frequency and wave form etc.)

It is recommended to measure and check "Surface Temperature of the Capacitor" in your equipment at your estimated/designed maximum ambient temperature.

**1.5 Restriction on Environmental Conditions**

The Capacitors shall not be operated and/or stored under following environmental conditions;

- a) To be exposed directly to water or salt water.
- b) To be exposed directly to sunlight.
- c) Under conditions of condensation
- d) Under conditions of corrosive atmosphere such as hydrogen sulfide, sulfuric acid, chlorine, or ammonia etc.
- e) Under severe conditions of vibration or shock beyond the specified conditions in the Specifications.

**1.6 Secular Changes in Capacitance**

(1) Peculiar characteristics of "Secular Changes in Capacitance" are observed in the Capacitors (Class 2 High Dielectric Constant, Temperature Characteristics "X7R" and "Y5V"). The "secular changes" shall be considered in your circuit design.

(2) The Capacitance changes, due to the individual characteristics of ceramic dielectric materials applied, can be recovered to the each initial values at shipping by a heat treatment (140 to 150 °C for 1 hour).

(The recovered capacitance of Class 2 Capacitor shall be measured at the standard test condition after recovery times of 48 hours.)

**2. ⚠ Design of Printed Circuit Board****2.1 Selection of Printed Circuit Boards**

When the Capacitors are mounted and soldered on an "Aluminum Substrate", the substrate has influences on Capacitor's reliability against "Temperature Cycles" and "Heat shock" because of difference of thermal expansion coefficient between them. It shall be carefully confirmed that the actual board to be used does not deteriorate the characteristics of the Capacitors.

# Panasonic

## Multilayer Ceramic Capacitors

### 2.2 Design of Land Pattern

(1) Recommended Dimensions of Lands: As shown in Table 1 and Fig.1.

Notes: \* Too large land requires excess amount of solder.  
 \*\* The Dimensions shall be symmetrical

Fig.1 Recommended Land Dimensions




Table 1 Recommended Land Dimensions in mm


Size Code (EIA)	Components Dimensions			Land Dimensions for Flow Soldering			Land Dimensions for Reflow Soldering		
	L	W	T	a	b	c	a	b	c
13 (1206)	3.2	1.6	0.5-1.25	2.0-2.4	4.4-4.8	1.0-1.3	1.8-2.4	3.8-4.8	1.2-1.6
12 (0805)	2.0	1.25	0.5-1.45	1.0-1.4	3.0-3.2	0.8-1.0	0.8-1.2	2.4-3.2	1.0-1.2
11 (0603)	1.6	0.8	0.8	0.8-1.0	2.0-2.6	0.6-0.8	0.8-1.0	2.0-2.6	0.8-1.0
10 (0402)	1.0	0.5	0.5	—	—	—	0.5-0.6	1.5-1.7	0.5-0.6

(2) Recommended amount of solder

Recommended amount of solder: As shown in Fig.2

Excess amount of solder gives large mechanical stresses to the Capacitors/components.


Fig.2 Recommended Amount of Solder



### 2.3 Component Layout

When placing/mounting the Capacitors/components near an area which is apt to bend or a grid groove on the PC board, it is advisable to have both electrodes subjected to uniform stresses, or to position the components electrodes at right angles to the grid groove or bending line.

Fig.3 Component Layout



### 2.4 Mounting Density and Spaces

Placements in too narrow spaces between components may cause "Solder Bridges", during soldering. The minimum space between components shall be 0.5 mm in view of the positioning tolerances of the mounting machines and the dimensional tolerances of the components and PC Boards.

### 2.5 Applications of Solder Resist

Applications of Solder Resist are effective to prevent solder bridges and to control amounts of solder on PC boards. (As shown in Table 2)

Table 2 Application Examples of Solder Resist

	Recommended Application Examples	Examples of Solder Bridges
Narrow Spacing between Chip Components	<b>Solder Resist</b> 	<b>Solder Bridge</b> 
Radial Components are directly connected to Chip Components	<b>Solder Resist</b> 	<b>Solder Bridge</b> 
Common lands (chassis, etc.) are close to Chip Components.	<b>Solder Resist</b> 	<b>Solder Bridge</b> 

## 3. Precautions for Assembly

### 3.1 Adhesives for Mounting

(1) Selection of adhesives

- The viscosity of an adhesive for mountings shall be such that the adhesive does not flow off on the land during it's curing.
- If the adhesive is too low in its viscosity, mounted components may be out of alignment after or during soldering.
- The adhesives shall not be corrosive or chemically active to the mounted components and the PC boards.

# Panasonic

## Multilayer Ceramic Capacitors

- The amount of adhesive shall be such that the adhesive does not flow off or be out of alignment.
- (2) Curing Conditions
- Adhesives for mountings can be cured by ultraviolet or infrared radiation. In order to prevent the terminal electrodes of the Capacitors from oxidizing. The curing shall be done at conditions of 160 °C max., for 2 minutes max.


### 3.2 Chip Mounting Consideration

In mounting the Capacitors/components on a printed circuit board,/any bending and expanding force against them shall be kept minimum to prevent them from being damaged or cracked.

Following precautions and recommendations shall be observed carefully in the process;


- (1) Maximum stroke of the vacuum nozzle shall be adjusted so that the pushing force to the printed circuit board shall be limited to a static load of 1 to 3 N (100 to 300 gf). (See Fig.4)
- (2) Maximum stroke of the nozzle shall be adjusted so that the maximum bending of printed circuit board does not exceed 0.5 mm. (See Fig.4)

Fig.4



- (3) The printed circuit board shall be supported by means of adequate supporting pins as shown in Fig.5-(b).

Fig.5



### 3.3 Soldering Flux and Solder

- (1) Soldering Flux:
  - The content of halogen in the soldering flux shall be 0.2 wt% or less.
  - Rosin-based and non-activated soldering flux is recommended.
- (2) Water soluble type Soldering Flux:
 

In case of water soluble type soldering flux being applied, the flux residue on the surface of P.C. boards may have influence on the reliability of the components and cause deterioration and failures of them.
- (3) Solder:
 


An eutectic solder (Sn63: Pb37) is recommended.

### 3.4 Soldering

#### 3.4.1 Flow Soldering

In flow soldering process, abnormal and large thermal and mechanical stresses, caused by "Temperature Gradient" between the mounted Capacitors and melted solder in a soldering bath, may be applied directly to the Capacitors, resulting in failure and damage of the capacitors. So it is essential that the soldering process shall be controlled to the following recommended conditions and precautions. (See Fig. 6)

Fig.6 Recommended Soldering Temperature-Time Profile (Flow soldering)



- (1) Application of Flux:
 

The soldering flux (3.3) shall be applied to the mounted Capacitors thinly and uniformly by forming method.
- (2) Preheating:
 

The mounted Capacitors/Components shall be preheated sufficiently so that the "Temperature Gradient" between the Capacitors/components and the melted solder shall be 150 °C or below.
- (3) Immersion to Soldering Bath:
 

The Capacitors shall be immersed into a soldering bath of 240 to 250 °C for 3 to 5 seconds.
- (4) Cooling:
 


The Capacitors shall be cooled gradually to room ambient temperature with the cooling temperature rates of 8 °C/s max. from 250 °C to 170 °C, and 4 °C/s max. from 170 °C to 130 °C.
- (5) Flux Cleaning:
 

When the Capacitors are immersed into cleaning solvent, it shall be confirmed that the surface temperatures of devices do not exceed 100 °C. (See 3.5)

#### 3.4.2 Reflow Soldering

In reflow soldering process, the mounted Capacitors/components are generally heated and soldered by a thermal conduction system such as an "Infrared radiation and hot blast soldering system" or a "Vapor Phase Soldering System (VPS)". Large temperature gradients such as a rapid heating and cooling in the process may cause electrical failure and mechanical damage of the devices. It is essential that the soldering process shall be controlled by the following recommended conditions and precautions. (See Fig.7)

Fig.7 Recommended Soldering Temperature-Time Profile (Reflow soldering)



- (1) Preheating 1:  
The mounted Capacitors/components shall be preheated sufficiently, for 60 to 90 seconds so that the surface temperatures of them to be 140 to 160 °C.
- (2) Preheating 2:  
After "Preheating 1", the mounted Capacitors/components shall be heated to the elevated temperatures of 150 to 200 °C for 2 to 5 seconds.
- (3) Soldering:  
The mounted Capacitors/components shall be heated under the specified heating conditions (200 to 240 to 200 °C for total of 20 to 40 seconds, See Fig.7) and shall be soldered at the maximum temperature of 240 °C for 10 seconds or less.
- (4) Cooling:  
After soldering, the mounted Capacitors/components shall be gradually cooled to room ambient temperature for preventing mechanical damages such as cracking of the devices.
- (5) Flux Cleaning:  
When the mounted Capacitors/components are immersed into cleaning solvent, it shall be confirmed the surface temperatures of them does not exceed 100 °C. (See, 3.5  $\Delta$  Post Soldering Cleaning)

Note: If the mounted Capacitors/components are partially heated in the soldering process, the devices may be separated from the printed circuit board by the surface tension of partially melted solder, and stand up like a "Tomb Stone".

### 3.4.3 Hand Soldering

In hand soldering of the Capacitors, large temperature gradient between preheated the Capacitors and the tip of soldering iron may cause electrical failures and mechanical damages such as cracking or breaking of the devices. The soldering shall be carefully controlled and carried out so that the temperature gradient is kept minimum with following recommended conditions for hand soldering.

[Recommended Soldering Conditions]

- (1) Solder:  
 $\phi$ 1 mm Thread eutectic solder (Sn63: Pb37) with soldering flux\* in the core.  
 \* Rosin-based, and non-activated flux is recommended.
- (2) Preheating:  
The capacitors shall be preheated so that "Temperature Gradient" between the devices and the tip of soldering iron is 150 °C or below.
- (3) Soldering Iron:  
Rated Power of 20 W max. with 3 mm soldering tip in diameter.
- (4) Temperature of soldering iron tip: 300 °C max.  
(The required amount of solder shall be melted in advance on the soldering tip.)
- (5) Cooling:  
After soldering, The Capacitors shall be cooled gradually at room ambient temperature.

### 3.5 $\Delta$ Post Soldering Cleaning

- (1) Residues of corrosive soldering fluxes on the PC board after cleaning may have great influence on the electrical characteristics and the reliability (such as humidity resistance) of the Capacitors which have been mounted on the board, it shall be confirmed that the characteristics and the reliability of the devices are not affected by the applied cleaning conditions.
- (2) Solubility of alternative cleaning solvent such as alcohol etc, is inferior to that of freon cleaning solvent in flux cleaning.  
So in the case of alternative cleaning solvents applied, fresh cleaning solvent shall always be used, and sufficient rinsing and drying shall be carried out.
- (3) When an ultrasonic cleaning is applied to the mounted Capacitors on PC boards, following conditions are recommended for preventing failure or damage of the devices due to the large vibration energy and the resonance caused by the ultrasonic waves :
 

Frequency	: 29 kHz max.
Radiated Power	: 20 W/liter max.
Period	: 5 minuts max.

### 3.6 Process Inspection

When the mounted printed circuits are inspected with measuring terminal pins, abnormal and excess mechanical stresses shall not be applied to the PC board and mounted components, to prevent failure or damage of the devices.

- (1) The mounted PC boards shall be supported by some adequate supporting pins to prevent their bending.
- (2) It shall be confirmed that the measuring pins have the right shaped tip, are equal in height and are set in the right positions.

### 3.7 Protective Coating

When the surface of a printed board on which the Capacitors has been mounted is coated with resin to protect against moisture and dust, it shall be confirmed that the protective coat does not influence the reliability of the capacitors in the actual equipment.

- (1) Coating materials, such as being corrosive and chemically active, shall not be applied to the Capacitors and other components.
- (2) Coating materials with a large expansivity shall not be applied to the Capacitors for preventing failures or damages (such as cracking) of the devices in the curing process.

### 3.8 $\Delta$ Dividing/Breaking of PC Boards

- (1) Abnormal and excessive mechanical stresses, such as bending or expanding force, on the components on the printed circuit board, shall be kept minimum in dividing/breaking.
- (2) Dividing/Breaking of the PC boards shall be done carefully at moderate speed by using a jig or apparatus to protect the Capacitors on the boards from mechanical damages.

### 3.9 Long Term Storage

The Capacitors shall not be stored under severe conditions of high temperatures and high humidities. Store them indoors under 40 °C max. and 75 % RH max.. Use them within 6 months and check the solderability before use. (See 1.5)