

147-144  
147-145  
147-146  
147-147

	To Fit	
	<p>W K2 P2 P5</p> <p>W. K2 P2</p>	<p><b>A19259 Sealing Washer</b> Black Neoprene 0.062" (1.6mm) thick</p> <p><b>A20055 Earthing Tag</b> Brass 0.031" (0.8mm) thick</p>
	<p>K2</p> <p>P5. W</p>	<p><b>A20254 Terminal Shroud</b> Black flexible P.V.C</p> <p><b>A20135 Terminal Shroud</b> (not illustrated)</p>
	<p>3N</p> <p>3F/T/D</p> <p>3R/S</p> <p>3K</p> <p>KS</p>	<p><b>A20201 Mounting Plate</b> Mild steel, chrome-plated</p> <p><b>A20389 Mounting Plate</b> Mild steel, nickel-plated. 23mm centre hole</p>
	<p>3F/T/D</p> <p>W. K2. P2</p>	<p><b>A20479 Drip-proof Lock Cover</b> Black P.V.C.</p>
	<p>3F/T/D</p> <p>3R/S*</p> <p>3K</p> <p>W. K2. P2. P5</p> <p>*Not suitable for mastered versions of R &amp; S locks</p>	<p><b>A20488/1 Heavy Duty Lock Cover</b> 3/4" x 26 TPI</p> <p><b>A20488/2 Heavy Duty Lock Cover</b> 13/16" x 26 TPI</p> <p><b>A20488/3 Heavy Duty Lock Cover</b> 23mm Black Nylon</p> <ul style="list-style-type: none"> <li>• Spring Loaded</li> <li>• Screws on body in place of bezel</li> <li>• Maximum projection from panel when closed 13/16"</li> </ul>

## Standard Switch Enclosures

SHEET STEEL		Drawing No.	Nominal Internal Dimensions (ins)	Wall s.w.g.	
			X Y Z		
		B20291/1	3 x 3 x 2	o	20
		B20291/2	3 x 3 x 3	o	20
		B20291/3	4 x 4 x 2	w	18
		B20291/4	4 x 4 x 3	w	18
		B20291/5	4 x 4 x 4	w	18
		B20291/6	6 x 6 x 4	w	16
		B20291/7	6 x 6 x 6	w	16
		B20291/8	8 x 8 x 6	w	16
		B20291/9	8 x 8 x 8	w	16
<p>o = open seams w = all welded seams</p>					
CAST ALUMINIUM		Drawing No.	Nominal Internal Dimensions (ins)		
			X Y Z		
		B20292/1	2 1/2 x 2 1/2 x 2 1/2		0.25"
			Max. wall thickness		
<p>Cases can be drilled or fitted with the switch upon request</p> <p>All supplied with one tapped 20mm conduit entry only, unless otherwise stated. Standard finish is Silver Hammer, except B20291/1 and B20291/2 which are black, and have flat lids for flush mounting and knockouts. Drip or weatherproofing can be provided on all except B20291/1 and B20291/2. Wall mounting holes are provided only if specified. Special boxes can be supplied to customers' specification.</p>					