

EXCELON®72
General Purpose Filter/Regulator
1/4", 3/8" Port Sizes

- **EXCELON design allows in-line installation or modular installation with other Excelon 72 products**
- **High efficiency water and particle removal**
- **Quick release bayonet bowl**
- **Patented quarter turn manual drain**
- **Highly visible, prismatic liquid level indicator lens on metal bowls**
- **Full flow gauge ports**
- **Balanced valve design for optimum pressure control**
- **Push to lock adjusting knob with tamper resistant accessory**

Technical Data

Fluid: Compressed air

Maximum pressure:

Transparent bowl:

10 bar (145 psig)

Metal bowl:

With manual or semi automatic drain: 17 bar (250 psig)

With automatic drain: 8 bar (116 psig)

Operating temperature*:

Transparent bowl: -20° to +50°C (0° to +125°F)

Metal bowl: -20° to +65°C (0° to +150°F)

* Air supply must be dry enough to avoid ice formation at temperatures below 2°C (35°F).

Partical removal: 5 µm, 25 µm or 40 µm. Within ISO 8573-1, Class 3 and Class 5

Typical flow at 10 bar (145 psig) inlet pressure, 6,3 bar (90 psig) set pressure and a droop of 1 bar (15 psig) from set: 38 dm³/s (80 scfm)

Manual drain thread: 7/16-24 UNS male for 1/4" tube nut and ferrule

Semi automatic drain connection: 8 mm (5/16") ID tube

Semi automatic drain operating pressure:

Drain closes when bowl pressure exceeds 0,1 bar (1.5 psig) and opens when bowl pressure drops below 0,1 bar (1.5 psig).

Can be operated manually by lifting the stem.

Automatic drain connection: ISO R1/8

Automatic drain operating conditions:

Minimum flow to close drain: 0,14 dm³/s (0.3 scfm)

Drain closes when bowl pressure exceeds 0,7 bar (10 psig) and opens when bowl pressure drops below 0,07 bar (1 psig).

Gauge ports:

1/8" PTF with PTF main ports

1/8" ISO Rc with ISO Rc main ports

1/8" ISO Rc with ISO G main ports

Nominal bowl size:

Short bowl: 56 ml (1.9 ounce)

Long bowl: 65 ml (2.2 ounce)



Materials:

Body: Zinc

Bonnet: Acetal

Valve: Brass

Bowl:

Transparent: Polycarbonate

Metal: Zinc

Metal bowl liquid level indicator lens:

Transparent nylon


Element: Sintered polypropylene

Elastomers: Neoprene and nitrile


Ordering Information

See *Ordering Information* on the following pages.


ISO Symbols




Automatic and
Semi Automatic Drain
Relieving



Manual Drain
Relieving





Automatic and
Semi Automatic Drain
Non Relieving



Manual Drain
Non Relieving



Typical Performance Characteristics



Ordering Information. Models listed include BSP threads, knob adjustment, semi automatic drain, transparent bowl without guard, 40 µm element, relieving diaphragm, 0,3 to 10 bar (5 to 145 psig) outlet pressure adjustment range* without gauge.

Port Size	Model	Flow† dm³/s (scfm)	Weight kg (lb)
G1/4	B72G-2GK-ST3-RMN	38 (80)	0,52 (1.15)
G3/8	B72G-3GK-ST3-RMN	38 (80)	0,52 (1.15)

† Typical flow with 10 bar (145 psig) inlet pressure, 6,3 bar (90 psig) set pressure and a 1 bar (15 psig) droop from set.

Alternative Models





B 7 2 G - ★ ★ ★ - ★ ★ ★ - ★ ★ ★			
Port Size	Substitute	Gauge	Substitute
1/4"	2	With	G
3/8"	3	Without	N
Threads	Substitute	Outlet Pressure Adjustment Range*	Substitute
PTF	A	0,3 to 2 bar (5 to 30 psig)	C
ISO Rc taper	B	0,3 to 4 bar (5 to 60 psig)	F
ISO G parallel	G	0,3 to 10 bar (5 to 145 psig)	M
Adjustment	Substitute	Diaphragm	Substitute
Knob	K	Relieving	R
T-bar	T	Non relieving	N
		Element	Substitute
		5 µm	1
		25 µm	2
		40 µm	3
		Bowl	Substitute
		Metal with liquid level indicator	D
		Transparent without guard	T
		Long transparent without guard	L
		Drain	Substitute
		1/4 turn manual	Q
		Semi automatic	S
		Auto drain†	A


* Outlet pressure can be adjusted to pressures in excess of, and less than, those specified. Do not use these units to control pressures outside of the specified ranges.

† Supplied in long bowl options only



Accessories


				
Wall Mounting Bracket	Neck Mounting Bracket	Pressure Gauge	Ø 40 mm R1/8 Connection	1/8 PTF Connection
4224-50	74316-50	4 bar (60 psig):	18-013-990	18-013-211
	Includes plastic panel nut	10 bar (150 psig):	18-013-989	18-013-212
		25 bar (360 psig):	18-013-908	
			Plastic: 4248-89	


Tamper Resistant Cover and Seal wire
4255-51
Seal Wire: 2117-01

Dimensions mm (inches)

Panel mounting hole diameter: 40 mm (1.57")

Panel thickness: 0 to 4 mm (0" to 0.16")



* For semi automatic drain add 30 mm (1.17") to 1/4 turn manual drain shown.


† Minimum clearance required to remove bowl. For semi automatic drain add 30 mm (1.17") to 1/4 turn manual drain shown.




Bracket Mounting

Wall Bracket

Use 4 mm (5/32") screws to mount bracket to wall.



Neck Mounting for B72, R72, V72, includes plastic panel nut
Use 4 mm (5/32") screws to mount bracket to wall.




Service Kits

Item	Type	Part Number
Service kit	Relieving	4383-500
	Non relieving	4383-501
Replacement elements	5 µm	5925-03
	25 µm	5925-01
	40 µm	5925-02
Liquid level lens kit	Prismatic	4380-030
Replacement drains	1/4 turn manual	619-50
	Semi automatic	5379-RK
	Automatic	4000-50R

Service kit includes diaphragm assembly, valve assembly, valve spring, louvre o-ring, bowl o-ring, drain seal.

Quikclamp and Quikclamp Wall Bracket

Use 5 mm (3/16") screws to mount bracket to wall.



Bracket Kit Reference

Item	Part Number
Wall bracket	4224-50
Neck mounting wall bracket	74316-50
Quikclamp and Quikclamp wall bracket	4214-52

Warning

These products are intended for use in industrial compressed air systems only. Do not use these products where pressures and temperatures can exceed those listed under 'Technical Data'.

Before using these products with fluids other than those specified, for non-industrial applications, life-support systems, or other applications not within published specifications, consult NORGREN.

Through misuse, age, or malfunction, components used in fluid power systems can fail in various modes. The system designer is warned to consider the failure modes of all component parts used in fluid power systems and to provide adequate safeguards to prevent personal injury or damage to equipment in the event of such failure.

System designers must provide a warning to end users in the system instructional manual if protection against a failure mode cannot be adequately provided.

System designers and end users are cautioned to review specific warnings found in instruction sheets packed and shipped with these products.

Water vapor will pass through these units and will condense into liquid if air temperature drops in the downstream system. Install an air dryer if water condensation could have a detrimental effect on the application.