

SPECIFICATION SHEET

JFW MODEL 50D-051

DETECTOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range 1-2000 MHz
Impedance 50 Ohms nominal
VSWR 1.2:1 maximum 1-1000 MHz
1.3:1 maximum 1000-2000 MHz
Flatness ± 0.3 dB

Typical Sensitivity
(-20 dBm) 0.006 V
(-10 dBm) 0.050 V
(0 dBm) 0.220 V
(+10 dBm) 0.840 V
(+20 dBm) 2.650 V

DC Output Polarity Positive or Negative
(customer to specify)

RF Input Power 100 mW maximum

RF Input Connector BNC, TNC, SMA or N male

DC Output Connector BNC, TNC, SMA or N Female

Operating Temperature Range -40°C to +85°C

Physical Size See outline drawing

092-5252 (BNC M / BNC F)
092-5251 (N M / BNC F)
092-5402 (SMA M / BNC F)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	11/20/2006		CLK 11/20/2006				
14147	05/02/2007	A	CLK 05/02/2007				
15350	02/11/2008	B	CLK 02/11/2008				