





JENTEC TECHNOLOGY CO., LTD

JTA0302X-EX 15W Switching Adapter Series

FEATURES	SPECIFICATIONS
	<p>Input Characteristics</p> <p>Voltage 90 ~ 264VAC</p> <p>Frequency 47 to 63Hz</p> <p>Inrush Current 30A max. @ 115VAC</p> <p>Conducted EMI BSMI,CISPR22 class B</p> <p>Safety EN/UL60950</p> <p>Leakage Current 0.25mA max.</p> <p>Output Characteristics</p> <p>Hold-up Time 10mSec. @ 115VAC</p> <p>Short Circuit Protection Continuous</p> <p>Over Voltage Protection Option</p> <p>Environmental Characteristics</p> <p>Operating Temperature 0 to 40°C</p> <p>Storage Temperature -25 to +85°C</p> <p>Mechanical Characteristics</p> <p>Dimensions 75 x 54 x 34 mm</p> <p>Weight 158g</p> <p>AC Inlet 2PIN</p>



D33190



0 4 2 3 X X - 1 1

Model	Output Voltage	Output Current	Ripple & Noise	Line Regulation	Load Regulation
JTA0302D-EX	5V	2.0 A	50mV	+/-1%	+/-5%
JTA0302E-EX	5V	2.5 A	50mV	+/-1%	+/-5%
JTA0302F-EX	5V	3.0 A	50mV	+/-1%	+/-5%
JTA0302G-EX	6V	1.5 A	60mV	+/-1%	+/-5%
JTA0302H-EX	6V	2.5 A	60mV	+/-1%	+/-5%
JTA0302M-EX	5V	2.4 A	50mV	+/-1%	+/-5%

JENTEC TECHNOLOGY CO., LTD.