





**Led Signalleuchten Einbaudurchmesser 6 mm**  
**Led Indicators Body diameter 6 mm**

**Außenreflektor**  
**Exterior reflector**

Bestell-Nr. Part No.	Farbe Colour	$V_{OP} +10\%$ (V)	$I_{OP max.}$ (mA)	$V_F$ (V)	$I_{V typ. (mcd)}$ $*I_F = 20mA$	$I_{F max.}$ (mA)	Abb. Illu.	Abmessungen, siehe Zeichnungsnr. Dimensions, see Drawing No.	19020-A	A			
1902*000	Rot Red			1,6/2,0	*4,0	75	A		19020-A	A			
1902*001	Grün Green			2,0/2,6	*27,0	45	A						
1902*002	Gelb Yellow			2,0/2,6	*32,0	45	A						
1902*003	Super rot Super red			2,0/2,6	*17,5	45	A						
1902*050	Rot Red			1,6/2,0	*4,0	75	B					19020-B	B
1902*051	Grün Green			2,0/2,6	*27,0	45	B						
1902*052	Gelb Yellow			2,0/2,6	*32,0	45	B						
1902*053	Super rot Super red			2,0/2,6	*17,5	45	B						
1902*150	Rot Red	6	30		4,0		B						
1902*151	Grün Green	6	30		48,0		B					19020-B	B
1902*152	Gelb Yellow	6	30		41,0		B						
1902*153	Super rot Super red	6	30		23,5		B						
1902*250	Rot Red	12	30		4,0		B						
1902*251	Grün Green	12	30		48,0		B						
1902*252	Gelb Yellow	12	30		41,0		B						
1902*253	Super rot Super red	12	30		23,5		B						
1902*350	Rot Red	24	18		3,7		B						
1902*351	Grün Green	24	18		28,5		B						
1902*352	Gelb Yellow	24	18		24,5		B						
1902*353	Super rot Super red	24	18		15,0		B		19020-B	B			

**Blaue Led Signalleuchten** lieferbar.

Bei Bestellung bitte an die letzte Stelle der jeweiligen Bestellnummer die "7" einsetzen.

Arbeitstemperatur ( $T_{OP}$ ): -55°C - +70°C  
 Lagertemperatur ( $T_{STG}$ ): -55°C - +100°C

\* Die Signalleuchte kann mit Glanzchrom oder Schwarzchrom geliefert werden. Die 5. Stelle der Bestellnummer wird mit 0 oder 1 codiert.

Glanzchrom = 0                      Schwarzchrom = 1

Beispiel:                      19020000 rot mit Glanzchrom  
                                     19021000 rot mit Schwarzchrom

**Led Signalleuchten mit anderen Spannungen auf Anfrage**

Technische Änderungen vorbehalten

**Blue Led Indicators** can be supplied.

When ordering, please use on the relevant partnumber the "7" for the last digit.

Operating temperature ( $T_{OP}$ ): -55°C - +70°C  
 Storage temperature ( $T_{STG}$ ): -55°C - +100°C

\* The Led indicator can be delivered in bright or black chrome reflector. The 5. digit has to be coded with 0 or 1.

Bright chrome = 0                      Black chrome = 1

Example:                      19020000 red with bright chrome  
                                     19021000 red with black chrome

**Led Indicators with other voltages upon request**

Specification subject to change without notice