

## General Description

The AAT7157 low threshold 20V, dual P-Channel MOSFET is a member of AnalogicTech™'s TrenchDMOS™ product family. Using an ultra-high density proprietary TrenchDMOS technology the AAT7157 is designed for use as a load switch in battery powered applications and protection in battery packs.


## Features

- $V_{DS(MAX)} = -20V$
- $I_{D(MAX)}^1 = -5.8A @ 25^{\circ}C$
- Low  $R_{DS(ON)}$ :
  - $36 m\Omega @ V_{GS} = -4.5V$
  - $62 m\Omega @ V_{GS} = -2.5V$

## Applications

- Battery Packs
- Battery-powered portable equipment

## Dual SOP-8L Package



www.DataSheet4U.com

## Absolute Maximum Ratings ( $T_A = 25^{\circ}C$ unless otherwise noted)

Symbol	Description	Value	Units
$V_{DS}$	Drain-Source Voltage	-20	V
$V_{GS}$	Gate-Source Voltage	$\pm 12$	
$I_D$	Continuous Drain Current @ $T_J = 150^{\circ}C$ <sup>1</sup>	$T_A = 25^{\circ}C$	A
		$T_A = 70^{\circ}C$	
$I_{DM}$	Pulsed Drain Current <sup>2</sup>	$\pm 24$	A
$I_S$	Continuous Source Current (Source-Drain Diode) <sup>1</sup>	-1.5	
$P_D$	Maximum Power Dissipation <sup>1</sup>	$T_A = 25^{\circ}C$	W
		$T_A = 70^{\circ}C$	
$T_J, T_{STG}$	Operating Junction and Storage Temperature Range	-55 to 150	$^{\circ}C$

## Thermal Characteristics

Symbol	Description	Value	Units
$R_{\theta JA}$	Typical Junction-to-Ambient steady state <sup>1</sup>	100	$^{\circ}C/W$
$R_{\theta JA2}$	Maximum Junction-to-Ambient $t < 10$ seconds <sup>1</sup>	62.5	
$R_{\theta JF}$	Typical Junction-to-Foot <sup>1</sup>	35	

**Electrical Characteristics** ( $T_J=25^\circ\text{C}$  unless otherwise noted)

Symbol	Description	Conditions	Min	Typ	Max	Units
DC Characteristics						
BV <sub>DSS</sub>	Drain-Source Breakdown Voltage	V <sub>GS</sub> =0V, I <sub>D</sub> =-250μA	-20			V
R <sub>DS(ON)</sub>	Drain-Source ON-Resistance <sup>2</sup>	V <sub>GS</sub> =-4.5V, I <sub>D</sub> =-5.8A		29	36	mΩ
		V <sub>GS</sub> =-2.5V, I <sub>D</sub> =-4.4A		49	62	
I <sub>D(ON)</sub>	On-State Drain Current <sup>2</sup>	V <sub>GS</sub> =-4.5V, V <sub>DS</sub> =5V (Pulsed)	-24			A
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>GS</sub> =V <sub>DS</sub> , I <sub>D</sub> =-250μA	-0.6			V
I <sub>GSS</sub>	Gate-Body Leakage Current	V <sub>GS</sub> =±12V, V <sub>DS</sub> =0V			±100	nA
I <sub>DSS</sub>	Drain Source Leakage Current	V <sub>GS</sub> =0V, V <sub>DS</sub> =-20V			-1	μA
		V <sub>GS</sub> =0V, V <sub>DS</sub> =-16V, T <sub>J</sub> =70°C <sup>3</sup>			-5	
g <sub>fs</sub>	Forward Transconductance <sup>2</sup>	V <sub>DS</sub> =-5V, I <sub>D</sub> =-5.8A		12		S
Dynamic Characteristics <sup>3</sup>						
Q <sub>G</sub>	Total Gate Charge	V <sub>DS</sub> =-15V, R <sub>D</sub> =2.6Ω, V <sub>GS</sub> =-4.5V		14		nC
Q <sub>GS</sub>	Gate-Source Charge	V <sub>DS</sub> =-15V, R <sub>D</sub> =2.6Ω, V <sub>GS</sub> =-4.5V		2.3		
Q <sub>GD</sub>	Gate-Drain Charge	V <sub>DS</sub> =-15V, R <sub>D</sub> =2.6Ω, V <sub>GS</sub> =-4.5V		5.5		
t <sub>D(ON)</sub>	Turn-ON Delay	V <sub>DS</sub> =-15V, R <sub>D</sub> =2.6Ω, V <sub>GS</sub> =-4.5V, R <sub>G</sub> =6Ω		10		ns
t <sub>R</sub>	Turn-ON Rise Time	V <sub>DS</sub> =-15V, R <sub>D</sub> =2.6Ω, V <sub>GS</sub> =-4.5V, R <sub>G</sub> =6Ω		37		
t <sub>D(OFF)</sub>	Turn-OFF Delay	V <sub>DS</sub> =-15V, R <sub>D</sub> =2.6Ω, V <sub>GS</sub> =-4.5V, R <sub>G</sub> =6Ω		36		
t <sub>F</sub>	Turn-OFF Fall Time	V <sub>DS</sub> =-15V, R <sub>D</sub> =2.6Ω, V <sub>GS</sub> =-4.5V, R <sub>G</sub> =6Ω		52		
Source-Drain Diode Characteristics						
V <sub>SD</sub>	Source-Drain Forward Voltage <sup>2</sup>	V <sub>GS</sub> =0, I <sub>S</sub> =-5.8A			-1.5	V
I <sub>S</sub>	Continuous Diode Current <sup>1</sup>				-1.5	A

Note 1: Based on thermal dissipation from junction to ambient while mounted on a 1" x 1" PCB with optimized layout. A 10 second pulse on a 1" x 1" PCB approximates testing a device mounted on a large multi-layer PCB as in most applications.  $R_{\theta JF} + R_{\theta FA} = R_{\theta JA}$  where the foot thermal reference is defined as the normal solder mounting surface of the device's leads.  $R_{\theta JF}$  is guaranteed by design, however  $R_{\theta CA}$  is determined by the PCB design. Actual maximum continuous current is limited by the application's design.


Note 2: Pulse test: Pulse Width = 300  $\mu s$

Note 3: Guaranteed by design. Not subject to production testing.


## Typical Characteristics

( $T_J = 25^\circ\text{C}$  unless otherwise noted)


**Output Characteristics**




**Transfer Characteristics**




**On-Resistance vs. Drain Current**




**On-Resistance vs. Gate to Source Voltage**



**On-Resistance vs. Junction Temperature**




**Threshold Voltage**




### Typical Characteristics

( $T_J = 25^\circ\text{C}$  unless otherwise noted)


Gate Charge



Source-Drain Diode Forward Voltage



Capacitance






### Ordering Information

Package	Marking	Part Number (Tape and Reel)
SOP-8	7157	<b>AAT7157IAS-T1</b>

Note: Sample stock is generally held on all part numbers listed in **BOLD**.

### Package Information

#### SOP-8



All dimensions in millimeters.

AnalogicTech cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in an AnalogicTech product. No circuit patent licenses, copyrights, mask work rights, or other intellectual property rights are implied.

AnalogicTech reserves the right to make changes to their products or specifications or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgement, including those pertaining to warranty, patent infringement, and limitation of liability.

AnalogicTech warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with AnalogicTech's standard warranty. Testing and other quality control techniques are utilized to the extent AnalogicTech deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed.

**Advanced Analogic Technologies, Inc.**  
**830 E. Arques Avenue, Sunnyvale, CA 94085**  
**Phone (408) 737-4600**  
**Fax (408) 737-4611**