SAFETY ANTI-FATIGUE



KEY FEATURES

- Comfortable to stand on and designed to reduce operator fatigue, leading to increased productivity.
- Weight in the Highly visible yellow border increases safety awareness.
- Made from 100% closed cell PVC foam.
- Pebble surface enables easy cleaning.
- 6 Effectively insulates against a cold concrete floor.

SUITABLE APPLICATIONS

♦ Dry environments.

♦ Ideal for INDUSTRIAL use, in dry, indoor situations, particularly PRODUCTION LINES, ASSEMBLY AREAS, PACKING STATIONS and WORKBENCHES.

FATIGUE PREVENTION	WEAR TOLERANCE	SLIP RESISTANCE
Good	Moderate	Moderate

PRODUCT DATA

Material:

Virgin Closed Cell PVC (Foam)

Appearance:

Pebble finish with 100 mm yellow border

Thickness: 9 mm nominal

Chemical Resistance:

* PVC is resistant to many different chemicals, alkalis and general industrial chemicals. Resists alcohol's, aliphatic hydrocarbons, oils, weak acids, strong mineral acids and alkalis. Resists oil and grease if properly cleaned. Does NOT resist organic solvents, ketones,

esters and aromatic hydrocarbons.

UV Resistance:

N/A

Operating Temperature:

 0° c to $+60^{\circ}$ c

Flame Retardancy:

Conforms to FMVSS 302. Will not burn after the ignition source is

removed. When 'forced' to burn, Carbon Monoxide, Carbon

Dioxide and Hydrogen Chloride fumes are emitted.

INSTALLATION & CLEANING

Installation:

Loose lay

Cleaning:

Brush/mop the top surface.

SIZES & OPTIONS

Sizes:

 $0.6 \text{ m} \times 0.9 \text{ m}, \ 0.9 \text{ m} \times 1.5 \text{ m}, \ 0.9 \text{ m} \times 18.3 \text{ m}$

Special sizes available on request.