

DESIGNED TO MITI STANDARD

5 x 20 mm Medium Acting Fuse



- Designed to Japanese Standard JIS C6575.
- Available in Cartridge, Axial and Radial Lead Format.
- Available in ratings of 500mA to 10A.

ELECTRICAL CHARACTERISTICS:

% of Ampere Rating	Opening Time
130%	1 hour, Minimum
160%	1 hour, Maximum
200%	2 minutes, Maximum

AGENCY APPROVALS: MITI B Approval.

INTERRUPTING RATING:

500 amperes at 125 VAC

100 amperes at 250 VAC

PACKAGING: For Axial Leads add packaging suffix XE. For Radial Leads add packaging suffix XW. For tape and reel options contact Littelfuse.

ORDERING INFORMATION:

Catalog Number	Ampere Rating	Voltage Rating	Nominal Resistance Cold Ohms	Nominal Melting I ² t A ² Sec
0232.500*	.500	250	0.60	1.11
0232.630*	.630	250	0.46	2.18
0232.800*	.800	250	0.48	3.59
0232.001.	1	250	0.0957	1.41
0232.1.25	1.25	250	0.0707	4.22
0232.01.6	1.6	250	0.0567	7.14
0232.002.	2	250	0.0385	8.47
0232.02.5	2.5	250	0.0297	14.25
0232.003.	3	250	0.0257	17.65
0232.3.15	3.15	250	0.0235	22.55
0232.004.	4	250	0.018	38.75
0232.005.	5	250	0.0145	58.25
0232.06.3	6.3	250	0.0105	92.85
0232.008.	8	250	.0076	187.5
0232.010.	10	250	.0061	298.5

*Japanese Standards for 5 x 20 mm fuses do not include ratings below 1 ampere.

