


**SOT23 NPN PLANAR
SMALL SIGNAL TRANSISTORS**

ISSUE 2 – FEBRUARY 1995

**BCW71
BCW72**

PARTMARKING DETAILS –	BCW71	– K1
	BCW72	– K2
	BCW71R	– K4
	BCW72R	– K5



ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	V_{CBO}	50	V
Collector-Emitter Voltage	V_{CEO}	45	V
Emitter-Base Voltage	V_{EBO}	5	V
Peak Pulse Current	I_{CM}	200	mA
Continuous Collector Current	I_C	100	mA
Power Dissipation at $T_{amb}=25^\circ\text{C}$	P_{TOT}	330	mW
Operating and Storage Temperature Range	tj:tstg	-55 to +150	°C


ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^\circ\text{C}$ unless otherwise stated).

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Collector-Base Cut-Off Current	I_{CBO}			100 10	nA μA	$I_E=0, V_{CB}=20V$ $I_E=0,$ $V_{CB}=20V, T_j=100^\circ\text{C}$
Base-Emitter Voltage	V_{BE}	550		700	mV	$I_C=2.0\text{mA}, V_{CE}=5\text{V}$
Collector-Emitter Saturation Voltage	$V_{CE(\text{sat})}$		120 210	250	mV mV	$I_C=10\text{mA}, I_B=0.5\text{mA}$ $I_C=50\text{mA}, I_B=2.5\text{mA}$
Base-Emitter Saturation Voltage	$V_{BE(\text{sat})}$		750 850		mV mV	$I_C=10\text{mA}, I_B=0.5\text{mA}$ $I_C=50\text{mA}, I_B=2.5\text{mA}$
Static Forward Current Transfer Ratio	h_{FE}	110	90	220		$I_C=10\mu\text{A}, V_{CE}=5\text{V}$ $I_C=2\text{mA}, V_{CE}=5\text{V}$
		200	150	450		$I_C=10\mu\text{A}, V_{CE}=5\text{V}$ $I_C=2\text{mA}, V_{CE}=5\text{V}$
Transition Frequency	f_T		300		MHz	$I_C=10\text{mA}, V_{CE}=5\text{V}$ $f=35\text{MHz}$
Collector Capacitance	C_{TC}			4	pF	$I_E=I_e=0, V_{CB}=10\text{V}$ $f=1\text{MHz}$
Noise Figure	N			10	dB	$I_C=200\mu\text{A}, V_{CE}=5\text{V}$ $R_S=2\text{K}\Omega, f=1\text{KHz}$ $B=200\text{Hz}$

*Measured under pulsed conditions. Pulse width=300μs. Duty cycle ≤2%
Spice parameter data is available upon request for these devices

BCW71

BCW72



DIM	Millimeters		Inches	
	Min	Max	Min	Max
A	2.67	3.05	0.105	0.120
B	1.20	1.40	0.047	0.055
C	—	1.10	—	0.043
D	0.37	0.53	0.0145	0.021
F	0.085	0.15	0.0033	0.0059
G	NOM 1.9		NOM 0.075	
K	0.01	0.10	0.0004	0.004
L	2.10	2.50	0.0825	0.0985
N	NOM 0.95		NOM 0.37	

