


145224 + 145225



ROADRUNNER DISTRIBUTION STRIPS



Order No.

- RRS-G-102 General purpose glue strip 20/pkt.
- RRS-G-103 High density glue strips 20/pkt.
- RRS-P-102 Press fit strips 20/pkt.



The distribution strips are used to route and support the wiring in position. The strip has several advantages – it allows point-to-point wiring of components to be very fast and neat, prevents breakage, is simply and quickly fitted, and provides easy access for test and modification as there are no impeding posts.

Furthermore, a strip can comfortably contain a large number of wires without losing its very low profile (only 5.4mm total height including board).

The strips are of patented design (No. 1469581) and are available in 51mm (2'') lengths for press fitting, or in 152mm (6'') lengths for adhesive fixing. Two types of the glue fix strip are available – general purpose or high wiring density applications. The press fitting type is intended for use on any boards having 1.02mm dia. drillings on 2.54mm pitch matrix.

Material

Glue type ABS plastic
Press type Nylon 66.



Type	Dimensions (mm)							
	a	b	c	d	e	f	g	h
General purpose Glue Strip	152	5.08	3.81	3.81	2.54	2.54	-	-
High density Glue Strip	152	3.81	3.81	3.81	2.54	2.54	-	-
Press fit Strip	51	5.08	3.81	3.81	2.54	2.54	1.02 nom.	1.4