

E-Series Plug-In Mixer

0.07 - 200 MHz

EMR-3

V3.00

Features

- LO Power: +23 dBm
- Up to +15 dBm RF

Specifications @ 25°C

Frequency Range		
RF		0.07 - 200 MHz
LO		0.07 - 200 MHz
IF		DC - 200 MHz
Conversion Loss (dB)		
0.14 - 100 MHz	Typical 6.0	Maximum 7.5
0.07 - 200 MHz	Typical 6.5	Maximum 8.0
Isolation (dB)		
LO to RF	Typical	Minimum
0.07 - 0.7 MHz	55	45
0.7 - 100 MHz	40	30
100 - 200 MHz	30	25
LO to IF		
0.07 - 0.7 MHz	55	45
0.7 - 100 MHz	40	30
100 - 200 MHz	30	20

Operating Characteristics

Impedance	50 Ohms Nominal
RF input for 1dB Compression	+15 dBm


Ordering Information

Part No.	Packaging
EMR-3	Tube
EMR-3TR	Forward Tape & Reel

Absolute Maximum Ratings

Parameter	Absolute Maximum
RF Power	350 mW
Peak IF Current	40 mA
Storage Temperature	-55°C to 100°C
Operating Temperature	-55°C to 100°C
Pin Temperature (10 Seconds)	260°C

R-1



Dimensions in () are in mm.
 Unless Otherwise Noted: .x = ±0.04 (1.00)
 .xx = ±0.02 (0.50)
 .xxx = ±0.010 (0.250)
 WEIGHT (APPROX.): 0.16 OUNCES 4.4 GRAMS

Pin Configuration

Function	Pin No.
LO	8
RF	1
IF*	3,4
Ground	2,5,6,7
Case Ground	2

*IF pins must be connected together externally.

S 0084 B