

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [0039299183](#)  
**Status:** **Active**  
**Overview:** [minifit\\_jr](#)  
**Description:** 4.20mm (.165") Pitch Mini-Fit Jr.™ Header, Dual Row, Vertical, with Snap-in Plastic Peg PCB Lock, 18 Circuits, PA Polyamide Nylon 6/6 94V-2, Tin (Sn) Plating, without Drain Holes

**Documents:**

[3D Model](#) [Product Specification PS-5556-001 \(PDF\)](#)  
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

**Agency Certification**

|     |           |
|-----|-----------|
| CSA | LR19980   |
| TUV | R72081037 |
| UL  | E29179    |

**General**

|                |  |
|----------------|--|
| Product Family | PCB Headers  |
| Series         | <a href="#">5566</a>   |
| Application    | Wire-to-Board  |
| Comments       | Current = 13A max. per circuit when header is mated to a receptacle loaded with <a href="#">45750</a> Mini-Fit Plus HCS™ Crimp Terminal Crimped to to 16 AWG wire. . See Molex product specification PS-45750-001 for additional current de-rating information.. High Temperature, Square Pin, Solder Type |
| Overview       | <a href="#">minifit_jr</a>   |
| Product Name   | Mini-Fit Jr.™  |

**Physical**

|                                |          |
|--------------------------------|----------|
| Breakaway                      | No       |
| Circuits (Loaded)              | 18       |
| Circuits (maximum)             | 18       |
| Color - Resin                  | Natural  |
| Durability (mating cycles max) | 30       |
| First Mate / Last Break        | No       |
| Flammability                   | 94V-2    |
| Glow-Wire Compliant            | No       |
| Guide to Mating Part           | No       |
| Keying to Mating Part          | None     |
| Lock to Mating Part            | Yes      |
| Material - Metal               | Brass    |
| Material - Plating Mating      | Tin      |
| Material - Plating Termination | Tin      |
| Material - Resin               | Nylon    |
| Number of Rows                 | 2        |
| Orientation                    | Vertical |
| PC Tail Length (in)            | 0.138 In |
| PC Tail Length (mm)            | 3.50 mm  |
| PCB Locator                    | Yes      |
| PCB Retention                  | Yes      |
| PCB Thickness Recommended (in) | 0.062 In |
| PCB Thickness Recommended (mm) | 1.60 mm  |
| Packaging Type                 | Tray     |
| Pitch - Mating Interface (in)  | 0.165 In |
| Pitch - Mating Interface (mm)  | 4.20 mm  |



**EU RoHS**

**ELV and RoHS Compliant**  
**REACH SVHC**  
 Not Reviewed  
**Halogen-Free Status**  
**Not Reviewed**

**China RoHS**



**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

**Search Parts in this Series**

[5566Series](#)

**Mates With**

[5557](#) Mini-Fit Jr.™ Receptacle Housing

|                                |                 |
|--------------------------------|-----------------|
| Pitch - Term. Interface (in)   | 0.165 In        |
| Pitch - Term. Interface (mm)   | 4.20 mm         |
| Plating min: Mating (µin)      | 35              |
| Plating min: Mating (µm)       | 0.90            |
| Plating min: Termination (µin) | 100             |
| Plating min: Termination (µm)  | 2.50            |
| Polarized to Mating Part       | Yes             |
| Polarized to PCB               | Yes             |
| Shrouded                       | Fully           |
| Stackable                      | No              |
| Surface Mount Compatible (SMC) | No              |
| Temperature Range - Operating  | -40°C to +105°C |
| Termination Interface: Style   | Through Hole    |

### **Electrical**

|                               |      |
|-------------------------------|------|
| Current - Maximum per Contact | 13A  |
| Voltage - Maximum             | 600V |

### **Solder Process Data**

|  |                        |
|--|------------------------|
| Duration at Max. Process Temperature (seconds) | 5                      |
| Lead-free Process Capability                   | Wave Capable (TH only) |
| Max. Cycles at Max. Process Temperature        | 1                      |
| Process Temperature max. C                     | 240                    |

### **Material Info**

|                 |           |
|-----------------|-----------|
| Old Part Number | A556618A2 |
|-----------------|-----------|

### **Reference - Drawing Numbers**

|                         |                 |
|-------------------------|-----------------|
| Packaging Specification | PK-5566-001     |
| Product Specification   | PS-5556-001     |
| Sales Drawing           | SDA-5566-N*2*-* |
| Test Summary            | TS-5556-002     |

This document was generated on 05/21/2010

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**



**NOTES:**

- 1) HOUSING MATERIAL:
  - "BLANK" - NYLON 6/6, U.L. 94V-2, COLOR: NATURAL.
  - 210 - NYLON 6/6, U.L. 94V-0, COLOR: NATURAL.
  - BL - NYLON 6/6, U.L. 94V-2, COLOR: DYED BLACK.
- 2) TERMINAL MATERIAL: BRASS ALLOY 260
- 3) PART MATES WITH MINI-FIT JR. RECEPTACLE #5557.
- 4) PACKAGING: SEE CHARTS
- 5) MOUNTING OPTIONS:
  - "BLANK" - NO MOUNTING (SEE SD-5566-NA AND -NB SERIES DWGS.)
  - 2 - PEG MOUNT
- 6) TERMINAL PLATING:
  - "BLANK" - .000035/(.00090) MIN. TIN OVER .000020/(.00050) MIN. COPPER.
  - \*GS - .000030/(.00076) MIN. SELECT GOLD .000100/(.00254) MIN. SELECT MATTE TIN OVER .000050/(.00127) MIN. NICKEL OVERALL.
  - \*GS2 - .000015/(.00038) MIN. SELECT GOLD AND .000100/(.00254) MIN. SELECT MATTE TIN OVER .000050/(.00127) MIN. NICKEL OVERALL.
  - S - .000100/(.00254) MIN. TIN OVER .000050/(.00127) MIN. NICKEL.
- \*THE PRIMARY SHIPPING CARTON WILL BE LABELED "COMPLIANT TO RoHS DIRECTIVE 2002/95/EC AND ELV ANNEX II OF DIRECTIVE 2000/53/EC."
- \*CARTONS WITHOUT THIS LABEL MAY CONTAIN PRODUCT WITH TIN-LEAD PLATING.
- 7) PRODUCT SPECIFICATION AND PROCESSING PARAMETERS: SEE PS-5566-001
- 8) ANTI-SHINGLING RIB MAY OR MAY NOT APPEAR ON HOUSINGS.
- 9) CONNECTORS ARE NOT TO BE MATED OR UNMATED WHILE CIRCUITS ARE LIVE.
- 10) PARTS ARE NOT DESIGNED FOR CURRENT SHARING.



RECOMMENDED HOLE LAYOUT FOR .070/(1.78) MAX. THICK P. C. BOARD

VIEWED FROM COMPONENT SIDE

| CIRCUIT SIZE | DIM. "A"    | DIM. "B"    | DIM. "C"      |
|--------------|-------------|-------------|---------------|
| 2            | —           | .21 (5.4)   | .370 (9.40)   |
| 4            | .17 (4.2)   | .38 (9.6)   | .535 (13.60)  |
| 6            | .33 (8.4)   | .54 (13.8)  | .701 (17.80)  |
| 8            | .50 (12.6)  | .71 (18.0)  | .866 (22.00)  |
| 10           | .66 (16.8)  | .87 (22.2)  | 1.031 (26.20) |
| 12           | .83 (21.0)  | 1.04 (26.4) | 1.197 (30.40) |
| 14           | .99 (25.2)  | 1.20 (30.6) | 1.362 (34.60) |
| 16           | 1.16 (29.4) | 1.37 (34.8) | 1.528 (38.80) |
| 18           | 1.32 (33.6) | 1.54 (39.0) | 1.693 (43.00) |
| 20           | 1.49 (37.8) | 1.70 (43.2) | 1.858 (47.20) |
| 22           | 1.65 (42.0) | 1.87 (47.4) | 2.024 (51.40) |
| 24           | 1.82 (46.2) | 2.03 (51.6) | 2.189 (55.60) |

**LEGEND:**



|           |    |
|-----------|----|
| 4         | R2 |
| 3         | R2 |
| 2         | R2 |
| 1         | R2 |
| SHT. REV. |    |

| REVISED NOTES 8<br>EC NO: UCP2009-1336<br>DRAWN: JLOSTEMEIER 2008/11/24<br>CHKD: JBEL 2008/11/24<br>APPR: FSMITH 2008/11/24 | QUALITY SYMBOLS<br>▽=0<br>▽=0 | GENERAL TOLERANCES (UNLESS SPECIFIED)<br><table border="1"> <thead> <tr> <th></th> <th>mm</th> <th>INCH</th> </tr> </thead> <tbody> <tr> <td>4 PLACES ±</td> <td>---</td> <td>---</td> </tr> <tr> <td>3 PLACES ±</td> <td>---</td> <td>±.015</td> </tr> <tr> <td>2 PLACES ±</td> <td>0.38</td> <td>±.015</td> </tr> <tr> <td>1 PLACE ±</td> <td>0.38</td> <td>±---</td> </tr> </tbody> </table> |   | mm                                 | INCH                       | 4 PLACES ± | --- | --- | 3 PLACES ± | --- | ±.015 | 2 PLACES ± | 0.38 | ±.015 | 1 PLACE ± | 0.38 | ±--- | DIMENSION STYLE<br><b>IN/MM</b> | SCALE<br><b>1:1</b> | DESIGN UNITS<br><b>METRIC</b> | THIRD ANGLE PROJECTION |
|---|-------------------------------|---|---|------------------------------------|----------------------------|------------|-----|-----|------------|-----|-------|------------|------|-------|-----------|------|------|---------------------------------|---------------------|-------------------------------|------------------------|
|   |                               | mm  | INCH  |                                    |                            |            |     |     |            |     |       |            |      |       |           |      |      |                                 |                     |                               |                        |
|   | 4 PLACES ±                    | ---   | ---   |                                    |                            |            |     |     |            |     |       |            |      |       |           |      |      |                                 |                     |                               |                        |
|   | 3 PLACES ±                    | ---   | ±.015   |                                    |                            |            |     |     |            |     |       |            |      |       |           |      |      |                                 |                     |                               |                        |
| 2 PLACES ±  | 0.38                          | ±.015   |   |                                    |                            |            |     |     |            |     |       |            |      |       |           |      |      |                                 |                     |                               |                        |
| 1 PLACE ±   | 0.38                          | ±---  |   |                                    |                            |            |     |     |            |     |       |            |      |       |           |      |      |                                 |                     |                               |                        |
| MATERIAL NO.<br><b>SEE SHTS 2-4</b>   | DRAWN BY<br>RJF               | DATE<br>8/19/87   | TITLE<br><b>MINI-FIT JR. VERTICAL HEADER ASSEMBLIES WITH MOUNTING PEGS</b>  | MOLEX<br><b>MOLEX INCORPORATED</b> | SHEET NO.<br><b>1 OF 4</b> |            |     |     |            |     |       |            |      |       |           |      |      |                                 |                     |                               |                        |
| DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS  | APPROVED BY<br>RAS            | DATE<br>8/19/87   | DOCUMENT NO.<br><b>SDA-5566-N*2*-*</b>  |                                    |                            |            |     |     |            |     |       |            |      |       |           |      |      |                                 |                     |                               |                        |
|   |                               |   | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION |                                    |                            |            |     |     |            |     |       |            |      |       |           |      |      |                                 |                     |                               |                        |

| 13             | 12         | 11                      | 10 | 9              | 8              | 7                       | 6 | 5              | 4            | 3                       | 2 | 1              |                  |                         |  |
|----------------|------------|-------------------------|----|----------------|----------------|-------------------------|---|----------------|--------------|-------------------------|---|----------------|------------------|-------------------------|--|
| PLATING:       |            | 35 M.I. TIN             |    | PLATING:       |                | 35 M.I. TIN             |   | PLATING:       |              | 30 M.I. GOLD            |   | PLATING:       |                  | 30 M.I. GOLD            |  |
| DRAIN HOLES:   |            | WITHOUT DRAIN HOLES     |    | DRAIN HOLES:   |                | WITHOUT DRAIN HOLES     |   | DRAIN HOLES:   |              | WITHOUT DRAIN HOLES     |   | DRAIN HOLES:   |                  | WITHOUT DRAIN HOLES     |  |
| MTG. OPTION:   |            | WITH PEGS               |    | MTG. OPTION:   |                | WITH PEGS               |   | MTG. OPTION:   |              | WITH PEGS               |   | MTG. OPTION:   |                  | WITH PEGS               |  |
| HOUSING MAT'L: |            | NYLON 6/6 94V-2 NATURAL |    | HOUSING MAT'L: |                | NYLON 6/6 94V-0 NATURAL |   | HOUSING MAT'L: |              | NYLON 6/6 94V-2 NATURAL |   | HOUSING MAT'L: |                  | NYLON 6/6 94V-0 NATURAL |  |
| PACKAGING:     |            | TRAY                    |    | PACKAGING:     |                | TRAY                    |   | PACKAGING:     |              | TRAY                    |   | PACKAGING:     |                  | TRAY                    |  |
| PART NO.       | ENG NO.    | CKTS                    |    | PART NO.       | ENG NO.        | CKTS                    |   | PART NO.       | ENG NO.      | CKTS                    |   | PART NO.       | ENG NO.          | CKTS                    |  |
| 39-29-9023     | 5566 -02A2 | 2                       |    | 39-29-9027     | 5566 -02A2-210 | 2                       |   | 39-29-9025     | 5566 -02A2GS | 2                       |   | 39-29-9029     | 5566 -02A2GS-210 | 2                       |  |
| 39-29-9043     | 5566 -04A2 | 4                       |    | 39-29-9047     | 5566 -04A2-210 | 4                       |   | 39-29-9045     | 5566 -04A2GS | 4                       |   | 39-29-9049     | 5566 -04A2GS-210 | 4                       |  |
| 39-29-9063     | 5566 -06A2 | 6                       |    | 39-29-9067     | 5566 -06A2-210 | 6                       |   | 39-29-9065     | 5566 -06A2GS | 6                       |   | 39-29-9069     | 5566 -06A2GS-210 | 6                       |  |
| 39-29-9083     | 5566 -08A2 | 8                       |    | 39-29-9087     | 5566 -08A2-210 | 8                       |   | 39-29-9085     | 5566 -08A2GS | 8                       |   | 39-29-9089     | 5566 -08A2GS-210 | 8                       |  |
| 39-29-9103     | 5566 -10A2 | 10                      |    | 39-29-9107     | 5566 -10A2-210 | 10                      |   | 39-29-9105     | 5566 -10A2GS | 10                      |   | 39-29-9109     | 5566 -10A2GS-210 | 10                      |  |
| 39-29-9123     | 5566 -12A2 | 12                      |    | 39-29-9127     | 5566 -12A2-210 | 12                      |   | 39-29-9125     | 5566 -12A2GS | 12                      |   | 39-29-9129     | 5566 -12A2GS-210 | 12                      |  |
| 39-29-9143     | 5566 -14A2 | 14                      |    | 39-29-9147     | 5566 -14A2-210 | 14                      |   | 39-29-9145     | 5566 -14A2GS | 14                      |   | 39-29-9149     | 5566 -14A2GS-210 | 14                      |  |
| 39-29-9163     | 5566 -16A2 | 16                      |    | 39-29-9167     | 5566 -16A2-210 | 16                      |   | 39-29-9165     | 5566 -16A2GS | 16                      |   | 39-29-9169     | 5566 -16A2GS-210 | 16                      |  |
| 39-29-9183     | 5566 -18A2 | 18                      |    | 39-29-9187     | 5566 -18A2-210 | 18                      |   | 39-29-9185     | 5566 -18A2GS | 18                      |   | 39-29-9189     | 5566 -18A2GS-210 | 18                      |  |
| 39-29-9203     | 5566 -20A2 | 20                      |    | 39-29-9207     | 5566 -20A2-210 | 20                      |   | 39-29-9205     | 5566 -20A2GS | 20                      |   | 39-29-9209     | 5566 -20A2GS-210 | 20                      |  |
| 39-29-9223     | 5566 -22A2 | 22                      |    | 39-29-9227     | 5566 -22A2-210 | 22                      |   | 39-29-9225     | 5566 -22A2GS | 22                      |   | 39-29-9229     | 5566 -22A2GS-210 | 22                      |  |
| 39-29-9243     | 5566 -24A2 | 24                      |    | 39-29-9247     | 5566 -24A2-210 | 24                      |   | 39-29-9245     | 5566 -24A2GS | 24                      |   | 39-29-9249     | 5566 -24A2GS-210 | 24                      |  |
|                | -          |                         |    |                | -              |                         |   |                | -            |                         |   |                | -                |                         |  |
|                | -          |                         |    |                | -              |                         |   |                | -            |                         |   |                | -                |                         |  |

| 13             | 12         | 11                      | 10 | 9              | 8              | 7                       | 6 | 5              | 4            | 3                       | 2 | 1              |                  |                         |  |
|----------------|------------|-------------------------|----|----------------|----------------|-------------------------|---|----------------|--------------|-------------------------|---|----------------|------------------|-------------------------|--|
| PLATING:       |            | 35 M.I. TIN             |    | PLATING:       |                | 35 M.I. TIN             |   | PLATING:       |              | 30 M.I. GOLD            |   | PLATING:       |                  | 30 M.I. GOLD            |  |
| DRAIN HOLES:   |            | WITH DRAIN HOLES        |    | DRAIN HOLES:   |                | WITH DRAIN HOLES        |   | DRAIN HOLES:   |              | WITH DRAIN HOLES        |   | DRAIN HOLES:   |                  | WITH DRAIN HOLES        |  |
| MTG. OPTION:   |            | WITH PEGS               |    | MTG. OPTION:   |                | WITH PEGS               |   | MTG. OPTION:   |              | WITH PEGS               |   | MTG. OPTION:   |                  | WITH PEGS               |  |
| HOUSING MAT'L: |            | NYLON 6/6 94V-2 NATURAL |    | HOUSING MAT'L: |                | NYLON 6/6 94V-0 NATURAL |   | HOUSING MAT'L: |              | NYLON 6/6 94V-2 NATURAL |   | HOUSING MAT'L: |                  | NYLON 6/6 94V-0 NATURAL |  |
| PACKAGING:     |            | TRAY                    |    | PACKAGING:     |                | TRAY                    |   | PACKAGING:     |              | TRAY                    |   | PACKAGING:     |                  | TRAY                    |  |
| PART NO.       | ENG NO.    | CKTS                    |    | PART NO.       | ENG NO.        | CKTS                    |   | PART NO.       | ENG NO.      | CKTS                    |   | PART NO.       | ENG NO.          | CKTS                    |  |
| 39-29-9022     | 5566 -02B2 | 2                       |    | 39-29-9026     | 5566 -02B2-210 | 2                       |   | 39-29-9024     | 5566 -02B2GS | 2                       |   | 39-28-9028     | 5566 -02B2GS-210 | 2                       |  |
| 39-29-9042     | 5566 -04B2 | 4                       |    | 39-29-9046     | 5566 -04B2-210 | 4                       |   | 39-29-9044     | 5566 -04B2GS | 4                       |   | 39-28-9048     | 5566 -04B2GS-210 | 4                       |  |
| 39-29-9062     | 5566 -06B2 | 6                       |    | 39-29-9066     | 5566 -06B2-210 | 6                       |   | 39-29-9064     | 5566 -06B2GS | 6                       |   | 39-28-9068     | 5566 -06B2GS-210 | 6                       |  |
| 39-29-9082     | 5566 -08B2 | 8                       |    | 39-29-9086     | 5566 -08B2-210 | 8                       |   | 39-29-9084     | 5566 -08B2GS | 8                       |   | 39-28-9088     | 5566 -08B2GS-210 | 8                       |  |
| 39-29-9102     | 5566 -10B2 | 10                      |    | 39-29-9106     | 5566 -10B2-210 | 10                      |   | 39-29-9104     | 5566 -10B2GS | 10                      |   | 39-28-9108     | 5566 -10B2GS-210 | 10                      |  |
| 39-29-9122     | 5566 -12B2 | 12                      |    | 39-29-9126     | 5566 -12B2-210 | 12                      |   | 39-29-9124     | 5566 -12B2GS | 12                      |   | 39-28-9128     | 5566 -12B2GS-210 | 12                      |  |
| 39-29-9142     | 5566 -14B2 | 14                      |    | 39-29-9146     | 5566 -14B2-210 | 14                      |   | 39-29-9144     | 5566 -14B2GS | 14                      |   | 39-28-9148     | 5566 -14B2GS-210 | 14                      |  |
| 39-29-9162     | 5566 -16B2 | 16                      |    | 39-29-9166     | 5566 -16B2-210 | 16                      |   | 39-29-9164     | 5566 -16B2GS | 16                      |   | 39-28-9168     | 5566 -16B2GS-210 | 16                      |  |
| 39-29-9182     | 5566 -18B2 | 18                      |    | 39-29-9186     | 5566 -18B2-210 | 18                      |   | 39-29-9184     | 5566 -18B2GS | 18                      |   | 39-28-9188     | 5566 -18B2GS-210 | 18                      |  |
| 39-29-9202     | 5566 -20B2 | 20                      |    | 39-29-9206     | 5566 -20B2-210 | 20                      |   | 39-29-9204     | 5566 -20B2GS | 20                      |   | 39-28-9208     | 5566 -20B2GS-210 | 20                      |  |
| 39-29-9222     | 5566 -22B2 | 22                      |    | 39-29-9226     | 5566 -22B2-210 | 22                      |   | 39-29-9224     | 5566 -22B2GS | 22                      |   | 39-28-9228     | 5566 -22B2GS-210 | 22                      |  |
| 39-29-9242     | 5566 -24B2 | 24                      |    | 39-29-9246     | 5566 -24B2-210 | 24                      |   | 39-29-9244     | 5566 -24B2GS | 24                      |   | 39-28-9248     | 5566 -24B2GS-210 | 24                      |  |
|                | -          |                         |    |                | -              |                         |   |                | -            |                         |   |                | -                |                         |  |
|                | -          |                         |    |                | -              |                         |   |                | -            |                         |   |                | -                |                         |  |

| <b>SEE SHEET 1</b><br>EC NO: UCP2009-1336<br>DRWN:KLOSTEMEIER 2008/11/24<br>CHKD:JBELL 2008/11/24<br>APPR:FSMITH 2008/11/24 | DESCRIPTION<br>REV | QUALITY SYMBOLS<br> = 0<br> = 0 | GENERAL TOLERANCES (UNLESS SPECIFIED)<br><table border="1"> <tr> <th></th> <th>mm</th> <th>INCH</th> </tr> <tr> <td>4 PLACES</td> <td>± .005</td> <td>± .0005</td> </tr> <tr> <td>3 PLACES</td> <td>± .015</td> <td>± .0015</td> </tr> <tr> <td>2 PLACES</td> <td>± .038</td> <td>± .015</td> </tr> <tr> <td>1 PLACE</td> <td>± .38</td> <td>± .015</td> </tr> </table> |   | mm | INCH | 4 PLACES | ± .005                                 | ± .0005               | 3 PLACES | ± .015 | ± .0015 | 2 PLACES | ± .038 | ± .015 | 1 PLACE | ± .38 | ± .015 | DIMENSION STYLE<br><b>IN/MM</b> | SCALE<br><b>1:1</b> | DESIGN UNITS<br><b>METRIC</b> |  <b>THIRD ANGLE PROJECTION</b> |
|---|--------------------|---|---|---|----|------|----------|--|-----------------------|----------|--------|---------|----------|--------|--------|---------|-------|--------|---------------------------------|---------------------|-------------------------------|---|
|   |                    |   | mm  | INCH  |    |      |          |  |                       |          |        |         |          |        |        |         |       |        |                                 |                     |                               |   |
|   |                    | 4 PLACES  | ± .005  | ± .0005   |    |      |          |  |                       |          |        |         |          |        |        |         |       |        |                                 |                     |                               |   |
|   |                    | 3 PLACES  | ± .015  | ± .0015   |    |      |          |  |                       |          |        |         |          |        |        |         |       |        |                                 |                     |                               |   |
| 2 PLACES  | ± .038             | ± .015  |   |   |    |      |          |  |                       |          |        |         |          |        |        |         |       |        |                                 |                     |                               |   |
| 1 PLACE   | ± .38              | ± .015  |   |   |    |      |          |  |                       |          |        |         |          |        |        |         |       |        |                                 |                     |                               |   |
|   |                    | DRAWN BY<br>RJF<br>DATE<br>8/19/87  | CHECKED BY<br>GT<br>DATE<br>8/19/87   | TITLE<br><b>MINI-FIT JR. VERT HEADER ASSEMBLIES WITH MOUNTING PEGS</b>  |    |      |          |  |                       |          |        |         |          |        |        |         |       |        |                                 |                     |                               |   |
|   |                    | APPROVED BY<br>RAS<br>DATE<br>8/19/87   | MATERIAL NO.<br><b>SEE CHART</b>  |   |    |      |          | DOCUMENT NO.<br><b>SDA-5566-N*2*-*</b> | SHEET NO.<br><b>2</b> |          |        |         |          |        |        |         |       |        |                                 |                     |                               |   |
|   |                    | DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS  |   | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION |    |      |          |  |                       |          |        |         |          |        |        |         |       |        |                                 |                     |                               |   |