

DWDM Multirate SFP Transceivers

SFP27DWLR



Overview

The DWDM Multirate SFP Transceivers from MRV provide flexible DWDM solutions in a compact package about six times smaller than the standard hot-plug MSA transceiver. Nearly any equipment with SFP ports can easily use CWDM wavelengths or the narrower DWDM channels with 100 GHz spacing.

The traditional CWDM advantages include cost, simplicity, power consumption, and equipment density. The MRV DWDM multirate SFPs maximize scalability in both channel count and distance. C-band DWDM systems currently use 44 channels that can easily reach across metro networks with inexpensive erbium-doped fiber amplifiers (EDFA). These DWDM SFPs combine the best of all these features.

Features

- 100 GHz ITU DWDM grid
 - C-band standard
 - L-band by request
- 80 km, 120 km, and 200 km long reach
- DWDM SFP MSA compliance
- Cold start up wavelength compliance
- Low power dissipation (<1.3W maximum)
- -5° C to 70° C operating case temperature
- 100 Mbps to 2.7 Gbps multirate functionality
- SONET OC-48 /SDH STM-16 compliance
- Standard SFP cage interface
- Diagnostic performance monitoring of transmit power, receive power, laser bias, module temperature, laser temperature, APD bias voltage, and TEC current
- -28 dBm at OC-48 APD-based receiver sensitivity

General Operating

Parameter	Symbol	Min.	Typical	Max.	Unit
Supply Voltage	V_{cc}	3.135	3.3	3.465	V
Total Current (BOL)	I_{cc}	-	-	375	mA
Power Supply Noise Rejection ^a	PSR	100	-	-	mV _{p-p}
Operating Temperature (case)	T_{op}	-5	-	70	°C
Storage Temperature	T_{st}	-40	-	85	°C
Data Rate Multirate	MR	100	-	2700	Mbps

a) 20 Hz to 155 MHz

Datasheet

Transmitter Specifications (Optical)

Parameter	Symbol	Min	Typical	Max	Unit
Optical Power	P_{OP}	0	2	4	dBm
Average Launch Power (Tx: Off)	P_{Off}	-	-	-30	dBm
Extinction Ratio	ER	8.2	-	-	dB
Eye Mask	IEEE 802.3z, SONET/SDH compliant				
Optical Jitter Generation	$J_{gen}(pk-pk)$	-	-	0.07	UI
Optical Rise Time ^b	t_r	-	-	160	ps
Optical Fall Time ^b	t_f	-	-	160	ps
Channel Spacing	Δf	-	100	-	GHz
Deviation From Central Frequency, EOL	-	-	-	± 12	GHz
Spectral Width (20 dB)	$\Delta \lambda$	-	-	0.3	nm
Side Mode Suppression Ratio	SMSR	30	-	-	dB
Dispersion Penalty at specified distance ^c	dp	-	-	<2	dB
Relative Intensity Noise	RIN	-	-	-135	dB/Hz
Reflection Tolerance ^d	rp	-24	-	-	dB

b) 20%-80% values

c) Measured at BER of 10^{-12} , PRBS of $2^{23}-1$, at eye center, OC-48.

d) 2 dB degradation of receiver sensitivity

Transmitter Specifications (Electrical)

Parameter	Symbol	Min	Typical	Max	Unit
Input Differential Impedance	R_{in}	80	100	120	Ω
PECL Single-Ended Data Input Swing	$V_{in,p-p}$	250	-	1200	mV
TxFault_Fault	V_{fault}	2	-	V_{cc}	V
TxFault_Normal	V_{normal}	V_{ee}	-	$V_{ee}+0.5$	V
TxDisable_Disable	V_d	2	-	V_{cc}	V
TxDisable_Enable	V_{en}	V_{ee}	-	$V_{ee}+0.8$	V

Receiver Specifications

Parameter	Symbol	Min	Typical	Max	Unit
Receive Power Low ^e	$R_{sens,low}$	-	-30	-28	dBm
Receive Power at Specified Distance and 20 dB OSNR ^e	$R_{sens,OSNR}$	-	-	-24	dBm
Receive Power High	$R_{sens,high}$	-6	-	-	dBm
Damage Threshold for Receiver	$P_{in,damage}$	4	-	-	dBm
Wavelength	λ	1528	-	1564	nm
Maximum Reflectance of Receiver	RX_r	-	-	-27	dB
LOS Assert	-	-40	-	-	dBm
LOS De-assert	-	-	-	-28	dBm
LOS Hysteresis	-	0.5	-	-	dB

e) at 10^{-12} BER, PRS $2^{23}-1$, OC-48

Datasheet

Electrical Output

Parameter	Symbol	Min	Typical	Max	Unit
Single-Ended Data Output	$V_{out, p-p}$	185	-	800	mV
Data Output Rise Time	t_r	-	-	175	ps
Data Output Fall Time	t_f	-	-	175	ps

Timing and Electrical

Parameter	Symbol	Min	Typical	Max	Unit
Tx Disable Negate Time	t_{on}	-	-	20	ms
Tx Disable Assert Time	t_{off}	-	-	20	ms
Time to Initialize, after Reset of Tx_Fault/INT in Normal Operation	t_{init}	-	-	300	ms
Start-up Time	$t_{startup}$	-	-	90	secs
Tx Fault/INT Assert Time	t_{fault}	-	-	50	ms
Tx Disable to Reset	t_{reset}	10	-	-	μ s
LOS Assert Time	$t_{loss_{on}}$	-	-	100	μ s
LOS De-assert Time	$t_{loss_{off}}$	-	-	100	μ s
Serial ID Clock Rate	f_{serial_clock}	-	-	100	KHz
RX_LOS Voltage (High)	-	2	-	-	V
RX_LOS Voltage (Low)	-	-	-	0.8	V
LOS Output Voltage-Fault	$V_{LOS\ fault}$	2	-	V_{CC}	V
LOS Output Voltage-Normal	$V_{LOS\ normal}$	V_{EE}	-	$V_{EE}+0.55$	V
MOD_DEF (0:2)-High	V_H	2	-	V_{CC}	V
MOD_DEF (0:2)-Low	V_L	V_{EE}	-	$V_{EE}+0.5$	V

Diagnostics


Parameter	Range	Accuracy	Unit
Temperature	-40 to 102	± 3	$^{\circ}$ C
Voltage	0 to V_{CC}	0.1	V
Bias Current	0 to 120	5	mA
TX Power	0 to 4	± 2	dBm
RX Power	-32 to -9	± 2	dBm
TEC Current	-1200 to 1200	± 60	mA
TEC Temperature ^f	20 to 70	± 0.25	$^{\circ}$ C

f) Relative accuracy. Absolute accuracy is +/-3°C

Datasheet

Pin	Function	Notes
1	V _{ee} T	TX Ground
2	TX_FAULT/INT	Open Collector
3	TX_DISABLE	Internally Pulled High
4	MOD_DEF2	Serial Data Input
5	MOD_DEF1	Serial Clock Input
6	MOD_DEF0	Internally Grounded
7	NC	Not Connected
8	LOS	Open Collector
9	V _{ee} R	RX Ground
10	V _{ee} R	RX Ground
11	V _{ee} R	RX Ground
12	RXD-	RX Data Negative
13	RXD+	RX Data Positive
14	V _{ee} R	RX Ground
15	V _{cc} R	RX Power
16	V _{cc} T	TX Power
17	V _{ee} T	TX Ground
18	TXD+	TX Data Positive
19	TXD-	TX Data Negative
20	V _{ee} T	TX Ground

Outline Drawing





Datasheet

Ordering Information

Model	Description	Data Rate (Mbps)	Dispersion Penalty(dB)	Bail Latch Color	Distance Range (km)
SFP27DWLR08-xx*	SFP Multirate DWDM Transceiver	100 - 2700 Mbps	<2dB (@ 1600 ps/nm)	Black	40 - 80
SFP27DWLR12-xx*	SFP Multirate DWDM Transceiver	100 - 2700 Mbps	<2dB (@ 2400 ps/nm)	Black	40 - 120
SFP27DWLR20-xx*	SFP Multirate DWDM Transceiver	100 - 2700 Mbps	<2dB (@ 4000 ps/nm)	Black	40 - 200**

* See tables below for ITU channel "xx" values. L-band wavelengths are available by special order.

** EDFA is required for full distance reach

C-Band Channel Guide

ITU Channel (xx)	Frequency (THz)	Wavelength (nm)	ITU Channel (xx)	Frequency (THz)	Wavelength (nm)
17	191.7	1563.863	39	193.9	1546.119
18	191.8	1563.047	40	194.0	1545.322
19	191.9	1562.233	41	194.1	1544.526
20	192.0	1561.419	42	194.2	1543.730
21	192.1	1560.606	43	194.3	1542.936
22	192.2	1559.794	44	194.4	1542.142
23	192.3	1558.983	45	194.5	1541.349
24	192.4	1558.173	46	194.6	1540.557
25	192.5	1557.363	47	194.7	1539.766
26	192.6	1556.555	48	194.8	1538.976
27	192.7	1555.747	49	194.9	1538.186
28	192.8	1554.940	50	195.0	1537.397
29	192.9	1554.134	51	195.1	1536.609
30	193.0	1553.329	52	195.2	1535.822
31	193.1	1552.524	53	195.3	1535.036
32	193.2	1551.721	54	195.4	1534.250
33	193.3	1550.918	55	195.5	1533.465
34	193.4	1550.116	56	195.6	1532.681
35	193.5	1549.315	57	195.7	1531.898
36	193.6	1548.515	58	195.8	1531.116
37	193.7	1547.715	59	195.9	1530.334
38	193.8	1546.917	60	196.0	1529.553

MRV has more than 50 offices throughout the world. Addresses, phone numbers and fax numbers are listed at www.mrv.com.

Please e-mail us at sales@mrv.com or call us for assistance.

MRV Los Angeles
20415 Nordhoff St.
Chatsworth, CA 91311
800-338-5316
818-773-0900

MRV Boston
295 Foster St.
Littleton, MA 01460
800-338-5316
978-952-4700

MRV International
Business Park Moerfelden
Waldeckerstrasse 13
64546 Moerfelden-Walldorf
Germany
Tel. (49) 6105/2070
Fax (49) 6105/207-100

All statements, technical information and recommendations related to the products herein are based upon information believed to be reliable or accurate. However, the accuracy or completeness thereof is not guaranteed, and no responsibility is assumed for any inaccuracies. Please contact MRV Communications for more information. MRV Communications and the MRV Communications logo are trademarks of MRV Communications, Inc. Other trademarks are the property of their respective holders.