

RoHS Compliant Product
A suffix of "-C" specifies halogen & lead-free


FEATURE

- Low C_{ob} , $C_{ob}=2.0pF$
- Complements of the 2SA1037

CLASSIFICATION OF h_{FE}

Product-Rank	2SC2412-Q	2SC2412-R	2SC2412-S
Range	120~270	180~390	270~560
Marking Code	BQ	BR	BS


SOT-23



PACKAGE INFORMATION

Package	MPQ	LeaderSize
SOT-23	3K	7' inch

REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	2.80	3.04	G	0.09	0.18
B	2.10	2.55	H	0.45	0.60
C	1.20	1.40	J	0.08	0.177
D	0.89	1.15	K	0.6 REF.	
E	1.78	2.04	L	0.89	1.02
F	0.30	0.50			



ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ C$ unless otherwise specified)

Parameter	Symbol	Ratings	Unit
Collector to Base Voltage	V_{CBO}	60	V
Collector to Emitter Voltage	V_{CEO}	50	V
Emitter to Base Voltage	V_{EBO}	7	V
Collector Current - Continuous	I_C	150	mA
Collector Power Dissipation	P_C	200	mW
Junction, Storage Temperature	T_J, T_{STG}	150, -55 ~ 150	$^\circ C$

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ C$ unless otherwise specified)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Collector to Base Breakdown Voltage	$V_{(BR)CBO}$	60	-	-	V	$I_C=50\mu A, I_E=0$
Collector to Emitter Breakdown Voltage	$V_{(BR)CEO}$	50	-	-	V	$I_C=1mA, I_B=0$
Emitter to Base Breakdown Voltage	$V_{(BR)EBO}$	7	-	-	V	$I_E=50\mu A, I_C=0$
Collector Cut-Off Current	I_{CBO}	-	-	0.1	μA	$V_{CB}=60V, I_E=0$
Emitter Cut-Off Current	I_{EBO}	-	-	0.1	μA	$V_{EB}=7V, I_C=0$
DC Current Gain	h_{FE}	120	-	560		$V_{CE}=6V, I_C=1mA$
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	-	-	0.4	V	$I_C=50mA, I_B=5mA$
Transition Frequency	f_T	-	160	-	MHz	$V_{CE}=12V, I_C=-2mA, f=100MHz$
Collector Output Capacitance	C_{ob}	-	2.0	3.5	pF	$V_{CB}=12V, I_E=0, f=1MHz$

CHARACTERISTIC CURVES




Fig.1 Grounded emitter propagation characteristics




Fig.2 Grounded emitter output characteristics (I)




Fig.3 Grounded emitter output characteristics (II)




Fig.4 DC current gain vs. collector current (I)




Fig.5 DC current gain vs. collector current (II)




Fig. 6 Collector-emitter saturation voltage vs. collector current




Fig.7 Collector-emitter saturation voltage vs. collector current (I)




Fig.8 Collector-emitter saturation voltage vs. collector current (II)




Fig.9 Gain bandwidth product vs. emitter current

CHARACTERISTIC CURVES




Fig.10 Collector output capacitance vs. collector-base voltage
Emitter input capacitance vs. emitter-base voltage




Fig.11 Base-collector time constant vs. emitter current