



tolerances according to DIN ISO 2768 m

Magnetic properties	Conditions	Min	Typ	Max	Unit
Pull-In excitation (Reference value)	Reed switch unmodified measured in coil-"define operation"	50		100	AT
Test-Coil	Reed switch unmodified	KMS-05			

Contact data 76/2	Conditions	Min	Typ	Max	Unit
Contact-No.		76/2			
Contact-form		A			
Contact-material		Ruthenium			
Contact-rating	Any DC combination of V & A not to exceed their individual max.'s			120	W
Switching voltage	DC or Peak AC			300	V
Switching current	DC or Peak AC			3	A
Carry current	DC or Peak AC			5	A
Contact resistance static	Measured with 40% overdrive Start Value			150	mOhm
Contact resistance dynamic	Maximum value 1,5 ms after excitation Start Value			200	mOhm
Insulation resistance	RH <45 %, 100 V test voltage	10			GOhm
Breakdown voltage	according to IEC 255-5	800			VDC
Operate time incl. bounce	measured with 40% overdrive			5	ms
Release time	measured with no coil excitation			0,4	ms
Capacity	@ 10 kHz across open switch		0,2		pF

Contact dimensions	C	Conditions	Min	Typ	Max	Unit
Overall length		Tolerance according to drawing		83,4		mm
Glass body length		Tolerance according to drawing		50,8		mm

Environmental data	Conditions	Min	Typ	Max	Unit
Shock	1/2 sine wave duration 11ms			50	g
Vibration	from 10 - 2000 Hz			20	g
Operating temperature		-40		200	°C
Storage temperature		-55		200	°C
Soldering temperature	wave soldering max. 5 sec.			260	°C