


## Plasma Panel Displays

### Linear Bar Graph



PBG-C7005



PBG-C7008

#### FEATURES

- Extra long columns for extended viewing distances
- At normal viewing distances glow blends into continuous, but precisely controlled bar length
- Unique scanning technique minimizes the number of drivers required
- Available with attached terminals

#### ENVIRONMENTAL SPECIFICATIONS

**Altitude:** 0 to 70,000 feet.

**Operating Temperature:** 0°C to + 55°C.

**Storage Temperature:** - 55°C to + 85°C.

**Relative Humidity (No condensation):** 85% maximum.

**Vibration:** .018 inches DA, 10 to 50 Hz, 2G, 50 to 2000 Hz.

**Shock:** 50G, 1/2 sine wave, 11 mS duration.

#### OPTICAL SPECIFICATIONS

	PBG-C7005	PBG-C7008
<b>Elements</b>	201	201
<b>Resolution</b>	1/2%	1/2%
<b>Segment Length</b>	.250	.120
<b>Segment Width</b>	.020	.020
<b>Segment Spacing</b>	.050	.0394
<b>Drivers Required</b>	7	8
<b>Luminance</b>	30 fl	30 fl
<b>Viewing Angle</b>	120°	120°
<b>Color</b>	Neon Orange	Neon Orange

#### ELECTRICAL SPECIFICATIONS

OPERATING PARAMETERS	PBG-C7005				PBG-C7008			
	MINIMUM	MAXIMUM	RECOMMENDED	UNITS	MINIMUM	MAXIMUM	RECOMMENDED	UNITS
<b>Anode Supply Voltage</b>	235	265	250	V	235	265	250	V
<b>Cathode Off Bias Voltage</b>	68	76	72	V	68	76	72	V
<b>Anode Off Bias Voltage</b>	80	120	100	V	80	120	100	V
<b>Anode Sustaining Voltage (Typical)</b>	—	—	150	V	—	—	150	V
<b>Refresh Rate</b>	—	—	66	Hz	—	—	65	Hz
<b>Keep Alive Anode Resistor</b>	—	—	1M	Ω	—	—	1M	Ω
<b>Keep Alive Cathode Resistor</b>	—	—	1M	Ω	—	—	1M	Ω
<b>Keep Alive Current (Typical)</b>	—	—	50	μA	—	—	50	μA
<b>Display Anode Resistor</b>	—	—	6k	Ω	—	—	15k	Ω
<b>Display Peak Anode Current</b>	10	20	15	mA	6	10	8	mA
<b>Scan Time per Cathode</b>	70	150	75	μS	70	150	75	μS
<b>Applied Reset Pulse Width</b>	70	150	75	μS	70	150	75	μS
<b>Character Anode Resistor</b>	—	—	—	—	—	—	6.8k	Ω
<b>Character Anode Current</b>	—	—	—	—	11	15	13	mA



## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.