

# Surface Mount Directional Coupler

## TCD-9-1W+ TCD-9-1W

50Ω

5 to 2000 MHz



### Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C

### Pin Connections

INPUT	3
OUTPUT	4
COUPLED	1
GROUND	2
50Ω TERM EXTERNAL	6
NOT USED	5

### Features

- wideband, 5 to 2000 MHz
- low mainline loss, 1.2 dB typ. (5-1000 MHz)
- aqueous washable
- leads for excellent solderability
- protected by US Patent 6,140,887

### Applications

- GPS
- cellular
- satellite distribution
- cable tv

CASE STYLE: DB714  
PRICE: \$1.49 ea. QTY (25)

**+ RoHS compliant in accordance with EU Directive (2002/95/EC)**


The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.

### Directional Coupler Electrical Specifications


FREQ. RANGE (MHz)	COUPLING (dB)		MAINLINE LOSS <sup>1</sup> (dB)						DIRECTIVITY (dB)			VSWR (:1)	POWER INPUT, W				
	Nom.	Flatness	L		M		U		L		M		U	Typ.	L	MU	
			Typ.	Max.	Typ.	Max.	Typ.	Max.	Typ.	Min.	Typ.		Min.		Typ.	Max.	Max.
5-1000	8.9±0.5	±0.6	1.2	2.1	1.2	1.8	1.5	2.1	21	17	17	10	13	—	1.30	0.5	1.0
1000-2000	8.9±0.5	±0.6	—	—	2.5	—	—	—	—	—	10	—	—	—	1.60	—	1.0

L = low range [ $f_L$  to  $10 f_L$ ] M = mid range [ $10 f_L$  to  $f_U/2$ ] U = upper range [ $f_U/2$  to  $f_U$ ]  
1. Mainline loss includes theoretical power loss at coupled port.

### Outline Drawing



### PCB Land Pattern




Suggested Layout.  
Tolerance to be within ±.002

### Outline Dimensions (inch/mm)

A	B	C	D	E	F
.160	.150	.160	.050	.040	.025
4.06	3.81	4.06	1.27	1.02	0.64
G	H	J	K		wt
.028	.065	.190	.030		grams
0.71	1.65	4.83	0.76		0.15




### Demo Board MCL P/N: TB-71 Suggested PCB Layout (PL-009)




- NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS 0.050" ± 0.002". COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.  
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.  
■ DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)  
■ DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

### Typical Performance Data

Frequency (MHz)	Mainline Loss (dB) In-Out	Coupling (dB) In-Cpl	Directivity (dB)	Return Loss (dB)		
				In	Out	Cpl
5.00	1.11	8.96	21.65	19.14	27.81	18.92
200.00	1.14	8.97	20.18	20.84	30.26	20.66
600.00	1.26	8.67	15.41	21.16	22.87	20.18
800.00	1.38	8.61	13.30	20.11	22.87	18.90
1000.00	1.54	8.48	11.72	18.37	22.07	17.30
1200.00	1.74	8.57	10.31	16.42	21.82	15.67
1400.00	2.04	8.57	9.19	14.49	22.16	14.29
1600.00	2.32	8.61	8.42	12.72	21.46	12.97
1800.00	2.72	8.75	7.63	11.17	23.19	11.93
2000.00	3.07	8.76	7.28	9.96	22.33	10.99



### Electrical Schematic



\* ELECTRICAL SCHEMATIC IS FOR DIRECTIONAL COUPLER WITH INTERNAL TRANSFORMER(S) AND EXTERNAL TERMINATION.

**Mini-Circuits**  
ISO 9001 ISO 14001 AS 9100 CERTIFIED

[minicircuits.com](http://minicircuits.com)

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site



The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: [www.minicircuits.com](http://www.minicircuits.com)

IF/RF MICROWAVE COMPONENTS

REV. F  
M119986  
ED-8571/1  
TCD-9-1W  
WZ/TD/CP/AM  
081113