

HD74AC107/HD74ACT107

Dual JK Flip-Flop (with Separate Clear and Clock)

HITACHI

ADE-205-363 (Z)
1st. Edition
Sep. 2000


Description

The HD74AC107/HD74ACT107 dual JK master/slave flip-flops have a separate clock for each flip-flop. Inputs to the master section are controlled by the clock pulse. The clock pulse also regulates the state of the coupling transistors which connect the master and slave sections. The sequence of operation is as follows: 1) isolate slave from master; 2) enter information from J and K inputs to master; 3) disable J and K inputs; 4) transfer information from master to slave.


Features

- Outputs Source/Sink 24 mA
- HD74ACT107 has TTL-Compatible Inputs

Pin Arrangement



Logic Symbol



Pin Names


- J₁, J₂, K₁, K₂
- CP₁, CP₂
- CD₁, CD₂
- Q₁, Q₂, Q₁[¯], Q₂[¯]
- Data Inputs
- Clock Pulse Inputs (Active Falling Edge)
- Direct Clear Inputs (Active Low)
- Outputs

Truth Table

Inputs		Outputs
@ t _n		@ t _{n+1}
J	K	Q
L	L	Qn
L	H	L
H	L	H
H	H	Qn [¯]

- H : High Voltage Level
- L : Low Voltage Level
- t_n : Bit time before clock pulse.
- t_{n+1} : Bit time after clock pulse.

Logic Diagram



DC Characteristics (unless otherwise specified)

Item	Symbol	Max	Unit	Condition
Maximum quiescent supply current	I_{CC}	40	μA	$V_{IN} = V_{CC}$ or ground, $V_{CC} = 5.5 V$, $T_a = \text{Worst case}$
Maximum quiescent supply current	I_{CC}	4.0	μA	$V_{IN} = V_{CC}$ or ground, $V_{CC} = 5.5 V$, $T_a = 25^{\circ}C$
Maximum additional I_{CC} /input (HD74ACT107)	I_{CCT}	1.5	mA	$V_{IN} = V_{CC} - 2.1 V$, $V_{CC} = 5.5 V$ $T_a = \text{Worst case}$

HD74AC107/HD74ACT107

AC Characteristics: HD74AC107

Item	Symbol	V _{CC} (V)*1	Ta = +25°C C _L = 50 pF			Ta = -40°C to +85°C C _L = 50 pF		Unit
			Min	Typ	Max	Min	Max	
Maximum clock frequency	f _{max}	3.3	125	—	—	100	—	MHz
		5.0	150	—	—	125	—	
Propagation delay C _p to Q or Q̄	t _{PLH}	3.3	1.0	9.5	13.0	1.0	14.0	ns
		5.0	1.0	7.5	10.0	1.0	11.0	
Propagation delay C _p to Q or Q̄	t _{PHL}	3.3	1.0	10.0	13.5	1.0	14.5	ns
		5.0	1.0	8.0	10.5	1.0	11.5	
Propagation delay C _D to Q̄	t _{PLH}	3.3	1.0	9.5	13.0	1.0	14.0	ns
		5.0	1.0	7.5	10.0	1.0	11.0	
Propagation delay C _D to Q̄	t _{PHL}	3.3	1.0	9.5	13.0	1.0	14.0	ns
		5.0	1.0	7.5	10.0	1.0	11.0	

Note: 1. Voltage Range 3.3 is 3.3 V ± 0.3 V
Voltage Range 5.0 is 5.0 V ± 0.5 V

Operating Requirements: HD74AC107

Item	Symbol	V _{CC} (V)*1	Ta = +25°C C _L = 50 pF		Ta = -40°C to +85°C C _L = 50 pF		Unit
			Typ	Guaranteed Minimum			
Setup time J or k to C _p	t _{su}	3.3	3.0	5.5	6.0		ns
		5.0	2.0	4.0	4.5		
Hold time C _p to J or k	t _h	3.3	-1.5	0.0	0.0		
		5.0	-0.5	0.0	0.0		
Pulse width C _p or C _D	t _w	3.3	2.0	5.5	7.0		
		5.0	2.0	4.5	5.0		
Recovery time C _D to C _p	t _{rec}	3.3	1.5	3.0	3.0		
		5.0	1.0	3.0	3.0		

Note: 1. Voltage Range 3.3 is 3.3 V ± 0.3 V
Voltage Range 5.0 is 5.0 V ± 0.5 V

AC Characteristics: HD74ACT107

Item	Symbol	$V_{CC} (V)^{*1}$	Ta = +25°C C _L = 50 pF			Ta = -40°C to +85°C C _L = 50 pF		Unit
			Min	Typ	Max	Min	Max	
Maximum clock frequency	f _{max}	5.0	100	—	—	80	—	MHz
Propagation delay C _p to Q or Q	t _{PLH}	5.0	1.0	9.5	12.5	1.0	13.5	ns
Propagation delay C _p to Q or Q	t _{PHL}	5.0	1.0	10.5	13.0	1.0	14.0	
Propagation delay C _D to Q	t _{PLH}	5.0	1.0	8.5	11.0	1.0	12.0	
Propagation delay C _D to Q	t _{PHL}	5.0	1.0	8.5	11.0	1.0	12.0	

Note: 1. Voltage Range 5.0 is 5.0 V ± 0.5 V

Operating Requirements: HD74ACT107

Item	Symbol	$V_{CC} (V)^{*1}$	Ta = +25°C C _L = 50 pF		Ta = -40°C to +85°C C _L = 50 pF	Unit
			Typ	Guaranteed Minimum		
Setup time J or k to C _p	t _{su}	5.0	2.5	7.0	8.0	ns
Hold time C _p to J or k	t _h	5.0	0.0	1.5	1.5	
Pulse width C _p or C _D	t _w	5.0	4.5	7.0	8.0	
Recovery time C _D to C _p	t _{rec}	5.0	—	3.0	3.0	


Note: 1. Voltage Range 5.0 is 5.0 V ± 0.5 V

Capacitance

Item	Symbol	Typ	Unit	Condition
Input capacitance	C _{IN}	4.5	pF	V _{CC} = 5.5 V
Power dissipation capacitance	C _{PD}	35.0	pF	V _{CC} = 5.0 V


Package Dimensions

Unit: mm



Hitachi Code	DP-14
JEDEC	Conforms
EIAJ	Conforms
Mass (reference value)	0.97 g



Unit: mm



*Dimension including the plating thickness
Base material dimension

Hitachi Code	FP-14DA
JEDEC	—
EIAJ	Conforms
Mass (reference value)	0.23 g

Unit: mm



*Pd plating

Hitachi Code	FP-14DN
JEDEC	Conforms
EIAJ	Conforms
Mass (reference value)	0.13 g

Cautions

1. Hitachi neither warrants nor grants licenses of any rights of Hitachi's or any third party's patent, copyright, trademark, or other intellectual property rights for information contained in this document. Hitachi bears no responsibility for problems that may arise with third party's rights, including intellectual property rights, in connection with use of the information contained in this document.

2. Products and product specifications may be subject to change without notice. Confirm that you have received the latest product standards or specifications before final design, purchase or use.

3. Hitachi makes every attempt to ensure that its products are of high quality and reliability. However, contact Hitachi's sales office before using the product in an application that demands especially high quality and reliability or where its failure or malfunction may directly threaten human life or cause risk of bodily injury, such as aerospace, aeronautics, nuclear power, combustion control, transportation, traffic, safety equipment or medical equipment for life support.

4. Design your application so that the product is used within the ranges guaranteed by Hitachi particularly for maximum rating, operating supply voltage range, heat radiation characteristics, installation conditions and other characteristics. Hitachi bears no responsibility for failure or damage when used beyond the guaranteed ranges. Even within the guaranteed ranges, consider normally foreseeable failure rates or failure modes in semiconductor devices and employ systemic measures such as fail-safes, so that the equipment incorporating Hitachi product does not cause bodily injury, fire or other consequential damage due to operation of the Hitachi product.

5. This product is not designed to be radiation resistant.

6. No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without written approval from Hitachi.

7. Contact Hitachi's sales office for any questions regarding this document or Hitachi semiconductor products.

HITACHI

Hitachi, Ltd.

Semiconductor & Integrated Circuits.
Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100-0004, Japan
Tel: Tokyo (03) 3270-2111 Fax: (03) 3270-5109

URL	NorthAmerica	: http://semiconductor.hitachi.com/
	Europe	: http://www.hitachi-eu.com/hel/ecg
	Asia	: http://sicapac.hitachi-asia.com
	Japan	: http://www.hitachi.co.jp/Sicd/indx.htm

For further information write to:

Hitachi Semiconductor (America) Inc. 179 East Tasman Drive, San Jose, CA 95134 Tel: <1> (408) 433-1990 Fax: <1> (408) 433-0223	Hitachi Europe GmbH Electronic Components Group Dornacher StraÙe 3 D-85622 Feldkirchen, Munich Germany Tel: <49> (89) 9 9180-0 Fax: <49> (89) 9 29 30 00 Hitachi Europe Ltd. Electronic Components Group. Whitebrook Park Lower Cookham Road Maidenhead Berkshire SL6 8YA, United Kingdom Tel: <44> (1628) 585000 Fax: <44> (1628) 585160
--	---

Hitachi Asia Ltd. Hitachi Tower 16 Collyer Quay #20-00, Singapore 049318 Tel : <65>-538-6533/538-8577 Fax : <65>-538-6933/538-3877 URL : http://www.hitachi.com.sg Hitachi Asia Ltd. (Taipei Branch Office) 4/F, No. 167, Tun Hwa North Road, Hung-Kuo Building, Taipei (105), Taiwan Tel : <886>-(2)-2718-3666 Fax : <886>-(2)-2718-8180 Telex : 23222 HAS-TP URL : http://www.hitachi.com.tw

Hitachi Asia (Hong Kong) Ltd. Group III (Electronic Components) 7/F., North Tower, World Finance Centre, Harbour City, Canton Road Tsim Sha Tsui, Kowloon, Hong Kong Tel : <852>-(2)-735-9218 Fax : <852>-(2)-730-0281 URL : http://www.hitachi.com.hk

Copyright © Hitachi, Ltd., 2000. All rights reserved. Printed in Japan.
Colophon 2.0