

TO-92



SOT-89



Pin Definition:

1. Ground
2. Input
3. Output

SOP-8



Pin Definition:

- |           |           |
|-----------|-----------|
| 1. Output | 8. N/C    |
| 2. Input  | 7. Input  |
| 3. Input  | 6. Input  |
| 4. N/C    | 5. Ground |

### General Description

The TS79L00 Series of negative voltage regulators are inexpensive, easy-to-use devices suitable for a multitude of applications that require a regulated supply of up to 100mA. Like their higher power TS7900 and TS79M00 Series cousins, these regulators feature internal current limiting and thermal shutdown making them remarkably rugged. No external components are required with the TS79L00 devices in many applications.

These devices offer a substantial performance advantage over the traditional zener diode-resistor combination, as output impedance and quiescent current are substantially reduced.

### Features


- Output Voltage Range -5 to -24V
- Output current up to 100mA
- No external components required
- Internal thermal overload protection
- Internal short-circuit current limiting
- Output transistor safe-area compensation
- Output voltage offered in 4% tolerance

### Ordering Information

Part No.	Package	Packing
TS79LxxCT B0	TO-92	1Kpcs / Bulk
TS79LxxCT A3	TO-92	2Kpcs / Ammo
TS79LxxCY RM	SOT-89	1Kpcs / 7" Reel
TS79LxxCS RL	SOP-8	2.5Kpcs / 13" Reel

Note: Where **xx** denote voltage option

### Standard Application Circuit



A common ground is required between the input and the output voltages. The input voltage must remain typically 2.0V above the output voltage even during the low point on the Input ripple voltage.

XX = these two digits of the type number indicate voltage.

\* = C<sub>in</sub> is required if regulator is located an appreciable distance from power supply filter.

\*\* = C<sub>o</sub> is not needed for stability; however, it does improve transient response.

### Absolute Maximum Rating (T<sub>a</sub> = 25°C unless otherwise noted)

Parameter	Symbol	Limit	Unit
Input Voltage	V <sub>IN</sub> *	-35	V
Input Voltage	V <sub>IN</sub> **	-40	V
Power Dissipation	P <sub>D</sub>	Internal Limited	W
Operating Temperature range	T <sub>OPR</sub>	0~+125	°C
Junction Temperature	T <sub>J</sub>	+150	°C
Storage Temperature Range	T <sub>STG</sub>	-65~+150	°C

Note: \* TS79L05 to TS79L18

\*\* TS79L24

### TS79L05 Electrical Characteristics

( $V_{in} = -10V$ ,  $I_{out} = 40mA$ ,  $0^{\circ}C \leq T_j \leq 125^{\circ}C$ ,  $C_{in} = 0.33\mu F$ ,  $C_{out} = 0.1\mu F$ ; unless otherwise specified.)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Output voltage	Vout	$T_j = 25^{\circ}C$	-4.80	-5	-5.20	V
		$-7.5V \leq V_{in} \leq -20V$ , $5mA \leq I_{out} \leq 100mA$	-4.75	-5	-5.25	
Line Regulation	REGline	$T_j = 25^{\circ}C$   $-7.5V \leq V_{in} \leq -20V$	--	50	150	mV
Load Regulation	REGload	$T_j = 25^{\circ}C$	$5mA \leq I_{out} \leq 100mA$	--	20	
			$5mA \leq I_{out} \leq 40mA$	--	10	30
Quiescent Current	Iq	$I_{out} = 0$ , $T_j = 25^{\circ}C$	--	3	6	mA
Quiescent Current Change	$\Delta Iq$	$-7.5V \leq V_{in} \leq -25V$	--	--	1.5	
		$5mA \leq I_{out} \leq 40mA$	--	--	0.1	
Output Noise Voltage	Vn	$10Hz \leq f \leq 100KHz$ , $T_j = 25^{\circ}C$	--	40	--	$\mu V$
Ripple Rejection Ratio	RR	$f = 120Hz$ , $-8V \leq V_{in} \leq -18V$	41	49	--	dB
Voltage Drop	Vdrop	$I_{out} = 100mA$ , $T_j = 25^{\circ}C$	--	1.7	--	V
Peak Output Current	I <sub>o peak</sub>	$T_j = 25^{\circ}C$	--	0.15	--	A
Temperature Coefficient of Output Voltage	$\Delta V_{out} / \Delta T_j$	$I_{out} = 5mA$ , $0^{\circ}C \leq T_j \leq 125^{\circ}C$	--	-0.65	--	$mV/^{\circ}C$

### TS79L06 Electrical Characteristics

( $V_{in} = -11V$ ,  $I_{out} = 40mA$ ,  $0^{\circ}C \leq T_j \leq 125^{\circ}C$ ,  $C_{in} = 0.33\mu F$ ,  $C_{out} = 0.1\mu F$ ; unless otherwise specified.)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Output voltage	Vout	$T_j = 25^{\circ}C$	5.76	6	6.24	V
		$-8.5V \leq V_{in} \leq -21V$ , $5mA \leq I_{out} \leq 100mA$	5.70	6	6.30	
Line Regulation	REGline	$T_j = 25^{\circ}C$   $-8.5V \leq V_{in} \leq -21V$	--	50	150	mV
Load Regulation	REGload	$T_j = 25^{\circ}C$	$5mA \leq I_{out} \leq 100mA$	--	20	
			$5mA \leq I_{out} \leq 40mA$	--	10	30
Quiescent Current	Iq	$I_{out} = 0$ , $T_j = 25^{\circ}C$	--	3	6	mA
Quiescent Current Change	$\Delta Iq$	$-10.5V \leq V_{in} \leq -21V$	--	--	1.5	
		$5mA \leq I_{out} \leq 40mA$	--	--	0.1	
Output Noise Voltage	Vn	$10Hz \leq f \leq 100KHz$ , $T_j = 25^{\circ}C$	--	40	--	$\mu V$
Ripple Rejection Ratio	RR	$f = 120Hz$ , $-10.5V \leq V_{in} \leq -21V$	41	49	--	dB
Voltage Drop	Vdrop	$I_{out} = 100mA$ , $T_j = 25^{\circ}C$	--	1.7	--	V
Peak Output Current	I <sub>o peak</sub>	$T_j = 25^{\circ}C$	--	0.15	--	A
Temperature Coefficient of Output Voltage	$\Delta V_{out} / \Delta T_j$	$I_{out} = 5mA$ , $0^{\circ}C \leq T_j \leq 125^{\circ}C$	--	-0.75	--	$mV/^{\circ}C$

- Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible, and thermal effects must be taken into account separately.
- This specification applies only for DC power dissipation permitted by absolute maximum ratings.

### TS79L08 Electrical Characteristics

$V_{in} = -14V$ ,  $I_{out} = 40mA$ ,  $0^{\circ}C \leq T_j \leq 125^{\circ}C$ ,  $C_{in} = 0.33\mu F$ ,  $C_{out} = 0.1\mu F$ ; unless otherwise specified.)

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Output voltage	Vout	Tj=25°C		7.69	8	8.32	V
		-10.5V ≤ Vin ≤ -23V, 5mA ≤ Iout ≤ 100mA		7.61	8	8.40	
Line Regulation	REGline	Tj=25°C	-10.5V ≤ Vin ≤ -25V	--	80	160	mV
Load Regulation	REGload	Tj=25°C	5mA ≤ Iout ≤ 100mA	--	25	80	
			5mA ≤ Iout ≤ 40mA	--	10	40	
Quiescent Current	Iq	Iout=0, Tj=25°C		--	3	6	mA
Quiescent Current Change	ΔIq	-10.5V ≤ Vin ≤ -23V		--	--	1.5	
		5mA ≤ Iout ≤ 40mA		--	--	0.1	
Output Noise Voltage	Vn	10Hz ≤ f ≤ 100KHz, Tj=25°C		--	60	--	μV
Ripple Rejection Ratio	RR	f=120Hz, -11V ≤ Vin ≤ -23V		37	57	--	dB
Voltage Drop	Vdrop	Iout=100mA, Tj=25°C		--	1.7	--	V
Peak Output Current	I <sub>o peak</sub>	Tj=25°C		--	0.15	--	A
Temperature Coefficient of Output Voltage	ΔVout/ ΔTj	Iout=5mA, 0°C ≤ Tj ≤ 125°C		--	-0.8	--	mV/°C

### TS79L09 Electrical Characteristics

$V_{in} = -15V$ ,  $I_{out} = 40mA$ ,  $0^{\circ}C \leq T_j \leq 125^{\circ}C$ ,  $C_{in} = 0.33\mu F$ ,  $C_{out} = 0.1\mu F$ ; unless otherwise specified.)

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Output voltage	Vout	Tj=25°C		8.65	9	9.36	V
		-11.5V ≤ Vin ≤ -24V, 5mA ≤ Iout ≤ 100mA		8.57	9	9.45	
Line Regulation	REGline	Tj=25°C	-11.5V ≤ Vin ≤ -24V	--	90	180	mV
Load Regulation	REGload	Tj=25°C	5mA ≤ Iout ≤ 100mA	--	30	90	
			5mA ≤ Iout ≤ 40mA	--	15	45	
Quiescent Current	Iq	Iout=0, Tj=25°C		--	3	6	mA
Quiescent Current Change	ΔIq	-11V ≤ Vin ≤ -23V		--	--	1.5	
		5mA ≤ Iout ≤ 40mA		--	--	0.1	
Output Noise Voltage	Vn	10Hz ≤ f ≤ 100KHz, Tj=25°C		--	60	--	μV
Ripple Rejection Ratio	RR	f=120Hz, -13V ≤ Vin ≤ -24V		37	57	--	dB
Voltage Drop	Vdrop	Iout=100mA, Tj=25°C		--	1.7	--	V
Peak Output Current	I <sub>o peak</sub>	Tj=25°C		--	0.15	--	A
Temperature Coefficient of Output Voltage	ΔVout/ ΔTj	Iout=5mA, 0°C ≤ Tj ≤ 125°C		--	-0.9	--	mV/°C

- Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible, and thermal effects must be taken into account separately.
- This specification applies only for DC power dissipation permitted by absolute maximum ratings.

### TS79L12 Electrical Characteristics

$V_{in} = -19V$ ,  $I_{out} = 40mA$ ,  $0^{\circ}C \leq T_j \leq 125^{\circ}C$ ,  $C_{in} = 0.33\mu F$ ,  $C_{out} = 0.1\mu F$ ; unless otherwise specified.)

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Output voltage	Vout	Tj=25°C		11.53	12	12.48	V
		-14.5V ≤ Vin ≤ -27V, 5mA ≤ Iout ≤ 100mA		11.42	12	12.60	
Line Regulation	REGline	Tj=25°C	-14.5V ≤ Vin ≤ -27V	--	120	240	mV
Load Regulation	REGload	Tj=25°C	5mA ≤ Iout ≤ 100mA	--	40	120	
			5mA ≤ Iout ≤ 40mA	--	20	60	
Quiescent Current	Iq	Iout=0, Tj=25°C		--	3	6.5	mA
Quiescent Current Change	ΔIq	-16V ≤ Vin ≤ -27V		--	--	1.5	
		5mA ≤ Iout ≤ 40mA		--	--	0.1	
Output Noise Voltage	Vn	10Hz ≤ f ≤ 100KHz, Tj=25°C		--	80	--	μV
Ripple Rejection Ratio	RR	f=120Hz, -11V ≤ Vin ≤ -23V		37	42	--	dB
Voltage Drop	Vdrop	Iout=100mA, Tj=25°C		--	1.7	--	V
Peak Output Current	I <sub>o peak</sub>	Tj=25°C		--	0.15	--	A
Temperature Coefficient of Output Voltage	ΔVout/ ΔTj	Iout=5mA, 0°C ≤ Tj ≤ 125°C		--	-1.0	--	mV/°C

### TS79L15 Electrical Characteristics

$V_{in} = -23V$ ,  $I_{out} = 40mA$ ,  $0^{\circ}C \leq T_j \leq 125^{\circ}C$ ,  $C_{in} = 0.33\mu F$ ,  $C_{out} = 0.1\mu F$ ; unless otherwise specified.)

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Output voltage	Vout	Tj=25°C		14.42	15	15.60	V
		-17.5V ≤ Vin ≤ -30V, 5mA ≤ Iout ≤ 100mA		14.28	15	15.75	
Line Regulation	REGline	Tj=25°C	-17.5V ≤ Vin ≤ -24V	--	150	30	mV
Load Regulation	REGload	Tj=25°C	5mA ≤ Iout ≤ 100mA	--	50	150	
			5mA ≤ Iout ≤ 40mA	--	25	75	
Quiescent Current	Iq	Iout=0, Tj=25°C		--	3	6.6	mA
Quiescent Current Change	ΔIq	-20V ≤ Vin ≤ -30V		--	--	1.5	
		5mA ≤ Iout ≤ 40mA		--	--	0.1	
Output Noise Voltage	Vn	10Hz ≤ f ≤ 100KHz, Tj=25°C		--	90	--	μV
Ripple Rejection Ratio	RR	f=120Hz, -18V ≤ Vin ≤ -28V		34	39	--	dB
Voltage Drop	Vdrop	Iout=100mA, Tj=25°C		--	1.7	--	V
Peak Output Current	I <sub>o peak</sub>	Tj=25°C		--	0.15	--	A
Temperature Coefficient of Output Voltage	ΔVout/ ΔTj	Iout=5mA, 0°C ≤ Tj ≤ 125°C		--	-1.3	--	mV/°C

- Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible, and thermal effects must be taken into account separately.
- This specification applies only for DC power dissipation permitted by absolute maximum ratings.

### TS79L18 Electrical Characteristics

$V_{in} = -27V$ ,  $I_{out} = 40mA$ ,  $0^{\circ}C \leq T_j \leq 125^{\circ}C$ ,  $C_{in} = 0.33\mu F$ ,  $C_{out} = 0.1\mu F$ ; unless otherwise specified.)

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Output voltage	Vout	T <sub>j</sub> =25°C		17.30	18	18.72	V
		-21V ≤ V <sub>in</sub> ≤ -33V, 5mA ≤ I <sub>out</sub> ≤ 100mA		17.14	18	18.90	
Line Regulation	REG <sub>line</sub>	T <sub>j</sub> =25°C	-21 ≤ V <sub>in</sub> ≤ -33V	--	180	360	mV
Load Regulation	REG <sub>load</sub>	T <sub>j</sub> =25°C	5mA ≤ I <sub>out</sub> ≤ 100mA	--	60	180	
			5mA ≤ I <sub>out</sub> ≤ 40mA	--	30	90	
Quiescent Current	I <sub>q</sub>	I <sub>out</sub> =0, T <sub>j</sub> =25°C		--	3	6.5	mA
Quiescent Current Change	ΔI <sub>q</sub>	-21V ≤ V <sub>in</sub> ≤ -33V		--	--	1.5	
		5mA ≤ I <sub>out</sub> ≤ 40mA		--	--	0.1	
Output Noise Voltage	V <sub>n</sub>	10Hz ≤ f ≤ 100KHz, T <sub>j</sub> =25°C		--	150	--	μV
Ripple Rejection Ratio	RR	f=120Hz, -23V ≤ V <sub>in</sub> ≤ -33V		33	48	--	dB
Voltage Drop	V <sub>drop</sub>	I <sub>out</sub> =100mA, T <sub>j</sub> =25°C		--	1.7	--	V
Peak Output Current	I <sub>o peak</sub>	T <sub>j</sub> =25°C		--	0.15	--	A
Temperature Coefficient of Output Voltage	ΔV <sub>out</sub> / ΔT <sub>j</sub>	I <sub>out</sub> =5mA, 0°C ≤ T <sub>j</sub> ≤ 125°C		--	-1.5	--	mV/°C


### TS79L24 Electrical Characteristics

$V_{in} = -33V$ ,  $I_{out} = 40mA$ ,  $0^{\circ}C \leq T_j \leq 125^{\circ}C$ ,  $C_{in} = 0.33\mu F$ ,  $C_{out} = 0.1\mu F$ ; unless otherwise specified.)

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Output voltage	Vout	T <sub>j</sub> =25°C		23.07	24	24.96	V
		-27V ≤ V <sub>in</sub> ≤ -38V, 5mA ≤ I <sub>out</sub> ≤ 100mA		22.85	24	25.20	
Line Regulation	REG <sub>line</sub>	T <sub>j</sub> =25°C	-27 ≤ V <sub>in</sub> ≤ -38V	--	200	400	mV
Load Regulation	REG <sub>load</sub>	T <sub>j</sub> =25°C	5mA ≤ I <sub>out</sub> ≤ 100mA	--	80	240	
			5mA ≤ I <sub>out</sub> ≤ 40mA	--	40	120	
Quiescent Current	I <sub>q</sub>	I <sub>out</sub> =0, T <sub>j</sub> =25°C		--	4	7	mA
Quiescent Current Change	ΔI <sub>q</sub>	-27V ≤ V <sub>in</sub> ≤ -38V		--	--	1.5	
		5mA ≤ I <sub>out</sub> ≤ 40mA		--	--	0.1	
Output Noise Voltage	V <sub>n</sub>	10Hz ≤ f ≤ 100KHz, T <sub>j</sub> =25°C		--	200	--	μV
Ripple Rejection Ratio	RR	f=120Hz, -29V ≤ V <sub>in</sub> ≤ -35V		31	45	--	dB
Voltage Drop	V <sub>drop</sub>	I <sub>out</sub> =100mA, T <sub>j</sub> =25°C		--	1.7	--	V
Peak Output Current	I <sub>o peak</sub>	T <sub>j</sub> =25°C		--	0.15	--	A
Temperature Coefficient of Output Voltage	ΔV <sub>out</sub> / ΔT <sub>j</sub>	I <sub>out</sub> =5mA, 0°C ≤ T <sub>j</sub> ≤ 125°C		--	-2.0	--	mV/°C


- Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible, and thermal effects must be taken into account separately.
- This specification applies only for DC power dissipation permitted by absolute maximum ratings.

### TO-92 Mechanical Drawing




TO-92 DIMENSION				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.30	4.70	0.169	0.185
B	4.30	4.70	0.169	0.185
C	14.30(typ)		0.563(typ)	
D	0.43	0.49	0.017	0.019
E	2.19	2.81	0.086	0.111
F	3.30	3.70	0.130	0.146
G	2.42	2.66	0.095	0.105
H	0.37	0.43	0.015	0.017

### Marking Diagram




- XX** = Output Voltage  
(05=5V, 06=6V, 08=8V, 09=9V, 12=12V, 15=15V, 18=18V, 24=24V)
- Y** = Year Code
- M** = Month Code  
(**A**=Jan, **B**=Feb, **C**=Mar, **D**=Apr, **E**=May, **F**=Jun, **G**=Jul, **H**=Aug, **I**=Sep, **J**=Oct, **K**=Nov, **L**=Dec)
- L** = Lot Code

### SOT-89 Mechanical Drawing



SOT-89 DIMENSION				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.40	4.60	0.173	0.181
B	1.50	1.7	0.059	0.070
C	2.30	2.60	0.090	0.102
D	0.40	0.52	0.016	0.020
E	1.50	1.50	0.059	0.059
F	3.00	3.00	0.118	0.118
G	0.89	1.20	0.035	0.047
H	4.05	4.25	0.159	0.167
I	1.4	1.6	0.055	0.068
J	0.35	0.44	0.014	0.017

### Marking Diagram




- XX** = Output Voltage  
(05=5V, 06=6V, 08=8V, 09=9V, 12=12V, 15=15V, 18=18V, 24=24V)
- Y** = Year Code
- M** = Month Code  
(A=Jan, B=Feb, C=Mar, D=Apl, E=May, F=Jun, G=Jul, H=Aug, I=Sep, J=Oct, K=Nov, L=Dec)
- L** = Lot Code

# TS79L00 Series


## 3-Terminal 100mA Negative Voltage Regulator

### SOP-8 Mechanical Drawing



SOP-8 DIMENSION				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX.
A	4.80	5.00	0.189	0.196
B	3.80	4.00	0.150	0.157
C	1.35	1.75	0.054	0.068
D	0.35	0.49	0.014	0.019
F	0.40	1.25	0.016	0.049
G	1.27BSC		0.05BSC	
K	0.10	0.25	0.004	0.009
M	0°	7°	0°	7°
P	5.80	6.20	0.229	0.244
R	0.25	0.50	0.010	0.019

### Marking Diagram



- XX** = Output Voltage  
(05=5V, 06=6V, 08=8V, 09=9V, 12=12V, 15=15V, 18=18V, 24=24V)
- Y** = Year Code
- M** = Month Code  
(A=Jan, B=Feb, C=Mar, D=Apr, E=May, F=Jun, G=Jul, H=Aug, I=Sep, J=Oct, K=Nov, L=Dec)
- L** = Lot Code



# TS79L00 Series

## 3-Terminal 100mA Negative Voltage Regulator

### Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.