


AT22V10/L

T-46-13-47

Features

- High Speed Programmable Logic Device
15 ns Max Propagation Delay
5V $\pm$ 10% Operation
 - Low Power CMOS Operation
- | Speed | "L" | -15 | All |
|---------|-------|-----|--------|
| Temp | C/M | All | Others |
| Icc(mA) | 12/15 | 90 | 55 |
- CMOS and TTL Compatible Inputs and Outputs
10 μ A Leakage Maximum
 - Reprogrammable - Tested 100% for Programmability
 - High Reliability CMOS Technology
2000V ESD Protection
200mA Latchup Immunity
 - Full Military, Commercial and Industrial Temperature Ranges
 - Dual-In-Line and Surface Mount Packages

Logic Diagram



Description

The AT22V10 and AT22V10L are CMOS high performance Erasable Programmable Logic Devices (EPLDs). Speeds down to 15 ns and power dissipation as low as 12 mW are offered. All speed ranges are specified over the full 5V $\pm$ 10% range. All pins offer a low $\pm$ 10 μ A leakage.

The AT22V10L provides the optimum low power CMOS EPLD solution, with low DC power (8mW typical) and full CMOS output levels. The AT22V10L significantly reduces total system power and enhances system reliability.

Full CMOS output levels help reduce power in many other system components.


The AT22V10 and AT22V10L incorporate a variable product term architecture. Each output is allocated from 8 to 16 product terms, which allows highly complex logic functions to be realized.

Two additional product terms are included to provide synchronous preset and asynchronous reset. These terms are common to all 10 registers. All registers are automatically cleared upon power up.

Register Preload simplifies testing. A Security Fuse prevents unauthorized copying of programmed fuse patterns.

Pin Configurations

Pin Name	Function
CLK/IN	Clock and Logic Input
IN	Logic Inputs
I/O	Bidirectional Buffers
*	No Internal Connection
VCC	+5V Supply



High Speed
UV Erasable
Programmable
Logic Device

7



Absolute Maximum Ratings*



Temperature Under Bias.....	-55°C to +125°C
Storage Temperature.....	-65°C to +150°C
Voltage on Any Pin with Respect to Ground.....	-2.0V to +7.0V ⁽¹⁾
Voltage on Input Pins with Respect to Ground During Programming	-2.0V to +14.0V ⁽¹⁾
Programming Voltage with Respect to Ground.....	-2.0V to +14.0V ⁽¹⁾
Integrated UV Erase Dose	7258 w·sec/cm ²

*NOTICE: Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.



Note:

1. Minimum voltage is -0.6V dc which may undershoot to -2.0V for pulses of less than 20ns. Maximum output pin voltage is $V_{CC}+0.75V$ dc which may overshoot to +7.0V for pulses of less than 20ns.

Logic Options



Output Options



D.C. and A.C. Operating Conditions

	Commercial AT22V10/L -15, -20, -25, -35	Industrial AT22V10/L -15, -20, -25, -35	Military AT22V10/L -15 ⁽¹⁾ , -20, -25, -30
Operating Temperature (Case)	0°C - 70°C	-40°C - 85°C	-55°C - 125°C
V _{CC} Power Supply	5V ± 10%	5V ± 10%	5V ± 10%

Note: 1. Preliminary.

Operating Modes

Mode	24 DIP Pin	1	5	8	13	I/O's	V _{CC} (24)
	28 JLCC Pin	2	6	10	16	I/O's	V _{CC} (28)
"EPLD"		X ⁽¹⁾	X	X	X	I/O	5V
Program		V _{PP}	X/V _H ⁽²⁾	X	V _{PP}	D _{IN}	6V
PGM Verify		V _{PP}	X/V _H	X	V _{IL}	D _{OUT}	6V
PGM Inhibit		V _{PP}	X/V _H	X	V _{IH}	High Z	6V
Preload		X	X	V _H	X	D _{IN}	5V

Notes: 1. X can be V_{IL} or V_{IH}.

2. V_H = 11.0V to 14.0V

D.C. Characteristics

Symbol	Parameter	Condition	Min	Max	Units
I _{LI}	Input Load Current	V _{IN} = -0.1V to V _{CC} + 1V		10	μA
I _{LO}	Output Leakage Current	V _{OUT} = -0.1V to V _{CC} + 0.1V		10	μA
I _{CC}	Power Supply Current	V _{CC} = MAX, V _{IN} = GND, Outputs Open	AT22V10-15	90	mA
			AT22V10-20,-25,-35 ⁽²⁾	55	mA
			22V10L ⁽²⁾ Com.	12	mA
			Ind., Mil.	15	mA
I _{CC2}	Clocked Power Supply Current	f = 1MHz, V _{CC} = MAX, Outputs Open	22V10L ⁽²⁾ Com.	15	mA
			Ind., Mil.	20	mA
I _{OS} ⁽¹⁾	Output Short Circuit Current	V _{OUT} = 0.5V		-90	mA
V _{IL}	Input Low Voltage		-0.6	0.8	V
V _{IH}	Input High Voltage		2.0	V _{CC} + 0.75	V
V _{OL}	Output Low Voltage	V _{IN} = V _{IH} or V _{IL} , V _{CC} = MIN	I _{OL} = 16mA Com., Ind.	0.5	V
			I _{OL} = 12mA Mil.	0.5	V
			I _{OL} = 24mA Com.	0.8	V
V _{OH}	Output High Voltage	V _{IN} = V _{IH} or V _{IL} , V _{CC} = MIN	I _{OH} = -100μA	V _{CC} - 0.3	V
			I _{OH} = -4.0mA	2.4	V

Notes: 1. Not more than one output at a time should be shorted.
Duration of short circuit test should not exceed 30 sec.
This parameter is only sampled and is not 100% tested.
See Absolute Maximum Ratings.

2. See I_{CC} vs. Frequency curves in the back of this data sheet.


7

A.C. Characteristics, Commercial and Industrial

Symbol	Parameter	22V10/L-15			22V10/L-20			22V10/L-25			22V10/L-35			Units
		Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
t _{PD}	Input or Feedback to Non-Registered Output	10	15		12	20		15	25		20	35		ns
t _{EA}	Input to Output Enable	10	15			20		15	25		20	35		ns
t _{ER}	Input to Output Disable	10	15			20		15	25		20	35		ns
t _{CF}	Clock to Feedback	0	1	2.5	0	4	8	0	5	10	0	10	15	ns
t _{CO}	Clock to Output	0	7	10	0	8	12	0	10	15	0	12	20	ns
t _S	Input or Feedback Setup Time	10	8		12	8		15	12		20	15		ns
t _H	Hold Time	0			0			0			0			ns
t _P	Clock Period	12			20			24			30			ns
t _W	Clock Width	6			10			12			15			ns
F _{MAX}	External Feedback 1/(t _S + t _{CO})			50.0			41.6			33.3			25.0	MHz
	Internal Feedback 1/(t _S + t _{CP})			80.0			50.0			40.0			28.5	MHz
	No Feedback 1/(t _P)			83.3			50.0			41.6			33.3	MHz
t _{AW}	Asynchronous Reset Width	15	8		20	9		25	10		30	15		ns
t _{AR}	Asynchronous Reset Recovery Time	15	8		20	12		25	15		30	18		ns
t _{AP}	Asynchronous Reset to Registered Output Reset		12	20		15	22		18	25		20	30	ns



29E D




Note: 1. Timing measurement reference is 1.5V. Input AC driving levels are 0.0V and 3.0V, unless otherwise specified.

A.C. Characteristics, Military


Symbol	Parameter	AT22V10/L-15 ⁽¹⁾			AT22V10/L-20			AT22V10/L-25			AT22V10/L-30			Units
		Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
t _{PD}	Input or Feedback to Non-Registered Output	10		15	12		20	15		25	20		30	ns
t _{EA}	Input to Output Enable	10		15			20	15		25	20		30	ns
t _{ER}	Input to Output Disable	10		15			20	15		25	20		30	ns
t _{CF}	Clock to Feedback	0	1	2.5	0	4	8	0	5	10	0	10	15	ns
t _{CO}	Clock to Output	0	7	10	0	8	15	0	10	15	0	12	20	ns
t _{SF}	Feedback Setup Time	10		8	12		10	15		12	18		15	ns
t _S	Input Setup Time	10		8	17		14	18		15	20		15	ns
t _H	Hold Time	0			0			0			0			ns
t _P	Clock Period	12			20			24			30			ns
t _W	Clock Width	6			10			12			15			ns
F _{MAX}	External Feedback 1/(t _S +t _{CO})			50.0			31.2			30.3			25.0	MHz
	Internal Feedback 1/(t _S + t _{CF})			80.0			50.0			40.0			30.0	MHz
	No Feedback 1/(t _P)			83.3			50.0			41.6			33.3	MHz
t _{AW}	Asynchronous Reset Width	15		8	20		9	25		10	30		15	ns
t _{AR}	Asynchronous Reset Recovery Time	15		8	20		12	25		15	30		18	ns
t _{AP}	Asynchronous Reset to Registered Output Reset			12			20			18			20	ns

Note: 1. Preliminary


Input Test Waveforms and Measurement Levels

 $t_R, t_F < 5\text{ns}$ (10% to 90%)

Output Test Loads: Commercial




Military



AT22V10/L

T-46-13-47

Functional Logic Diagram AT22V10/L




Preload of Registered Outputs

ATMEL CORP

29E D

The registers in the AT22V10 and AT22V10L are provided with circuitry to allow loading of each register asynchronously with either a high or a low. This feature will simplify testing since any state can be forced into the registers to control test sequencing. A V_{IH} level on the I/O pin will force the register high; a V_{IL} will force it low, independent of the polarity bit (C0) setting. The PRELOAD state is entered by placing an 11V to 14V signal on pin 8 on DIPs, and pin 10 on SMPs. When the clock pin is pulsed high, the data on the I/O pins is placed into the 10 registers.

Level forced on registered output pin during PRELOAD cycle.	Register state After Cycle
V_{IH}	High
V_{IL}	Low




Power Up Reset

The registers in the AT22V10 and AT22V10L are designed to reset during power up. At a point delayed slightly from V_{CC} crossing 3.8V, all registers will be reset to the low state. The output state will depend on the polarity of the output buffer.

This feature is critical for state machine initialization. However, due to the asynchronous nature of reset and the uncertainty of how V_{CC} actually rises in the system, the following conditions are required:

- 1) The V_{CC} rise must be monotonic,
- 2) After reset occurs, all input and feedback setup times must be met before driving the clock pin high, and
- 3) The clock must remain stable during t_{PR} .



Parameter	Description	Min	Typ	Max	Units
t_{PR}	Power-Up Reset Time	600	1000		ns

Pin Capacitance ($f = 1\text{MHz}$ $T = 25^\circ\text{C}$) ⁽¹⁾

	Typ	Max	Units	Conditions
C_{IN}	5	8	pF	$V_{IN} = 0V$
C_{OUT}	6	8	pF	$V_{OUT} = 0V$

Note: 1. Typical values for nominal supply voltage. This parameter is only sampled and is not 100% tested.

Erase Characteristics

The entire fuse array of an AT22V10 or AT22V10L is erased after exposure to ultraviolet light at a wavelength of 2537 Å. Complete erasure is assured after a minimum of 20 minutes exposure using 12,000 $\mu\text{W}/\text{cm}^2$ intensity lamps spaced one inch away from the chip. Minimum erase time for lamps at other intensity ratings can be calculated from the minimum


integrated erasure dose of 15W·sec/cm². To prevent unintentional erasure, an opaque label is recommended to cover the clear window on any UV erasable EPLD which will be subjected to continuous fluorescent indoor lighting or sunlight.

AT22V10/L

T-46-13-47



SUPPLY CURRENT vs. INPUT FREQUENCY

AT22V10-15 (TA = 25°C, VCC = 5V)




SUPPLY CURRENT vs. INPUT FREQUENCY

AT22V10L & AT22V10 (except AT22V10-15)


NORMALIZED SUPPLY CURRENT
vs. SUPPLY VOLTAGE

NORMALIZED ICC vs. AMBIENT TEMP.

f = 30 MHz





7

OUTPUT SINK CURRENT
vs. SUPPLY VOLTAGE (VOL = 0.5V)


OUTPUT SINK CURRENT

vs. OUTPUT VOLTAGE (TA = 25°C, VCC = 5V)

OUTPUT SOURCE CURRENT
vs. SUPPLY VOLTAGE (VOH = 2.4V)

OUTPUT SOURCE CURRENT

vs. OUTPUT VOLTAGE (TA = 25°C, VCC = 5V)





Ordering Information

ATMEL CORP

29E D

t _{PD} (ns)	t _S (ns)	t _{CO} (ns)	Ordering Code	Package	Operation Range
15	10	10	AT22V10-15DC AT22V10-15FC AT22V10-15GC AT22V10-15JC AT22V10-15KC AT22V10-15LC AT22V10-15NC AT22V10-15PC AT22V10-15YC	24DW3 24C 24D3 28J 28KW 28LW 28L 24P3 24CW	Commercial (0°C to 70°C)
			AT22V10-15DI AT22V10-15FI AT22V10-15GI AT22V10-15JI AT22V10-15KI AT22V10-15LI AT22V10-15NI AT22V10-15PI AT22V10-15YI	24DW3 24C 24D3 28J 28KW 28LW 28L 24P3 24CW	Industrial (-40°C to 85°C)
20	12	15	AT22V10-20DC AT22V10-20FC AT22V10-20GC AT22V10-20JC AT22V10-20KC AT22V10-20LC AT22V10-20NC AT22V10-20PC AT22V10-20YC	24DW3 24C 24D3 28J 28KW 28LW 28L 24P3 24CW	Commercial (0°C to 70°C)
			AT22V10-20DI AT22V10-20FI AT22V10-20GI AT22V10-20JI AT22V10-20KI AT22V10-20LI AT22V10-20NI AT22V10-20PI AT22V10-20YI	24DW3 24C 24D3 28J 28KW 28LW 28L 24P3 24CW	Industrial (-40°C to 85°C)
20	17	15	AT22V10-20DM AT22V10-20FM AT22V10-20GM AT22V10-20KM AT22V10-20LM AT22V10-20NM AT22V10-20YM	24DW3 24C 24D3 28KW 28LW 28L 24CW	Military (-55°C to 125°C)

AT22V10/L

T-46-13-47

Ordering Information

t _{PD} (ns)	t _S (ns)	t _{CO} (ns)	Ordering Code	Package	Operation Range
20	17	15	AT22V10-20DM/883 AT22V10-20FM/883 AT22V10-20GM/883 AT22V10-20KM/883 AT22V10-20LM/883 AT22V10-20NM/883 AT22V10-20YM/883	24DW3 24C 24D3 28KW 28LW 28L 24CW	Military/883C (-55°C to 125°C) Class B, Fully Compliant
25	15	15	AT22V10-25DC AT22V10-25FC AT22V10-25GC AT22V10-25JC AT22V10-25KC AT22V10-25LC AT22V10-25NC AT22V10-25PC AT22V10-25YC	24DW3 24C 24D3 28J 28KW 28LW 28L 24P3 24CW	Commercial (0°C to 70°C)
			AT22V10-25DI AT22V10-25FI AT22V10-25GI AT22V10-25JI AT22V10-25KI AT22V10-25LI AT22V10-25NI AT22V10-25PI AT22V10-25YI	24DW3 24C 24D3 28J 28KW 28LW 28L 24P3 24CW	Industrial (-40°C to 85°C)
25	18	15	AT22V10-25DM AT22V10-25FM AT22V10-25GM AT22V10-25KM AT22V10-25LM AT22V10-25NM AT22V10-25YM	24DW3 24C 24D3 28KW 28LW 28L 24CW	Military (-55°C to 125°C)
			AT22V10-25DM/883 AT22V10-25FM/883 AT22V10-25GM/883 AT22V10-25KM/883 AT22V10-25LM/883 AT22V10-25NM/883 AT22V10-25YM/883	24DW3 24C 24D3 28KW 28LW 28L 24CW	Military/883C (-55°C to 125°C) Class B, Fully Compliant
30	20	20	AT22V10-30DM AT22V10-30FM AT22V10-30GM AT22V10-30KM AT22V10-30LM AT22V10-30NM AT22V10-30YM	24DW3 24C 28D3 28KW 28LW 28L 24CW	Military (-55°C to 125°C)

7





Ordering Information

ATMEL CORP

29E D

t _{PD} (ns)	t _S (ns)	t _{CO} (ns)	Ordering Code	Package	Operation Range
30	20	20	AT22V10-30DM/883 AT22V10-30FM/883 AT22V10-30GM/883 AT22V10-30KM/883 AT22V10-30LM/883 AT22V10-30NM/883 AT22V10-30YM/883	24DW3 24C 24D3 28KW 28LW 28L 24CW	Military/883C (-55°C to 125°C) Class B, Fully Compliant
35	25	25	AT22V10-35DC AT22V10-35FC AT22V10-35GC AT22V10-35JC AT22V10-35KC AT22V10-35LC AT22V10-35NC AT22V10-35PC AT22V10-35YC	24DW3 24C 24D3 28J 28KW 28LW 28L 24P3 24CW	Commercial (0°C to 70°C)
			AT22V10-35DI AT22V10-35FI AT22V10-35GI AT22V10-35JI AT22V10-35KI AT22V10-35LI AT22V10-35NI AT22V10-35PI AT22V10-35YI	24DW3 24C 24D3 28J 28KW 28LW 28L 24P3 24CW	Industrial (-40°C to 85°C)
20	17	15	5962-87539 04 LX 5962-87539 04 3X	24DW3 28LW	Military/883C (-55°C to 125°C) Class B, Fully Compliant
25	18	15	5962-87539 01 KX 5962-87539 01 LX 5962-87539 01 3X	24CW 24DW3 28LW	Military/883C (-55°C to 125°C) Class B, Fully Compliant
30	20	20	5962-87539 02 KX 5962-87539 02 LX 5962-87539 02 3X	24CW 24DW3 28LW	Military/883C (-55°C to 125°C) Class B, Fully Compliant
40	30	25	5962-87539 03 KX 5962-87539 03 LX 5962-87539 03 3X	24CW 24DW3 28LW	Military/883C (-55°C to 125°C) Class B, Fully Compliant
20	17	15	5962-88670 04 KX 5962-88670 04 LX 5962-88670 04 3X	24C 24D3 28L	Military/883C (-55°C to 125°C) Class B, Fully Compliant
25	18	15	5962-88670 01 KX 5962-88670 01 LX 5962-88670 01 3X	24C 24D3 28L	Military/883C (-55°C to 125°C) Class B, Fully Compliant
30	20	20	5962-88670 02 KX 5962-88670 02 LX 5962-88670 02 3X	24C 24D3 28L	Military/883C (-55°C to 125°C) Class B, Fully Compliant

AT22V10/L

T-46-13-47

Ordering Information

t _{PD} (ns)	t _S (ns)	t _{CO} (ns)	Ordering Code	Package	Operation Range
40	30	25	5962-88670 03 KX 5962-88670 03 LX 5962-88670 03 3X	24C 24D3 28L	Military/883C (-55°C to 125°C) Class B, Fully Compliant

7

Package Type

24DW3	24 Lead, 0.300" Wide, Windowed, Ceramic Dual Inline Package (Cerdip)
24C	24 Lead, Non-Windowed, Ceramic Flat Package (Cerpack)
24D3	24 Lead, 0.300" Wide, Non-Windowed (OTP), Ceramic Dual Inline Package (Cerdip)
28J	28 Lead, Plastic J-Leaded Chip Carrier OTP (PLCC)
28KW	28 Lead, Windowed, Ceramic J-Leaded Chip Carrier (JLCC)
28LW	28 Pad, Windowed, Ceramic Leadless Chip Carrier (LCC)
28L	28 Pad, Non-Windowed, Ceramic Leadless Chip Carrier OTP (LCC)
24P3	24 Lead, 0.300" Wide, Plastic Dual Inline Package OTP (PDIP)
24CW	24 Lead, Windowed, Ceramic Flat Package (Cerpack)





Ordering Information

t _{PD} (ns)	t _S (ns)	t _{CO} (ns)	Ordering Code	Package	Operation Range
15	10	10	AT22V10L-15DC AT22V10L-15FC AT22V10L-15GC AT22V10L-15JC AT22V10L-15KC AT22V10L-15LC AT22V10L-15NC AT22V10L-15PC AT22V10L-15YC	24DW3 24C 24D3 28J 28KW 28LW 28L 24P3 24CW	Commercial (0°C to 70°C)
			AT22V10L-15DI AT22V10L-15FI AT22V10L-15GI AT22V10L-15JI AT22V10L-15KI AT22V10L-15LI AT22V10L-15NI AT22V10L-15PI AT22V10L-15YI	24DW3 24C 24D3 28J 28KW 28LW 28L 24P3 24CW	Industrial (-40°C to 85°C)
20	12	15	AT22V10L-20DC AT22V10L-20FC AT22V10L-20GC AT22V10L-20JC AT22V10L-20KC AT22V10L-20LC AT22V10L-20NC AT22V10L-20PC AT22V10L-20YC	24DW3 24C 24D3 28J 28KW 28LW 28L 24P3 24CW	Commercial (0°C to 70°C)
			AT22V10L-20DI AT22V10L-20FI AT22V10L-20GI AT22V10L-20JI AT22V10L-20KI AT22V10L-20LI AT22V10L-20NI AT22V10L-20PI AT22V10L-20YI	24DW3 24C 24D3 28J 28KW 28LW 28L 24P3 24CW	Industrial (-40°C to 85°C)
20	17	15	AT22V10L-20DM AT22V10L-20FM AT22V10L-20GM AT22V10L-20KM AT22V10L-20LM AT22V10L-20NM AT22V10L-20YM	24DW3 24C 24D3 28KW 28LW 28L 24CW	Military (-55°C to 125°C)

AT22V10/L

T-46-13-47

Ordering Information

t _{PD} (ns)	t _S (ns)	t _{CO} (ns)	Ordering Code	Package	Operation Range
20	17	15	AT22V10L-20DM/883 AT22V10L-20FM/883 AT22V10L-20GM/883 AT22V10L-20KM/883 AT22V10L-20LM/883 AT22V10L-20NM/883 AT22V10L-20YM/883	24DW3 24C 24D3 28KW 28LW 28L 24CW	Military/883C (-55°C to 125°C) Class B, Fully Compliant
25	15	15	AT22V10L-25DC AT22V10L-25FC AT22V10L-25GC AT22V10L-25JC AT22V10L-25KC AT22V10L-25LC AT22V10L-25NC AT22V10L-25PC AT22V10L-25YC	24DW3 24C 24D3 28J 28KW 28LW 28L 24P3 24CW	Commercial (0°C to 70°C)
			AT22V10L-25DI AT22V10L-25FI AT22V10L-25GI AT22V10L-25JI AT22V10L-25KI AT22V10L-25LI AT22V10L-25NI AT22V10L-25PI AT22V10L-25YI	24DW3 24C 24D3 28J 28KW 28LW 28L 24P3 24CW	Industrial (-40°C to 85°C)
25	18	15	AT22V10L-25DM AT22V10L-25FM AT22V10L-25GM AT22V10L-25KM AT22V10L-25LM AT22V10L-25NM AT22V10L-25YM	24DW3 24C 24D3 28KW 28LW 28L 24CW	Military (-55°C to 125°C)
			AT22V10L-25DM/883 AT22V10L-25FM/883 AT22V10L-25GM/883 AT22V10L-25KM/883 AT22V10L-25LM/883 AT22V10L-25NM/883 AT22V10L-25YM/883	24DW3 24C 24D3 28KW 28LW 28L 24CW	Military/883C (-55°C to 125°C) Class B, Fully Compliant
30	20	20	AT22V10L-30DM AT22V10L-30FM AT22V10L-30GM AT22V10L-30KM AT22V10L-30LM AT22V10L-30NM AT22V10L-30YM	24DW3 24C 24D3 28KW 28LW 28L 24CW	Military (-55°C to 125°C)

7





Ordering Information

t _{PD} (ns)	t _S (ns)	t _{CO} (ns)	Ordering Code	Package	Operation Range
30	20	20	AT22V10L-30DM/883 AT22V10L-30FM/883 AT22V10L-30GM/883 AT22V10L-30KM/883 AT22V10L-30LM/883 AT22V10L-30NM/883 AT22V10L-35YM/883	24DW3 24C 24D3 28KW 28LW 28L 24CW	Military/883C (-55°C to 125°C) Class B, Fully Compliant
35	25	25	AT22V10L-35DC AT22V10L-35FC AT22V10L-35GC AT22V10L-35JC AT22V10L-35KC AT22V10L-35LC AT22V10L-35NC AT22V10L-35PC AT22V10L-35YC	24DW3 24C 24D3 28J 28KW 28LW 28L 24P3 24CW	Commercial (0°C to 70°C)
35	25	15	AT22V10L-35DI AT22V10L-35FI AT22V10L-35GI AT22V10L-35JI AT22V10L-35KI AT22V10L-35LI AT22V10L-35NI AT22V10L-35PI AT22V10L-35YI	24DW3 24C 24D3 28J 28KW 28LW 28L 24P3 24CW	Industrial (-40°C to 85°C)
20	17	15	5962-88724 04 KX 5962-88724 04 LX 5962-88724 04 3X	24CW 24DW3 28LW	Military/883C (-55°C to 125°C) Class B, Fully Compliant
25	18	15	5962-88724 01 KX 5962-88724 01 LX 5962-88724 01 3X	24CW 24DW3 28LW	Military/883C (-55°C to 125°C) Class B, Fully Compliant
30	20	20	5962-88724 02 KX 5962-88724 02 LX 5962-88724 02 3X	24CW 24DW3 28LW	Military/883C (-55°C to 125°C) Class B, Fully Compliant
40	30	25	5962-88724 03 KX 5962-88724 03 LX 5962-88724 03 3X	24CW 24DW3 28LW	Military/883C (-55°C to 125°C) Class B, Fully Compliant
25	18	15	5962-89755 01 KX 5962-89755 01 LX 5962-89755 01 3X	24C 24D3 28L	Military/883C (-55°C to 125°C) Class B, Fully Compliant
30	20	20	5962-89755 02 KX 5962-89755 02 LX 5962-89755 02 3X	24C 24D3 28L	Military/883C (-55°C to 125°C) Class B, Fully Compliant

Ordering Information

T-46-13-47

t _{PD} (ns)	t _S (ns)	t _{CO} (ns)	Ordering Code	Package	Operation Range
40	30	25	5962-89755 03 KX 5962-89755 03 LX 5962-89755 03 3X	24C 24D3 28L	Military/883C (-55°C to 125°C) Class B, Fully Compliant

7

Package Type	
24DW3	24 Lead, 0.300" Wide, Windowed, Ceramic Dual Inline Package (Cerdip)
24C	24 Lead, Non-Windowed, Ceramic Flat Package (Cerpack)
24D3	24 Lead, 0.300" Wide, Non-Windowed (OTP), Ceramic Dual Inline Package (Cerdip)
28J	28 Lead, Plastic J-Leaded Chip Carrier OTP (PLCC)
28KW	28 Lead, Windowed, Ceramic J-Leaded Chip Carrier (JLCC)
28LW	28 Pad, Windowed, Ceramic Leadless Chip Carrier (LCC)
28L	28 Pad, Non-Windowed, Ceramic Leadless Chip Carrier OTP (LCC)
24P3	24 Lead, 0.300" Wide, Plastic Dual Inline Package OTP (PDIP)
24CW	24 Lead, Windowed, Ceramic Flat Package (Cerpack)

