

E-Series 2-Way 90° Power Divider

20 - 23 MHz

EQSM-2-21.4

V3.00

Features

- 2 Way
- 90°
- Surface Mount

Specifications @ 25°C

Frequency Range		20 - 23 MHz
Insertion Loss	Typical	Maximum
20 - 23 MHz	0.4 dB	0.7 dB
Isolation	Typical	Minimum
20 - 23 MHz	30 dB	25 dB
Amplitude Unbalance		Maximum
20 - 23 MHz		1.2 dB
Phase Unbalance		Maximum
20 - 23 MHz		3°

Operating Characteristics

Impedance	50 Ohms Nominal
-----------	-----------------


Ordering Information

Part No.	Packaging
EQSM-2-21.4	Tube
EQSM-2-21.4TR	Forward Tape & Reel

Absolute Maximum Ratings

Parameter	Absolute Maximum
Maximum Power Rating	1 Watt
Internal Load Dissipation	0.125 Watt
Pin Temp (10 sec)	260°C
Storage Temperature	-55°C to 100°C

SM-1



Dimensions in () are in mm.
Unless Otherwise Noted: .x = ±0.04 (1.00)
.xx = ±0.02 (0.50)
.xxx = ±0.010 (0.250)

Pin Configuration

Function	Pin No.
Not Connected	2,5
External 50 Ohms	3
Input	1
Port 1	4
Port 2	6

S 0226 B