

Dimensions mm[inch]
 tolerances acc. to DIN ISO 2768-m
 Toleranzen gem. DIN ISO 2768-m

Isometric
 Scale 1:2
 Maßstab 1:2

Cable
 flat cable LIYZ 2x0,14 mm², white
 Flachbandkabel LIYZ 2x0,14 mm², weiss

Terminals/Connector
 ends tinned
 Enden verzinkt

Schematic

R = 33 Ohm
 Tol. = 1%
 P = 0,6 W
 Type 0207

Marking
 according to EN60062/factory code
 gem. EN60062/Fertigungsstätte

Magnetic properties	Conditions	Min	Typ	Max	Unit
Pull-In	at 20 °C	21		40	AT
Test equipment		KMS13+PK002+SA002			

Special Product Data	Conditions	Min	Typ	Max	Unit
Contact - No.		66			
Contact - form		A - NO			
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			10	W
Switching voltage	DC or Peak AC			180	V
Carry current	DC or Peak AC			1,25	A
Switching current	DC or Peak AC			0,5	A
Sensor-resistance	measured with 40% overdrive			37,4	Ohm
Housing material		PBT glass fibre reinforced			
Case colour		white			
Sealing compound		Polyurethan			
Remark		resistor R 33 Ohm; 1%; 0,6 W; type 0207			
Remark		maximum current I _{max} = 134 mA			

Environmental data	Conditions	Min	Typ	Max	Unit
Shock	1/2 sine wave duration 11ms			50	g
Vibration	from 10 - 2000 Hz			20	g
Operating temperature	cable not moved	-30		70	°C
Operating temperature	cable moved	-5		70	°C
Storage temperature		-30		70	°C
Reach / RoHS conformity		yes			